

DECLARATION OF PERFORMANCE

No. 2021/EC-05B2/77

1. Unique identification code of the product type:

EC-05B2

2. Intended use or uses:

Double sash balcony doors with a low threshold ENERGY CONCEPT are intended for use in communication in domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin

Production facility no. 3 in Bilgoraj ul. Zamojska 165, 23-400 Bilgoraj

4. Authorised representative:

5. System of assessment and verification

3

of constancy of performance:

6a. Harmonised standard:

PN-EN 14351-1+A2:2016-10

Notified bodies:

Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:

6b. European Assessment Document:

N/A

7. Declared performance:

		Essential characteristics	Performance
Wind load			2
Test pressure P1 (Pa)			800 (Pa)
Wind load			С
Frame deflection			≤1/300
Water tightness Unprotected (A)			6A
Test pressure (Pa)			250 (Pa)
Load capacity of protective devices			350 N (threshold value)
Acoustic properties $R_w(C;C_{tr})$ (dB) Total area $\leq 2.7m^2$ $2,7m^2 < Total area \leq 3.6m^23,6m^2 < Total area \leq 4,6m^24,6m^2 < Total area$			34 (-1;-5) dB 33 (-1;-5) dB 32 (-1;-5) dB 31 (-1;-5) dB
Hazardous substances			not contain
Heat insulation	Pine	The highest value declared for window with undivided pane	npd
		Window with SGG Swisspacer pane spacer*	npd
Air permeability Max. Test pressure (Pa) Reference air permeability at 100 Pa (m³/h*m²) or (m³/h*m)			4 600 (Pa) 3 m³/h*m² 0.75 m³/h*m
Total atmospheric light transmittance g _n **			38 %
Light transmittance L _t **			59 %

^{* -} for window dimensions 1.48 X 2.18 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Monika Dudek-Stachal Lublin, 21.06.2021 (place and date of issue)

mgr Monika Dudék-Stachal Signature

Dyrektor Techniozny

Declaration of Performance is available on www.pol-skone.eu

^{** -} for glazing unit: PlanithermOne 4mm/16 Ar/Planiclear 4mm/16 Ar/ PlanithermOne 4mm, Ug=0,5 W/m²K