

DECLARATION OF PERFORMANCE

No. 2021/DR-10W1/104

 Unique identification code of the product type: DR-10W1

2. Intended use or uses:

Single sash windows 2+1 DUO ROYAL are intended for use in

communication in domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin

Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj

4. Authorised representative:

_

5. System of assessment and verification of constancy of performance:

3

6a. Harmonised standard:

PN-EN 14351-1+A2:2016-10

Notified bodies:

Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:

6b. European Assessment Document:

N/A

7. Declared performance:

		Performance	
Wind load			npd
Test pressure P1 (Pa)			
Wind load			npd
Frame deflection			9A
Water tightness Unprotected (A) Test pressure (Pa)			(750 Pa)
Load capacity of protective devices			350 N (thershold value)
Acoustic properties R _w (C;C _{tr}) (dB)			npd
Hazardous substances			not contain
Heat insulation	Pine	The highest value declared for window with undivided pane	1,2 (W/m ² K)
		Window with blinds and with Chromatech Ultra pane spacer*	1,0 (W/m ² K)
		Window without blinds with Chromatech Ultra pane spacer*	1,1 (W/m ² K)
Air permeability Max. Test pressure (Pa) Reference air permeability at 100 Pa (m³/h*m²) or (m³/h*m)			4 (600 Pa) (3m³/h*m²) (0,75m³/h*m)
Total atmospheric light transmittance g _n **			54%
Light transmittance L _t **			76%

^{* -} for window dimensions 1,23 x 1,48 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Lublin, 21.06.2021 (place and date of issue) Dyrektor Techniozny

Morika Dudek-Stachal

Monthe Durch - Nechol
Signature

Declaration of Performance is available on www.pol-skone.eu

^{** -} for glazing unit: 4 Float/16 Ar/4 Thermofloat 1,0, Ug=1,0 W/m²K