

1. Unique identification code of the product type: **AL-06W1**
2. Intended use or uses: Single sash windows **TYP C PLUS ALU - EFFECT** are intended for use in communication in domestic and commercial locations
3. Producer: POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin
Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj
4. Authorised representative: —
5. System of assessment and verification of constancy of performance: 3
- 6a. Harmonised standard: PN-EN 14351-1+A2:2016-10
- Notified bodies:
Instytut Techniki Budowlanej (Notified Body No. 1488) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:
Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:
- 6b. European Assessment Document: N/A
7. Declared performance:

Essential characteristics		Performance
Wind load Test pressure P1 (Pa)		npd
Wind load Frame deflection		npd
Water tightness Unprotected (A) Test pressure (Pa)		E900 (900 Pa)
Load capacity of protective devices		350 N (threshold value)
Acoustic properties** $R_w(C;C_{tr})$ (dB) Total area $\leq 2.7m^2$ $2.7m^2 < \text{Total area} \leq 3.6m^2$ $3.6m^2 < \text{Total area} \leq 4.6m^2$ $4.6m^2 < \text{Total area}$		33 (-1;-6) dB 32 (-1;-6) dB 31 (-1;-6) dB 30 (-1;-6) dB
Hazardous substances		not contain
Heat insulation	Pine	The highest value declared for window with undivided pane
		Window with Chromatech Ultra pane spacer *
Air permeability Max. Test pressure (Pa) Reference air permeability at 100 Pa ($m^3/h \cdot m^2$) or ($m^3/h \cdot m$)		4 (600 Pa) ($3m^3/h \cdot m^2$) ($0.75m^3/h \cdot m$)
Total atmospheric light transmittance g_n^{**}		41 %
Light transmittance L_t^{**}		65 %

* - for window dimensions 1.23 X 1.48 m

** - for glazing unit: Thermofloat 1,0 4mm/14 Argon/Float 4mm/14 Argon/ Thermofloat 1,0 4mm, $U_g=0,6 W/m^2K$

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Monika Dudek – Stachal
 Lublin, 21.06.2021.
 (place and date of issue)

Dyrektor Techniczny

 mgr Monika Dudek-Stachal
 Signature