

Better Interior



PRODUCT
CATALOGUE
2023



PRODUCT CATALOGUES

WOODEN, WOOD
AND ALUMINIUM
WINDOWS



ENTRANCE
DOORS,
TECHNICAL
DOORS



PRODUCTS WITH
A PRODUCTION TIME
OF UP TO 10 DAYS



CONTENTS

WHAT MAKES US UNIQUE	4	SONATA LUX	104
SYMBOLS AND THEIR MEANINGS	5	INTERSOLID	106
DIMENSIONS OF INTERIOR DOOR LEAVES	6	INTERSOLID II	108
COLOURS OF INTERIOR DOOR LEAVES	7	PASSO	110
METAL/ALUMINIUM DOOR FRAMES COLOUR PALETTE	11	ESTATO LUX	112
COLOURS OAKEN THRESHOLDS	11		
ADDITIONAL INFORMATION'S	12	SLIDING DOOR	
DOOR GLASS	12	SLIDING SYSTEM FOR IN-WALL INSTALLATION	114
REVES SYSTEM	13	SLIDING SYSTEM ON-WALL	116
RECUPERATION SYSTEM	14	SLIDING SYSTEM ON-WALL PREMIUM	118
HARMONY SYSTEM POL-SKONE CONCEALED DOOR LEAF (SLAB)	15	SLIDING SYSTEM ON-WALL MOVI	119
HARMONY SYSTEM POL-SKONE CONCEALED DOOR FRAME	16		
FLEXI POL-SKONE SYSTEM FOR HARMONY		SPECIAL DOOR	
CONCEALED DOOR FRAME	17	GALIO – NEW	120
HARMONY INVEST PRO FOR PANEL INSTALLATION	18	STALIO – NEW	122
HARMONY INVEST	20	LUMEN	124
HARMONY INVEST ULTRA – NEW	22	LUMEN LOFT – NEW	126
		FOLDING	128
		SOUNDPROOF	130
INTERIOR DOOR			
PAINTED		DOOR FRAMES	
FIORD	24	MDF FIXED	132
CAMBIO	26	POL-SKONE FIXED	133
SIMPLE	28	DIN SYSTEM ADJUSTABLE	134
SUBITO	30	DOOR FRAME	134
SUBLIME	32	AQUA DIN ADJUSTABLE – NEW	135
TIARA	34	POL-SKONE SYSTEM ADJUSTABLE	136
ESTATO	36	LUMEN METAL FIXED	137
PALAZZO – NEW	38	LUMEN METAL ADJUSTABLE	138
VERTIGO	40	POL-SKONE SYSTEM METAL DIAGONAL FIXED	139
VILANO	42	POL-SKONE SYSTEM METAL DIAGONAL ADJUSTABLE	140
MODERN	44	POL-SKONE SYSTEM METAL FIXED	141
MODENA	46	POL-SKONE SYSTEM METAL ADJUSTABLE	142
MODESTO – NEW	48	DUO SYSTEM FIXED	143
		DIN DUO SYSTEM ADJUSTABLE	144
ECO TOP HIGH TOP		AQUA DIN DUO ADJUSTABLE – NEW	145
LOFTY	50	DUO SYSTEM ADJUSTABLE	146
ARCO	52	VERTIGO ADJUSTABLE	147
INTER-AMBER	54	POL-SKONE SYSTEM METAL DUO FIXED	148
		POL-SKONE SYSTEM METAL DUO ADJUSTABLE	149
UNI MAT PLUS		REVES SYSTEM ADJUSTABLE	150
SEDO	56	ADJUSTMENT SYSTEM MADE OF MDF FOR FIXED METAL	151
CREATO	58		
HAPTIC	60	TUNNELS / WALL ENCASEMENTS	152
ARIA – NEW	62	TOPLIGHTS FOR DIN/DIN DUO DOOR FRAME	154
		TOPLIGHTS FOR THE FIXED DOOR FRAME	155
LAMISTONE SILKSTONE LAMINATED		SEMPRE INTERIOR DOOR SIDE PANELS	155
ESTO – NEW	64	STRIPS	156
MODO	66	BASEBOARDS	156
VERI	68	ABS EDGING	156
EGRO	70	PORTHOLES	157
FIORI	72	CROWNS	157
IMPULS	74	VENTILATION OPTIONS	158
ETIUDA	76	STAINLESS STEEL PROTECTORS	161
SONATA	78	ACCESSORIES	162
FORTIMO	80	HANDLES FOR INTERIOR DOORS	164
INVERNO	82		
NOSTRE	84		
MONA	86		
SEMPRE	88		
DECO	90		
PASSO	110		
		ATTENTION!	
VENEERED		WE WILL SOON INTRODUCE NEW PRODUCT CODES (NEW DOOR VERSIONS)	
SEMPRE LUX	92	You will already find them next to the icons of the individual door models, e.g.:	
TEO – NEW	94	old code → W02 / V4S4 ← new code	
ESPINA	96		
DECO LUX	98		
ETIUDA LUX	100		
FORTIMO LUX	102		

WHAT MAKES US UNIQUE

POL-SKONE FACTORIES



Z1 LUBLIN



Z4 LUBLIN



Z2 NIEMCE



Z3 BIŁGORAJ

VISION

As a Polish family company, we want to be the first choice brand in the premium segment.

MISSION

We are a manufacturer of doors and windows of the highest quality. We are building a strong brand associated with reliability, modern design and technological innovation.

We are a family-owned company, we care about long-term relationships with our business partners, and we treat our employees as our most valuable asset.



FSC® Certificate

Over the last 33 years, POL-SKONE has received many awards and certificates acknowledging the highest quality of services and products.

One of the most important distinctions is the international FSC® (Forest Stewardship Council®)

The FSC® certificate confirms that the raw materials used for the production come only from certified forests, managed in accordance with the law, good environment protection practices, principles of economy and with respect for the locally recognised social values.

SYMBOLS AND THEIR MEANINGS

STRUCTURE

The POL-SKONE door leaves are designed based on various structures and in-fills to be able to fulfil the requirements of various Customers and meet their needs.



Leaf (slab) STRUCTURE
wooden rail and stile
unit, honeycomb-like in-fill



Leaf (slab) STRUCTURE
wooden rail and stile
unit, perforated chipboard in-fill



Leaf (slab) STRUCTURE
wooden rail and stile
unit, solid chipboard in-fill



Leaf (slab) STRUCTURE
glued laminated wood




Leaf (slab) STRUCTURE
high quality MDF board



Leaf (slab) STRUCTURE
special POL-SKONE structure

DIMENSIONS

For the standard dimensions of interior leaves, go to page 6 (some models are additionally available in non-standard dimensions). For information on dimension ranges and door frames for relevant door models, go to the pages containing their respective descriptions.



"60"- "110"
SINGLE LEAF (SLAB) DOORS
(range of dimensions)



"120"- "180"
DOUBLE LEAF (SLAB) DOORS
(range of dimensions)

IN-FILL



"honeycomb"



perforated chipboard



solid chipboard

ATTRIBUTES



NEW
new products in the POL-SKONE line



FAST DELIVERY
door production takes 10 working days + delivery to customer



BESTSELLER
most popular door models



CHOICE OF DEVELOPERS
products recommended by experts

SYSTEMS

The configuration in which the door frame is connected to the leaf (slab) includes the rebated system and the non-rebated system. The former has a rabbet (groove) which overlaps the door frame; in the latter one, the leaf (slab) edge and the door frame form a uniform plane. The unique Harmony system uses a door frame concealed in the wall. POL-SKONE also offers a sliding system door.



REBATED SYSTEM

the leaf (slab) has a rabbet (groove) which overlaps the door frame



NON-REBATED SYSTEM

the straight leaf (slab) edge and the door frame form a uniform plane



REVES SYSTEM

the leaf (slab) has a reverse groove (notch) which is coplanar with the frame



HARMONY SYSTEM

a system with a door frame concealed in the wall



SLIDING SYSTEM

available for the sliding system

SPECIFICATIONS

POL-SKONE offers doors with special technical properties.



soundproof doors



flame retardant door



anti-burglar doors



mechanical class
I, II, III or IV



thermal transmittance



smoke control doors




resistance to climatic conditions



RTG

DIMENSIONS OF INTERIOR DOOR LEAVES




the POL-SKONE rebated door leaves fit all door frames which comply with the Polish industry standards

width (Ss)					height in rebate
618	718	818	918	928* (mm)	2020 (mm)


*width "90 plus"

Full range of dimensions of interior doors with door frames – p. 132-151
HANDLE HEIGHT




Height of handle for the rebated door standard height – 1040 mm from the leaf (slab) bottom edge


**SYMMETRY
IS PARAMOUNT**
STANDARDISED
HANDLE HEIGHT IN
REBATED AND NON-
REBATED SYSTEM




Height of handle for the not-rebated door standard height – 1040 mm from the leaf (slab) bottom edge



CLEARANCE BETWEEN LEAF (SLAB) AND FLOOR























version with Swiss threshold (option)



Dimensions of interiors entrance doors and exterior doors are provided on pages dedicated to the particular models of these doors.

COLOURS OF INTERIOR DOOR LEAVES

ECO TOP A surface that provides the perfect combination of price and quality for long term household use.	HIGH TOP ECO TOP surface finish with additional real wood grain effect.	UNI MAT PLUS Reinforced surface with silky tactile experience and special fingerprint-proof coating.	LAMISTONE CPL Surface finish with protective coating for resistance to wear and chemicals. Recommended for public utility buildings and applicable to intensive door use conditions, e.g. in hotels and offices.	SILKSTONE LAMISTONE CPL surface finish with additional unique real wood grain effect.
SILKSTONE CPL 0,5 mm Surface finish featuring the properties and resistance of the CPL 0.5 laminate with additional unique real wood grain effect. Recommended for public utility buildings and applicable to intensive door use conditions, e.g. in hotels and offices.	LAMINATED Highly resistant surface finish recommended for public utility buildings and applicable to intensive door use conditions, e.g. in hotels and offices. Differences in colour shades of door leaves, door frames and spacer frames are acceptable.	VENEERED The POL-SKONE veneered doors are coated with environment-friendly UV varnish. It is certainly more resistant to scratches and light than standard varnishes, including those laid in multiple layers. The actual colour shades and wood grain of veneers may vary since natural veneers are used.	PAINTED Environment-friendly acrylic paints, RAL and NCS colours* (except the metallic ones) – available at an extra charge according to the colour specification table for particular models.	

ECO TOP	 120 white	 121 oak	 132 walnut	 135 English oak	 141 Salinas oak
	 158 honey oak	 159 delano oak	 160 sonoma oak	 161 halif oak	
HIGH TOP	 148 coffee ash				
UNI MAT PLUS	 640 graphite	 641 titano	 642 white	 643 beige	 644 black
	 645 lava	 646 stone	 647 indigo	 648 moss	 NEW 649 sage

* available upon consultation with the Sales Department
The actual colours may vary from the colours printed in the catalogue. Differences in colour shades of door leaves, door frames and spacer frames are acceptable.

LAMISTONE
CPL



231 halif oak



240 whitewashed elm V



241 sand elm V



242 grey elm V



243 delano oak




244 black



247 industry 1



250 terra oak



258 white



260 white oak



263 premium walnut



265 wenge



289 grey



531 anthracite



232 segato walnut

SILKSTONE



230 gran oak



254 Royal anthracite H



255 Polish ash H



276 Polish oak



293 Royal anthracite



294 Royal ash



295 Royal merbau



296 Polish ash



297 Royal nougat



299 Royal ash H

SILKSTONE
CPL 0,5 mm*



976 Polish oak



993 Royal anthracite



994 Royal ash



995 Royal merbau




996 Polish ash




997 Royal nougat

**LAMINATED
CPL 0,2 mm**



820 white



222 grey



225 terra oak



227 delano oak



229 oak



280 halif oak



821 anthracite



844 black



849 industry 3**



863 premium walnut



228 segato walnut

**LAMINATED
CPL 0,5 mm***



945 white structure



252 oak



922 grey structure



926 anthracite structure



965 wenge



963 premium walnut




946 black structure



961 halif oak

**LAMINATED
CPL 0,7 mm***



745 white structure



722 grey structure



779 oak



726 anthracite structure



765 wenge



763 premium walnut




746 black structure



761 halif oak

**LAMINATED
HPL***




HPL colours apply to:
HARMONY INVEST,
DECO, FOLDING DOOR,
SOUNDPROOF DOOR, CERBER
PLUS, CERBER PLUS RC2, B-30,
C-30, RC3, RC3 INVEST, RC4,
RC4EI30.


* available upon consultation with the Sales Department.


** colours available while stocks last

The actual colours may vary from the colours printed in the catalogue. Differences in colour shades of door leaves, door frames and spacer frames are acceptable.

VENEERED
GROUP A









311 bright oak


312 swiss pine


334 European oak


VENEERED
GROUP B












323 rustic oak


340 ebony


351 marrone


376 steel oak


390 natural walnut











404 dark walnut


405 bright walnut


421 cappuccino


422 mocca

424 teak

VENEERED
GROUP C








370 white-stained oak

450 white matt


451 black matt


VENEERED
GROUP D




460 makassar


PAINTED








NEW





001 white (RAL 9003)


0M6 beige matt
(NCS s2005 Y50R)

0M5 grey matt
(RAL 7047)

003 sage
(NCSs4010-G50Y)

RAL and NCS colours*

BLACK



002 black (RAL 9005)

*NCS colours – upon consultation with the Sales Department

Colour samples and colour charts available on the market should be treated as illustrative. They may differ slightly from the final colour and shall not constitute grounds for complaint, unless the colour/painting has been approved in advance in consultation with the manufacturer. In order to verify the actual colour, a test painting must be ordered.

RAL PALETTE – division of colours according to the colour intensity grade (not applicable to the metal door frame). RALcolour palette for metal door frames – p. 11


GROUP I extra charge acc. to the extra charge table																													
6020 7002 7042 8000 9002																													
GROUP II extra charge acc. to the extra charge table																													
1000 1001 1002 1012 1013 1014 1015 1020 3011 3016 4002 4006 5001 5002 5005 5007 5008 5009 5010 5012 5013 5015 5017 5019 5022 5024 6000 6001 6004 6005																													
6007 6009 6012 6013 6014 6015 6016 6021 6022 6024 6026 6028 6029 6032 6034 7000 7001 7003 7004 7005 7006 7008 7009 7010 7011 7012 7013 7015 7016 7021																													
7022 7023 7024 7026 7030 7031 7032 7033 7034 7035 7036 7037 7038 7039 7040 7043 7044 7045 7046 7047 8001 8003 8007 8008 8011 8014 8015 8016 8017 8019																													
8022 8023 8025 8027 8028 9001 9010 9016 9018																													
GROUP III extra charge acc. to the extra charge table																													
1011 1021 1027 1037 2011 3009 3012 3013 3014 3015 4010 5003 5004 5011 5014 5018 5021 6002 6006 6008 6010 6017 6018 6025 6027 6033 8002 8004 8012																													
GROUP IV extra charge acc. to the extra charge table																													
1007 1016 1018 1032 2000 2004 3000 3002 3017 3018 3027 4001 4004 4005 4007 4008 4009 5000 5023 6023 6011 6019 6031 8024																													
GROUP V extra charge acc. to the extra charge table																													
1003 1004 1005 1006 1017 1019 1023 1024 1028 1033 1034 2001 2002 2003 2008 2009 2010 2012 3001 3020 3028 3031 6037																													

METAL/ALUMINIUM DOOR FRAMES


COLOUR PALETTE

Standard colours available in standard surface finish SEMI-MATT


STANDARD COLOURS




RAL 9003 (white)




RAL 9005 (black)




RAL 9016 (white)




RAL 7047 (grey)




RAL 1001 (beige)




RAL 8014 (brown)




RAL 7024 (graphite)



OS1
RAL 9003
structure



OS2
RAL 9005
structure



OS0
anthracite
structure

RAL COLOUR SURCHARGE TABLE
FOR DOOR METAL FRAMES
no possibility to make door frames in NCS coulors

Colour group
GROUP I
GROUP II
GROUP III
GROUP IV
GROUP V

SURCHARGE TABLE - STRUCTURES

Extra charge to the basic price of the metal frame

rebated system
non-rebated system
HARMONY in colour RAL 9003, RAL 9005

STALIO, GALIO doors



OS1
RAL 9003
structure



OS2
RAL 9005
structure



OS0
anthracite
structure



OS3
copper
structure

The range of entrance and exterior doors and technical doors is available in separate publications.

RAL COLOUR PALETTE (applies to metal and aluminium door frames)

GROUP I																															
1000	1002	1011	1013	1015	1019	1020	3009	4001	5000	5001	5004	5005	5007	5008	5009	5010	5011	5013	5014	5017	5019	5020	5021	5022	5023	5024	6000	6003	6004		
6005	6006	6007	6008	6011	6012	6013	6014	6015	6019	6020	6026	6027	6033	6034	7000	7001	7002	7003	7004	7005	7006	7008	7009	7010	7011	7012	7013	7015	7016		
7021	7022	7023	7026	7030	7031	7032	7033	7034	7035	7036	7037	7038	7039	7040	7042	7043	7044	7045	7046	8000	8001	8002	8003	8004	8007	8011	8012	8015	8017		
8019	8022	8023	8025	8028	9001	9002	9010	1024HR 6021HR 9004HR 9005HR																							
GROUP II																															
1014	3000	3001	3002	3004	3007	3011	3013	3016	4002	4008	5002	5003	5012	5015	5018	6017	6022	6025	6029	9018	3031HR 4005HR 4006HR 6002HR 8008HR										
GROUP III																															
3003	3005	3020	3022	6010	6018	6024	1024HR 4004HR 4010HR 6032HR																								
GROUP IV																															
3012	3014	6001	6028	3027HR 4003HR 4007HR 6037HR																											
GROUP V																															
1003	1004	1005	1006	1016	1017	1018	1021	1023	1027	1032	1033	1034	1037	2000	2001	2002	2004	2009	2010	2011	2012	3018	9006	1027HR	1028HR	2003HR	2008HR	3028HR			

The RAL colouring of metal frames and aluminium frames differs from the RAL colouring of painted door leaves due to the different material application technology.

COLOURS

OAKEN THRESHOLDS

applicable to models CERBER PLUS, CERBER PLUS RC2, B-30, C-30, RC3 and RC4



varnished oaken threshold,
silver-coloured ALU strip
(standard)



varnished grey-coloured oaken
threshold, silver-coloured ALU
strip (optional)




varnished brown-coloured oaken
threshold, black-coloured ALU
strip (optional)



varnished black-coloured oaken
threshold, black-coloured ALU
strip (optional)


ADDITIONAL INFORMATIONS

CONNECTION OF STRIPS




A, B VERSION

architraves interconnected at the 45° angle,
width: 60 mm
architraves interconnected at the 45° angle,
width: 80 mm





B 90° VERSION

architraves interconnected at the 90° angle,
width: 80 mm (applicable to DIN B version,
DUO and DIN DUO door frame)







C 90° VERSION

architraves interconnected at the 90° angle,
width: 80 mm (applicable to DIN B version
and DIN DUO door frame)




DOOR GLASS


See which side is the matt side of the glass



SLIDING SYSTEM FOR IN-WALL INSTALLATION




SLIDING SYSTEM FOR IN-WALL INSTALLATION left-hand door



ON-WALL SYSTEM left-hand door





REVES SYSTEM



leaf (slab) in the REVES system (left side), right-hand - opened inwards;
leaf (slab) in the DUO system (right side), left-hand - opened outwards

Door made of a **wooden rail and stile set** topped with two HDF boards. The standard in-fill is a honeycomb-like layer. Perforated chipboard infill and solid chipboard infill available at an extra charge. REVES leaf (slab) available as glazing models: IMPULS W13, IMPULS W14, ESTATO A01, ESTATO A02, ESTATO A03, ESPINA W01, CREATO A01, CREATO A02, CREATO A03, ESTATO LUX A01, ESTATO LUX A02, ESTATO LUX A03. REVES leaf (slab) available as flush models (without glazings): CAMBIO, SIMPLE, SUBLIME, TIARA, VERTIGO, VILANO, MODERN, MODENA, LOFTY, INTER AMBER, HAPTIC, IMPULS, SONATA, INVERNO, NOSTRE, DECO, ESPINA, DECO LUX, SONATA LUX, ESTATO, CREATO, ESTATO LUX, PALAZZO.


The combination of the DUO and REVES systems gives new interior arrangement opportunities. It enables the door opening in various directions to have an identical appearance when seen from the corridor side. The plane surface in both systems is flush with the door frame surface, forming a single plane with it. The hinges remain concealed and therefore the difference in their structure will not be visible from the corridor side.



DUO concealed hinge, silver colour
- DUO system



TE concealed hinge, silver colour
- REVES system



leaf (slab) in the REVES system (left side), right-hand - opened inwards; leaf (slab) in the DUO system (right side), left-hand - opened outwards

model REVES door frame p. 150

EQUIPMENT

STANDARD


magnetic mortise lock, key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
concealed: concealed TE satin chrome ("60"- "80" - 2 pcs, "90"- "100" - 3 pcs)
architraves interconnected at the 45° angle only
electric action door strike is not available

ADDITIONAL (available at an extra charge)

perforated chipboard in-fill
solid chipboard in-fill (third hinge recommended)

drop seal

third hinge in the door leaf (slab):
concealed TE for a width of "60"- "80"
standard chrom satin coloured lock replaced with white or black colour
standard silver-coloured lock replaced with black-coloured or polished golden-coloured one
door higher by 50 mm or 100 mm (third hinge recommended)
door higher by 200 mm (third hinge recommended) Cambio 00, Loft, Inter Amber A00, Haptic 00, Impuls W01, Deco 00, Deco Lux 00
door lower by 55 mm or 100 mm
maximum height of door with the REVES frame - 2288 mm




INTERIOR DOOR FOR ROOMS WITH A **RECUPERATION** SYSTEM



recuperation trim

The following models include doors with a recuperation trim: CAMBIO, SIMPLE, TIARA, INTER-AMBER, IMPULS, SONATA, INVERNO, NOSTRE, DECO, DECO LUX, HARMONY, SUBLIME, VILANO, VERTIGO, FIORD, MODERN, MODENA, HAPTIC. Recuperation trim for doors: ARCO, SEDO, MODO, VERI, EGRO, FIORI, FORTIMO, MONA, SEMPRE, SEMPRE LUX, FORTIMO LUX (Applicable to the standard height) at extra charge



The door leaves are 15 mm shorter than the standard height, i.e. 2005 mm (rebated system) and 2025 mm (non-rebated system and HARMONY opened inwards), 2035 mm (HARMONY opened outwards); the door frame height remains standard.



The door compatible with a recuperation system is available at a standard door price. In the www.drzwionline.pl configurator, the RECUPERATION TRIM option can be selected only when the standard height leaf (slab) and door frame are selected as a complete set.



recuperation trim in CAMBIO door, version 00, SYSTEM DIN adjustable frame



HARMONY SYSTEM POL-SKONE

CONCEALED door leaf (slab)

THE BEST OFFER ON THE MARKET

HARMONY IDEA* leaf (slab) for self-painting + ALU door frame raw for self-painting (applies to door leaf (slab) width "60"- "90" cm x height 2040/2050 mm honeycomb filling)



***single leaf (slab) door with hidden frame HARMONY with solid chipboard in-fill, equipped with a dropping seal, has the following parameters sound insulation power $R_w=27$ dB**

SPECIFICATIONS

Mechanical resistance requirements class 2, i.e. average service conditions

Leaf (slab) STRUCTURE

Non-rebated system leaf (slab) (opened outwards) or with a notch (opened inwards). The door leaf (slab) structure consists of a **rail and stile set** made of **coniferous wood**, topped with HDF boards on both sides. The leaf (slab) in-fill consists of a "honeycomb" type cellular cardboard, perforated or solid chipboard. The rated thickness of the door leaf (slab) is 40 mm.

The door leaf (slab) is designed in such a way that it can be installed flush with the door frame surface.

DOOR Leaf (slab) FINISH

HARMONY IDEA smooth surface, prime-coated for DIY painting, laminated, painted or veneered.

ACCESSORIES

Standard equipment:

concealed hinge (adjustable in 3 planes)

key-operated, cylinder or bathroom type magnetic lock

Auxiliary equipment (available at an extra charge):

perforated chipboard in-fill

solid chipboard in-fill

drop seal

additional hinge in the door leaf (slab)

ventilation trim (p. 159)

HOBES 2784 roller lock

preparation for an additional hinge (extra charge to the door leaf (slab))

for other door dimensions – contact the Sales Department

recuperation trim

Adapting the leaf (slab) for mounting a mirror or tile 4 mm thick on one side

(full plate and additional hinge required. Number of hinges "60-80" - 3 pcs,

"90-100" - 4 pcs. It is recommended to install the handle on the split shaft).

Maximum height of door - leaf (slab) adapted to mirror is 2240/2250 mm.

HARMONY door leaf (slab) trimmed every 10 mm is available

Double leaf (slab) door with an asymmetric division line is available on request

WIDTH

single leaf (slab) door				double leaf (slab) door				
type	S_d^*	S_d^{**}	S_o	type	S_d^*	S_o^*	S_d^{**}	S_o^{**}
"60"	696	693	710	"60"+"60"	1315	1330	1309	1325
"70"	796	793	810	"70"+"70"	1515	1530	1509	1525
"80"	896	893	910	"80"+"80"	1715	1730	1709	1725
"90"	996	993	1010	"90"+"90"	1915	1930	1909	1925
"100"	1096	1093	1110	"100"+"100"	2115	2130	2109	2125

HEIGHT

		H_d	H_o
		2092*	2100*
		2082**	2090**


* door openable inwards ** door openable outwards

S_d – door frame external width

S_o – installation hole width

H_d – door frame external height

H_o – installation hole height



DOOR LEAF (SLAB) FOR THE HARMONY DOOR FRAME

leaf (slab) dimensions

HARMONY IDEA – open to your design ideas

HARMONY IDEA

raw door leaf (slab) prepared for do-it-yourself painting

LAMISTONE
SILKSTONE
UNI MAT PLUS

PAINTED
white, beige, grey
white hinges

BLACK
RAL 9005
black hinges

VENEERED

GROUP A

GROUP B

GROUP C

"60" - "90" x 2040/2050 mm

"100" x 2040/2050 mm

"60" - "90" x 2140/2150 mm

"100" x 2140/2150 mm

"60" - "90" x 2240/2250 mm

"100" x 2240/2250 mm


"60" - "90" x 2340/2350 mm

"100" x 2340/2350 mm


"60" - "90" x 2440/2450 mm

DOUBLE LEAF (SLAB) DOOR


A. Left door opened inwards




B. Right door opened inwards



C. Left door opened outwards



D. Right door opened outwards



HARMONY SYSTEM POL-SKONE

CONCEALED door frame



PATENTED COMBINATION



opened inwards



opened outwards

DOOR FRAME - COLOURS

Concealed door frame for inwards or outwards opened doors. Made from anodised aluminum, raw aluminium for do-it-yourself painting in the colour of the wall or painted in white (RAL 9003), black (RAL 9005).

ACCESSORIES

Standard equipment:
concealed hinge (adjustable in 3 planes) - satin chrome colour – quantity of hinges as per table
key-operated, cylinder or bathroom type magnetic lock

Auxiliary equipment (available at an extra charge):
door frames in metallic colours (p. 11)
concealed hinge for the Harmony door frame in the colour of white, black or silver
door frame adaptation to the HOBES 2784 roller lock
door frame available with averse or reverse action electric strike – contact with the Sales Department

HARMONY door frame trimmed every 10 mm is available

HARMONY DOOR FRAME FOR SINGLE LEAF (SLAB) DOOR

door leaf (slab) dimensions and the number of hinges	for do-it-yourself painting (raw aluminum)	anodized aluminum	PAINTED white, beige, grey white hinges
			BLACK RAL 9005 black hinges
"60"- "80" x 2040/2050 mm (2 concealed hinges)			
"90"- "100" x 2040/2050 mm (3 concealed hinges)			
"60"- "100" x 2140/2150 mm (3 concealed hinges)			
"60"- "100" x 2240/2250 mm (3 concealed hinges)			
"60"- "100" x 2340/2350 mm (4 concealed hinges)			
"60"- "100" x 2440/2450 mm (4 concealed hinges)			

HARMONY DOOR FRAME FOR DOUBLE LEAF (SLAB) DOOR

door leaf (slab) dimensions and the number of hinges	for do-it-yourself painting (raw aluminum)	anodized aluminum	PAINTED white, beige, grey white hinges
			BLACK RAL 9005 black hinges
"60"+ "60", "70"+ "70", "80"+ "80" x 2040/2050 mm (4 concealed hinges)			
"90"+ "90", "100"+ "100" x 2040/2050 mm (6 concealed hinges)			
"60"+ "60", "70"+ "70", "80"+ "80", "90"+ "90", "100"+ "100" x 2140/2150 mm (6 concealed hinges)			
"60"+ "60", "70"+ "70", "80"+ "80", "90"+ "90", "100"+ "100" x 2240/2250 mm (6 concealed hinges)			
"60"+ "60", "70"+ "70", "80"+ "80", "90"+ "90", "100"+ "100" x 2340/2350 mm (8 concealed hinges)			
"60"+ "60", "70"+ "70", "80"+ "80", "90"+ "90", "100"+ "100" x 2440/2450 mm (8 concealed hinges)			

FLEXI POL-SKONE SYSTEM FOR HARMONY CONCEALED DOOR FRAME

PATENTED
DESIGN

ADJUSTMENT SYSTEM MADE OF MDF



architraves interconnected
at the 45° angle

PAINTED** white, beige, grey	BLACK RAL 9005	UNI MAT PLUS	ECO TOP	veneered	
		LAMISTONE		GROUP A (311, 312, 334)	GROUP B (323, 370, 372, 376, 390, 404, 405, 421, 422, 424)
		SILKSTONE			


HW, range in mm 85-310

HZ, range in mm 95-320

* the adjustment range includes the thickness of the HARMONY door frame
** RAL 9003, architraves 80 mm wide

COMPLETION OF COMPONENTS

adjustment range		HARMONY CONCEALED door frame	adjustment range		HARMONY CONCEALED door frame	adjustable angular architrave	panel
HW1	85-90	opened inwards HARMONY CONCEALED door frame	HZ1	95-100	opened outwards HARMONY CONCEALED door frame	12 mm	46 mm
HW2	90-95		HZ2	100-105		12 mm	51 mm
HW3	95-105		HZ3	105-115		16 mm	56 mm
HW4	105-130		HZ4	115-140		32 mm	66 mm
HW5	130-150		HZ5	140-160		32 mm	91 mm
HW6	150-170		HZ6	160-180		32 mm	111 mm
HW7	170-190		HZ7	180-200		32 mm	131 mm
HW8	190-210		HZ8	200-220		32 mm	151 mm
HW9	210-230		HZ9	220-240		32 mm	171 mm
HW10	230-250		HZ10	240-260		32 mm	191 mm
HW11	250-270		HZ11	260-280		32 mm	211 mm
HW12	270-290		HZ12	280-300		32 mm	231 mm
HW13	290-310		HZ13	300-320		32 mm	251 mm



opened inwards							opened outwards					
installation dimension	Sd	SopA	SopB	Hd	HopA	HopB	Sd	SopA	SopB	Hd	HopA	HopB
"60"	683	783	823	2086	2136	2156	663	763	803	2067	2117	2137
"70"	783	883	923				763	863	903			
"80"	883	983	1023				863	963	1003			
"90"	983	1083	1123				963	1063	1103			
"100"	1083	1183	1223	1063			1163	1203				

Maximum external height Hd 2286 mm
Maximum external height Hd 2267 mm

Sd - installation external width
SopA - architrave (60 mm) external width
SopB - architrave (80 mm) external width
Hd - installation external height
HopA - architrave (60 mm) external height
HopB - architrave (80 mm) external height



HARMONY INVEST PRO door, with HARMONY INVEST aluminium door frame and panel installation

HARMONY INVEST PRO FOR PANEL INSTALLATION

- **solid construction** – wooden rail and stile set reinforced with steel bars
- **aluminium frame**, reinforced, allowing to create a single surface of the wall panel with 4 mm thick door leaf (slab)
- **abundant colours** with the ECO TOP, LAMINATED CPL, LAMISTONE CPL, SILKSTONE, UNI MAT PLUS, VENEERED and PAINTED surface finish
- door leaf (slab) equipped with a **drop down seal**
- **Rw = 37dB acoustic insulation**
- rated **leaf (slab) thickness: 50 mm**

Entrance internal doors intended for rooms in public buildings including offices, hotels, etc.

door width opened outwards ODZP "60" - "90"

4 mechanical class according to PN-EN 1192:2001

door width opened outwards ODZP "90 plus" - "110"

3 mechanical class according to PN-EN 1192:2001

door width opened inwards ODWP "60" - "110"

3 mechanical class according to PN-EN 1192:2001

acoustic insulation: **Rw= 37 dB, D₁-35, D₂-30**



HARMONY INVEST PRO door with HARMONY INVEST aluminium door frame



HARMONY INVEST PRO DOOR Leaf (slab) AND PANEL

colours

raw for do-it-yourself painting

ECO TOP

LAMISTONE CPL

UNI MAT PLUS

SILKSTONE

SILKSTONE CPL 0,5 mm

LAMINATED CPL 0,2 mm

PAINTED white, beige, grey

BLACK RAL 9005

VENEERED GROUP A

VENEERED GROUP B

VENEERED GROUP C

SILKWOOD

panels – price per 1 m² (the exact dimensions of the panels are available upon consultation with the Sales Department)

ATTENTION! For panel heights of 2200 to 2500 mm, visible micro-glueing of the veneer.

VERSION

W00 / V00

COLOURS



*available at an extra charge upon consultation with the Sales Department


DOOR FRAMES

HARMONY INVEST PRO DOOR FRAME FOR PANEL


leaf (slab) dimensions [mm]	raw for do-it-yourself painting	ODW		raw for do-it-yourself painting	ODZ	
		PAINTED white, beige, grey	BLACK RAL 9005		PAINTED white, beige, grey	BLACK RAL 9005
625-960 x 2040/2050						
1025-1125 x 2040/2050						
625-960 x 2140/2150						
1025x1125 x 2140/2150						
625-960 x 2240/2250						
1025x1125x2240/2250						
625-960 x 2340/2350						
1025-1125 x2340/2350						
625-960 x 2440/2450						
1025-1125x 2440/2450						

surcharge for structural colors

HARMONY INVEST PRO DOOR
opened inwards for panel installation



HARMONY INVEST PRO DOOR
opened outwards for panel installation



DOOR OPENABLE INWARDS ODW

WIDTH [MM]	HEIGHT [MM]					
	Ss	Sd	So	Hs	Hd	Ho
"60"	625	715	735	1950	2002	2015
"70"	725	815	835	2050 - standard	2102	2115
"80"	825	915	935	2150	2202	2215
"90"	925	1015	1035	2250	2302	2315
"90 plus"*	960	1050	1070	2350	2402	2415
"100"	1025	1115	1135	2450	2502	2515
"110"	1125	1215	1235			

* investment width

So - installation hole width

Ss - door leaf (slab) width

Sd - door frame external width

DOOR OPENABLE OUTWARDS ODZ

WIDTH [MM]	HEIGHT [MM]					
	Ss	Sd	So	Hs	Hd	Ho
"60"	625	715	735	1940	1992	2005
"70"	725	815	835	2040 - standard	2092	2105
"80"	825	915	935	2140	2192	2205
"90"	925	1015	1035	2240	2292	2305
"90 plus"*	960	1050	1070	2340	2392	2405
"100"	1025	1115	1135	2440	2492	2505
"110"	1125	1215	1235			

Ho - installation hole height

Hs - door leaf (slab) height

Hd - door frame external height

EQUIPMENT

STANDARD

magnetic mortise lock, key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)

opened outwards: SIMONSWERK TECTUS TE 541 3D FVZ type concealed hinges, 3D adjustable ("60"- "90" – 2 pcs, "100"- "110" – 3 pcs)

opened inwards: SIMONSWERK TECTUS TE 240 3D type concealed hinges, 3D adjustable ("60"- "110" – 3 pcs)

door higher than standard - 3 pcs

drop down seal

recuperation trim*

ADDITIONAL (available at an extra charge)

CPL laminate 0.5 mm ("60" - "90")

CPL laminate 0.7 mm ("60" - "90")

CPL laminate 0.5 mm ("90+" - "110")

CPL laminate 0.7 mm ("90+" - "110")

SILKSTONE CPL colours

"100" width

"110" width

ventilation trim*

mortise sash lock

higher door - 2150/2140


higher door - 2250/2240

higher door - 2350/2340

higher door - 2450/2440

matching wall panel grain to the door as per pattern (tolerance of up to 10 mm)

*doors with ventilation trim or undercut do not have a drop seal and the declared acoustic and air permeability parameters. matching wall panel grain to the door as per pattern (tolerance of up to 10 mm)



HARMONY INVEST door, HARMONY INVEST aluminium door frame

HARMONY INVEST


- **solid construction - wooden rail and stile** set reinforced with steel bars
- **abundant colours** with the ECO TOP, LAMINATED CPL, LAMISTONE CPL, SILKSTONE, UNI MAT PLUS, VENEERED and PAINTED surface finish
- door leaf (slab) equipped with a **drop down seal**
- **Rw = 37dB acoustic insulation**
- **aluminium reinforced door frame**
- rated **leaf (slab) thickness: 50 mm**

Entrance internal doors intended for rooms in public buildings including offices, hotels, etc.

door width "60"- "90" - 4 mechanical class according to PN-EN 1192:2001
door width "90 plus" - "110" - 3 mechanical class according to PN-EN 1192:2001
acoustic insulation: **Rw= 37 dB, D₁-35, D₂-30**



HARMONY INVEST door, HARMONY INVEST aluminium door frame



VERSION W00 / V00

COLOURS

ECO TOP	HIGH TOP	LAMISTONE CPL	SILKSTONE	SILKSTONE CPL				
UNI MAT PLUS	LAMINATED CPL 0.2 mm	LAMINATED CPL 0.5 mm	LAMINATED HPL*	VENEERED GROUP A	VENEERED GROUP B	VENEERED GROUP C	SILKWOOD	PAINTED


*available at an extra charge upon consultation with the Sales Department

DOOR FRAMES

HARMONY INVEST DOOR FRAME FOR SINGLE Leaf (slab) DOOR

for do-it-yourself painting	(anodized aluminum)	PAINTED white, beige, grey	BLACK RAL 9005
(dimensions given for door leaf (slab))			
625-960 x 2040/2050 (2 concealed hinges)			
1025-1125 x 2040/2050 (3 concealed hinges)			
625-960 x 2140/2150 (3 concealed hinges)			
1025x1125 x 2140/2150 (3 concealed hinges)			
625-960 x 2240/2250 (3 concealed hinges)			
1025x1125x2240/2250 (3 concealed hinges)			
625-960 x 2340 /2350 (3 concealed hinges)			
1025-1125 x2340/2350 (3 concealed hinges)			
625-960 x 2440/2450 (3 concealed hinges)			
1025-1125x 2440/2450 (3 concealed hinges)			


HARMONY INVEST door (door openable inwards)



DOOR OPENABLE INWARDS ODZ

WIDTH [MM]				HEIGHT [MM]		
Ss	Sd	So		Hs	Hd	Ho
"60"	625	715	735	1950	2002	2015
"70"	725	815	835	2050 - standard	2102	2115
"80"	825	915	935	2150	2202	2215
"90"	925	1015	1035	2250	2302	2315
"90 plus"*	960	1050	1070	2350	2402	2415
"100"	1025	1115	1135	2450	2502	2515
"110"	1125	1215	1235			

HARMONY INVEST door (door openable outwards)



DOOR OPENABLE OUTWARDS ODZ

WIDTH [MM]				HEIGHT [MM]		
Ss	Sd	So		Hs	Hd	Ho
"60"	625	715	735	1940	1992	2005
"70"	725	815	835	2040 - standard	2092	2105
"80"	825	915	935	2140	2192	2205
"90"	925	1015	1035	2240	2292	2305
"90 plus"*	960	1050	1070	2340	2392	2405
"100"	1025	1115	1135	2440	2492	2505
"110"	1125	1215	1235			

* investment width

So - installation hole width

Ss - door leaf (slab) width

Sd - door frame external width

Ho - installation hole height

Hs - door leaf (slab) height


Hd - door frame external height

EQUIPMENT

STANDARD
magnetic mortise lock, key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
anodized aluminum door frame or for do-it-yourself painting - TECTUS TE 340 satin chrome hinges, silver hook plate
painting door frame in a colour of RAL 9003 – TECTUS TE 340 satin chrome hinges, chrome satin hook plate
painting door frame in a colour of RAL 9005 – TECTUS TE 340 black hinges, black hook plate
SIMONSWERK TECTUS TE 340 type concealed hinges (3D adjustable) ("60"- "90" – 2 pcs, "100"- "110" – 3 pcs), higher door - 3 pcs
drop down seal
recuperation trim*
ADDITIONAL (available at an extra charge)
CPL laminate 0.5 mm ("60" - "90")
CPL laminate 0.7 mm ("60" - "90")
CPL laminate 0.5 mm ("90+" - "110")
CPL laminate 0.7 mm ("90+" - "110")

*doors with ventilation trim or undercut do not have a drop seal and the declared acoustic and air permeability parameters. matching wall panel grain to the door as per pattern (tolerance of up to 10 mm)

SILKSTONE CPL colours
GEZE Boxer 2-4 concealed door closer
"100" width
"110" width
ventilation trim*
mortise sash lock
electric strikes in NC and NO versions
higher door - 2150/2140
higher door - 2250/2240
higher door - 2350/2340
higher door - 2450/2440



HARMONY INVEST ULTRA door with HARMONY ULTRA aluminium door frame

HARMONY INVEST ULTRA



- **concealed door frame without a lintel**
- **the latest trend in design, perfect matching the interiors**


- **solid construction – wooden rail and stile set** reinforced with steel bars
- **abundant colours** with the ECO TOP, LAMINATED CPL, LAMISTONE CPL, SILKSTONE, UNI MAT PLUS, VENEERED and PAINTED surface finish
- **aluminium frame**, reinforced
- **rated leaf (slab) thickness: 50 mm**

Entrance internal doors intended for rooms in public buildings including offices, hotels, etc.

door width "60" - "90" - 4 mechanical class according to PN-EN 1192:2001
door width "90 plus" - "110" - 3 mechanical class according to PN-EN 1192:2001



HARMONY INVEST ULTRA door with HARMONY ULTRA aluminium door frame



VERSION

W00

HARMONY INVEST ULTRA DOOR FRAME FOR SINGLE DOOR

leaf (slab) dimensions
[mm]

raw for
do-it-yourself
painting

anodized
aluminum

PAINTED
white

PAINTED
beige, grey

BLACK
RAL 9005

- 625-960 x 2040/2050 (2 hinges)
- 1025-1125 x 2040/2050 (3 hinges)
- 625-1125 x 2140/2050 (3 hinges)
- 625-1125 x 2240/2250 (3 hinges)
- 625-1125 x 2340/2350 (3 hinges)
- 625-1125 x 2440/2450 (3 hinges)

COLOURS

ECO TOP

HIGH TOP

LAMISTONE CPL

SILKSTONE

SILKSTONE CPL

UNI MAT PLUS

LAMINATED CPL 0.2 mm

LAMINATED CPL 0.5 mm

LAMINATED HPL*

VENEERED GROUP A


VENEERED GROUP B

VENEERED GROUP C

SILKWOOD

PAINTED

*available at an extra charge upon consultation with the Sales Department



DOOR OPENABLE INWARDS ODW / OUTWARDS ODZ						
	WIDTH [MM]			HEIGHT [MM]		
	Ss	Sd	So	Hs	Hd	Ho
"60"	625	715	735	1940	1952	1955
"70"	725	815	835	2040 - standard	2052	2055
"80"	825	915	935	2140	2152	2155
"90"	925	1015	1035	2240	2252	2255
"90 plus"	960	1050	1070	2340	2352	2355
"100"	1025	1115	1135	2440	2452	2455
"110"	1125	1215	1235			



So - installation hole width
Ss - door leaf (slab) width
Sd - door frame external width

Ho - installation hole height
Hs - door leaf (slab) height
Hd - door frame external height

* investment width - version "90 plus" allows getting a clear opening of min. 900 mm when the door leaf (slab) is opened at an angle of 90°

EQUIPMENT

STANDARD	CPL laminate 0.5 mm ("90+" - "110") CPL laminate 0.7 mm ("90+" - "110") SILKSTONE CPL colours "100" width "110" width ventilation trim mortise sash lock electric strikes in NC and NO versions higher door - 2150/2140 higher door - 2250/2240 higher door - 2350/2340 higher door - 2450/2440
ADDITIONAL (available at an extra charge)	
TECTUS TE 340 lock colour replaced with black colour CPL laminate 0.5 mm ("60" - "90") CPL laminate 0.7 mm ("60" - "90")	



FIORD door, 00 version, SYSTEM DIN DUO adjustable door frame

FIORD



- **solid construction – wooden rail and stile set**
- **3 - layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- **K and C type adjustable and DUO type concealed hinges**
- door available in **10 working days** under the "fast delivery" promotion



glazing, spacer frame



DUO concealed hinge, white – option for non-rebated system



door leaf (slab) profile



FIORD door, 00 version, adjustable door frame



VERSION	00 / V03	01 / V3S1	03 / V3S3	04 / V3SD
---------	----------	-----------	-----------	-----------

COLOURS




Applicable to Fiord 00 leaves and DIN, DIN DUO, Vertigo frames.

OPTIONAL COLOURS



RAL and NCS colours (except the metallic ones)

DOOR FRAMES



EQUIPMENT

STANDARD

white matt or transparent 4 mm thick glass
version 04: white matt tempered 4 mm thick glass
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs) in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90" – 4 pcs) - replacement
of standard hinges with hinge type T for an extra charge
BLACK collection: standard magnetic lock face plate and DUO hinges are in the colour of black

ADDITIONAL (available at an extra charge)

recuperation trim
solid chipboard in-fill (third hinge recommended)

third hinge in the door leaf (slab):
type M, type C, type K for a width of "60"- "80"
concealed DUO type for a width of "60"- "80"

the DUO hinge replaced with white or black colour

rebated system BLACK collection
the lock colour replaced with black colour

the DUO lock colour replaced with black or golden gloss colour
rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)

reinforcement for door closer



bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)

door lower by 50 mm or 100 mm (rebated system)

door lower by 55 mm or 100 mm (non-rebated system)

ventilation trim (p. 159)

tempered transparent 4 mm thick glass



CAMBIO door, 00 version, SYSTEM DIN adjustable door frame

CAMBIO



- **solid construction – wooden rail and stile set**
- **3 - layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- **K and C type adjustable and DUO type concealed hinges**



DUO concealed hinge, black – standard for the non-rebated system, collection BLACK




DUO concealed hinge, white – option for non-rebated system



leaf (slab) laminated edge in the colour of black, graphite or grey – option (not applicable to the BLACK surface)



CAMBIO door, 00 version, DIN DUO SYSTEM door frame



VERSION	00 / V00	02 / V2S	03SD / V3SD	04 / V4SD	05 / V5SD
---------	----------	----------	-------------	-----------	-----------

COLOURS



Applicable to Cambio leaves and DIN, DIN DUO and Vertigo frames.

OPTIONAL COLOURS



RAL and NCS colours (except the metallic ones)

DOOR FRAMES



POL-SKONE system fixed frame



DIN system adjustable frame



metal fixed frame



metal adjustable frame



DUO fixed frame



DIN DUO adjustable frame



VERTIGO adjustable frame



metal fixed frame



metal adjustable frame

EQUIPMENT

STANDARD

white matt or transparent 4 mm thick glass

version 03SD: white matt tempered glass

single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)

hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"-80" – 2 pcs, "90" – 3 pcs)

in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"-80" – 3 pcs, "90"-110" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge
BLACK collection: standard magnetic lock face plate and DUO hinges are in the colour of black

ADDITIONAL (available at an extra charge)

size "100" (glazing decoration as in "90")

size "110" (glazing decoration as in "90")

REVES system (version 00)

recuperation trim

perforated chipboard in-fill

solid chipboard in-fill (third hinge recommended)

third hinge in the door leaf (slab) or adjustable pivot hinge:

type M, type C, type K for a width of "60"-80"

concealed DUO type for a width of "60"-80"

the DUO hinge replaced with white or black colour

the DUO lock colour replaced with black or golden gloss colour

rebated system BLACK collection

the lock colour replaced with black colour

rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)

rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis)

reinforcement for door closer

bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)

door lower by 50 mm or 100 mm (rebated system)

door lower by 55 mm or 100 mm (non-rebated system)

door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)


door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)

ventilation trim (p. 159)

tempered glass: versions 02, 04, 05

leaf (slab) edge in the colour of black, grey or graphite

tempered transparent 4 mm thick glass



SIMPLE door, 00 version, SYSTEM DIN adjustable door frame


SIMPLE



- **solid construction – wooden rail and stile set**
- **3 - layer painting system** - colour fastness for many years
- **wide RAL and NCS colours palette**
- **K and C type adjustable and DUO type concealed hinges**



milled version view



DUO concealed hinge, white – option for non-rebated system



new type of milling



leaf (slab) laminated edge in the colour of black, graphite or grey – option (not applicable to the BLACK surface)



SIMPLE door, 02 version (door on the left side), 00 version (door on the right side), SYSTEM DIN adjustable door frame



VERSION **00 / VF0** **01 / VF1SD** **02 / VF2SD** **03 / VF4SD** **04 / VF4SM**

HIGHER DOOR

00 / V00



higher by
min. 100 mm

COLOURS



Applicable to Simple leaves and DIN,
DIN DUO and Vertigo frames.

**OPTIONAL
COLOURS**



RAL and NCS
colours
(except
the metallic
ones)

DOOR FRAMES



POL-SKONE
system fixed frame

DIN system
adjustable frame

metal fixed frame

metal adjustable
frame

DUO fixed frame

DIN DUO
adjustable frame

VERTIGO
adjustable frame

metal fixed frame

metal adjustable
frame

EQUIPMENT

STANDARD

white matt or transparent 4 mm thick glass
for the 01 and 02 model: white matt tempered glass, thickness: 4 mm
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic
mortise lock (non-rebated system), key-operated (spacing: 90 mm),
for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)

hinges: type K – for the DIN system door frame, type C – for the
wooden door frame, type M – for the metal door frame or the
concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)
in case of door leaf (slab) with door closer and DIN system or metal
frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "110" – 4 pcs) -
replacement of standard hinges with hinge type T for an extra charge
BLACK collection: standard magnetic lock face plate and DUO hinges
are in the colour of black

ADDITIONAL (available at an extra charge)

size "100" (glazing decoration as in "90")

size "110" (glazing decoration as in "90")

REVES system (version 00)

recuperation trim

perforated chipboard in-fill

solid chipboard in-fill (third hinge recommended)

third hinge in the door leaf (slab) or adjustable pivot hinge:

type M, type C, type K a width of "60"- "80"

concealed DUO type for a width of "60"- "80"

the DUO hinge replaced with white or black colour

rebated system BLACK collection

the lock colour replaced with black colour

rail and stile set (allowing the user to shorten the door leaf (slab)
by max. 50 mm on a do-it-yourself basis)

rail and stile set (allowing the user to shorten the door leaf (slab)
by max. 90 mm on a do-it-yourself basis)

reinforcement for door closer

bottom rail and stile set protection against excessive moisture impact
(not applicable to leaves with ventilation trim)

door lower by 50 mm or 100 mm (rebated system)

door lower by 55 mm or 100 mm (non-rebated system)

door higher by 50 mm or 100 mm
(third hinge in the door leaf (slab) is required)


door higher by 150 mm or 200 mm
(third hinge in the door leaf (slab) is required)

ventilation trim (p. 159)

leaf (slab) edge in the colour of black, grey or graphite

tempered glass (version 03, 04)

tempered transparent 4 mm thick glass (version 01, 02)



SUBITO door, 07 version, SYSTEM DIN adjustable door frame

SUBITO










- **solid construction – wooden rail and stile set**
- **3-layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- K and C type **adjustable** and DUO type concealed **hinges**







leaf (slab) laminated edge in the colour of black, graphite or grey – option (not applicable to the BLACK surface)




SUBITO door, 07 version, SYSTEM DIN adjustable door frame

							
VERSION	01 / VF1	02 / VF2	03 / VF3	04 / VF14	05 / VF15	06 / VF9	07 / VF16













COLOURS

PAINTED			
	001 white (RAL 9003)	0M6 beige matt (NCS s2005 Y50R)	0M5 grey matt (RAL 7047)
BLACK		Applicable to Subito leaves and DIN, DIN DUO and Vertigo frames.	
	002 black (RAL 9005)		

OPTIONAL COLOURS


PAINTED	
	RAL and NCS colours (except the metallic ones)

DOOR FRAMES

EQUIPMENT

STANDARD	solid chipboard in-fill (third hinge recommended)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	third hinge in the door leaf (slab) or adjustable pivot hinge:
hinges: silver type K – for the DIN system door frame, silver type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "80"- "90" – 3 pcs)	type M, type C, type K a width of "60"- "80"
in case of door leaf (slab) with door closer and DIN system or metal frame T type hinges should be used ("60"- "80" – 3 pcs, "90"- "110" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge	concealed DUO type for a width of "60"- "80"
BLACK collection: standard magnetic lock face plate and DUO hinges are in the colour of black	the DUO hinge replaced with white or black colour
version 07 - in case of double doors it is possible to order symmetric division: "60"+"60", "70"+"70", "80"+"80", "90"+"90"	rebated system BLACK collection:
no possibility of ordering asymmetric double doors (refers to 07 version)	the lock colour replaced with black colour
ADDITIONAL (available at an extra charge)	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)
size "100"	reinforcement for door closer
size "110"	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
REVES system	door lower by 50 mm or 100 mm (rebated system)
recuperation trim	door lower by 55 mm or 100 mm (non-rebated system)
perforated chipboard in-fill	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
	ventilation trim (p. 159)
	leaf (slab) edge in the colour of black, grey or graphite



SUBLIME door, B12 version, SYSTEM DIN adjustable door frame

SUBLIME



- **solid construction – wooden rail and stile set**
- stable perforated **chipboard in-fill**
- **3 - layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- **T, C type reinforced and DUO type adjustable hinges**



milling on the door leaf (slab) surface,
30 mm wide on versions B9



milling on the door leaf (slab) surface,
15 mm wide on versions B12





milling on the door leaf (slab) surface,
6 mm wide on versions A1-A3 and
B2-B6





leaf (slab) laminated edge in the
colour of black, graphite or grey –
option (not applicable to the BLACK
surface)




SUBLIME door, B12 version, SYSTEM DIN adjustable door frame




COLOURS



OPTIONAL COLOURS



DOOR FRAMES



EQUIPMENT

STANDARD	
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	the DUO hinge replaced with white or black colour
hinges: type T – for the DIN system door frame and the metal door frame, type C – for the wooden door frame ("60"- "80" – 2 pcs, "90" – 3 pcs) or the concealed DUO satin nickel ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs)	the DUO lock colour replaced with black or golden gloss colour
door higher than standard – a non-standard milled versions	rebated system BLACK collection
BLACK collection: standard magnetic lock face plate and DUO hinges are in the colour of black	the T hinge colour replaced with black colour
versions B9 - wider cut, versions B12, A1-A3, B2-B6 - narrower cut	the lock colour replaced with black colour
ADDITIONAL (available at an extra charge)	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)
size "100"	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis)
REVES system	reinforcement for door closer
recuperation trim	ventilation trim (p. 159)
solid chipboard in-fill (third hinge recommended)	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
third hinge in the door leaf (slab):	door lower by 50 mm or 100 mm (rebated system)
type C for a width of "60"- "80"	door lower by 55 mm or 100 mm (non-rebated system)
type T for a width of "60"- "80"	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
concealed DUO type for a width of "60"- "70"	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
	leaf (slab) edge in the colour of black, grey or graphite



TIARA




- **solid construction – wooden rail and stile set**
- stable solid **chipboard in-fill**
- **3 - layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- **K and C type adjustable and DUO type concealed hinges**



aluminium decors on the leaf (slab) surface in the colour of matt chrome (standard)



DUO concealed hinge, white – option for non-rebated system



aluminium decors on the leaf (slab) surface in the colour of black, golden gloss, chrome gloss (option) – p. 163



DUO concealed hinge, black – standard for the non-rebated system, collection BLACK

TIARA door, W02 version, RAL 5011, SYSTEM DIN adjustable door frame



TIARA door, W02 version, DIN DUO adjustable door frame



VERSION W01 / VD1 W02 / VD2 W07 / VD7




VERSION W03 / VD3 W04 / VD4 W06 / VD6 W08 / VD8



leaf (slab) laminated edge in the colour of black, graphite or grey – option (not applicable to the BLACK surface)

COLOURS




Applicable to Tiara leaves and DIN, DIN DUO and Vertigo frames.

OPTIONAL COLOURS



RAL and NCS colours (except the metallic ones)

DOOR FRAMES



EQUIPMENT

STANDARD

single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)

hinges: silver type K – for the DIN system door frame, silver type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs)

BLACK collection: standard magnetic lock face plate and DUO hinges are in the colour of black

version W08: no possibility to use a ventilation slot or a ventilation grill

ADDITIONAL (available at an extra charge)

size "100"

REVES system

recuperation trim

third hinge in the door leaf (slab):

type K, type C, type M for a width of "60"- "80"
concealed DUO type for a width of "60"- "70"

the DUO hinge replaced with white or black colour

rebated system BLACK collection
the lock colour replaced with black colour

rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis) (not applicable to W08 version)

rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis) (not applicable to W08 version)
bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)

door lower by 50 mm or 100 mm (rebated system)

door lower by 55 mm or 100 mm (non-rebated system)

door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)


door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)

ventilation trim (p. 159)

aluminium decorative strips in black, golden gloss or chrome gloss

change of the DUO lock colour to black or golden gloss

leaf (slab) edge in the colour of black, grey or graphite



ESTATO door, A02 version, SYSTEM DIN adjustable door frame

ESTATO



- **solid construction – wooden rail and stile set**
- stable perforated **chipboard in-fill**
- **3 - layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- **security glass pane**, white matt thickness: **6 mm or 44.2 laminated glass in the colour of black or white**
- **T, C type reinforced and DUO type adjustable hinges**



milled version on the door leaf (slab) surface



laminated glass in the colour of white matt



leaf (slab) laminated edge in the colour of black, graphite or grey – option (not applicable to the BLACK surface)



pane in the colour of black - optional



ESTATO door, A01 version, SYSTEM DIN adjustable door frame



WHITE MATT TEMPERED GLASS

VERSION	A01 / V1SA	A02 / V2SA	A03 / V3SA	B1 / VF11	B2 / VF12	B3 / VF13
---------	------------	------------	------------	-----------	-----------	-----------



BLACK LAMINATED GLASS

WHITE MATT LAMINATED GLASS

VERSION	A01 / V1SA	A02 / V2SA	A03 / V3SA	A01 / V1SA	A02 / V2SA	A03 / V3SA
---------	------------	------------	------------	------------	------------	------------

COLOURS



OPTIONAL COLOURS



RAL and NCS
colours (except
the metallic ones)


DOOR FRAMES

POL-SKONE
system fixed frameDIN system
adjustable frame

metal fixed frame

metal adjustable
frame

DUO fixed frame

DIN DUO
adjustable frameVERTIGO
adjustable frame

metal fixed frame

metal adjustable
frame

EQUIPMENT

STANDARD

white matt tempered glass, thickness: 6 mm
(versions A01-58 mm, A02-208 mm, A03-280 mm)*

laminated glass 44.2 in the colour of black or white matt, 8.5 mm thick
(versions A01-54 mm, A02-205 mm, A03-276 mm)

single-point mortise lock, spacing: 72 mm (rebated system) or magnetic
mortise lock (non-rebated system), key-operated (spacing: 90 mm),
for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)

hinges: type T – for the DIN system door frame and the metal door
frame, type C – for the wooden door frame ("60"- "80" – 2 pcs,
"90" – 3 pcs) or the concealed DUO satin nickel for the non-rebated
system ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs)

ADDITIONAL (available at an extra charge)

size "100"

REVES system

perforated chipboard in-fill (hinge in the door leaf (slab) is required)

third hinge in the door leaf (slab):

type C for a width of "60"- "80"

type T for a width of "60"- "80"

concealed DUO type for a width of "60"- "70"

the DUO hinge replaced with white or black colour

rebated system BLACK collection

the T hinge colour replaced with black colour

the lock colour replaced with black colour

rail and stile set (allowing the user to shorten the door leaf (slab)
by max. 50 mm on a do-it-yourself basis)
(not applicable to versions A01, A02, A03)

rail and stile set (allowing the user to shorten the door leaf (slab)
by max. 90 mm on a do-it-yourself basis)
(not applicable to versions A01, A02, A03)

reinforcement for door closer

(not applicable to versions A01, A02, A03)

bottom rail and stile set protection against excessive moisture impact
(not applicable to leaves with ventilation trim)
(not applicable to versions A01, A02, A03)

door lower by 50 mm or 100 mm (rebated system) (not applicable
to the version A01, A02, A03)

door lower by 55 mm or 100 mm (non-rebated system) (not applicable
to versions A01, A02, A03)

door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is
required) (not applicable to versions A01, A02, A03)

door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is
required) (not applicable to versions A01, A02, A03)

version A01, A02, A03 door lower by 50 mm (rebated system)

version A01, A02, A03 door lower by 55 mm (non-rebated system)

version A01, A02, A03 door higher by 100 mm (third hinge in the door
leaf (slab) is required)

version A01, A02, A03 door higher by 200 mm (third hinge in the door
leaf (slab) is required)

ventilation trim (applicable to versions B1, B2, B3) (p. 159)

ventilation trim A01 with the "60" - "100" widths (p. 159)

ventilation trim A02, A03 with the "70" - "100" widths (p. 159)



tempered 6 mm glass in the colour of graphite, brown

sliding system (not applicable to the version A01)

leaf (slab) edge in the colour of black, grey or graphite

p. 114-119

*+/- 2 mm tolerance



PALAZZO door, W00 version, SYSTEM DIN adjustable door frame

PALAZZO

NEW

- **solid construction – wooden rail and stile set**
- **unique** design
- **rebated** or **non-rebated** system
- **3 - layer painting system** - colour fastness for many years
- **large colours palette** - in standard white, gray matt, beige matt and optional black
- **K type adjustable** for the rebated door or **DUO type concealed hinges** for the not-rebated door



rail and stile set profile



PALAZZO door, W00 version, DIN adjustable door frame



VERSION W00

COLOURS



Applicable to DIN, DIN DUO and Vertigo frames.

OPTIONAL COLOURS




DOOR FRAMES



EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	size "100"
hinges: type K – for the DIN system door frame, type C – for the wooden door frame or the concealed DUO satin nickel ("70" – 2 pcs, "80"-"90" – 3 pcs)	REVES system
door closer is not available	recuperation trim
	third hinge in the door leaf (slab): type C for a width of "70"-"80" type K for a width of "70"-"80"
	concealed DUO type for a width of "70"
	the DUO hinge replaced with white or black colour
	ventilation trim
	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
	door lower by 50 mm or 100 mm (rebated system)
	door lower by 55 mm or 100 mm (non-rebated system)
	door higher by 50 mm or 100 mm



VERTIGO door, W03 version, SYSTEM DIN adjustable door frame

VERTIGO



- **solid construction – wooden rail and stile set**
- **3 - layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- **security glass pane**, white matt thickness: 6 mm
- K and C type adjustable and DUO type concealed hinges



frame



DUO concealed hinge, white – option for non-rebated system



standard connection of architraves at an angle of 45° for the DIN DUO door frame



VERTIGO door, W02 version, VERTIGO adjustable door frame



VERSION	W00 / V01	OSD / V1SD	W02 / V02	W02S1 / V2SD
---------	-----------	------------	-----------	--------------



VERSION	W03 / V03	W03S1 / V3S1	W03S2 / V3S2	W03S3 / V3S3
---------	-----------	--------------	--------------	--------------

COLOURS




Applicable to Vertigo W00, W02, W03 leaves and DIN, DIN DUO and Vertigo frames.

OPTIONAL COLOURS



RAL and NCS colours (except the metallic ones)

DOOR FRAMES



EQUIPMENT

STANDARD

white matt tempered glass, thickness: 6 mm
transparent pane cannot be used

single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)

hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)

door closer is not available

BLACK collection: standard magnetic lock face plate and DUO hinges are in the colour of black

ADDITIONAL (available at an extra charge)

size "100"

recuperation trim

REVES system (version W00, W02, W03) - the door opening angle is 87° above ZW5 range

third hinge in the door leaf (slab):

type K, type C, type M for a width of "60"- "80"

concealed DUO type for a width of "60"- "80"

the DUO hinge replaced with white or black colour

rebated system BLACK collection

the lock colour replaced with black colour

bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)

door lower by 50 mm (rebated system)

door lower by 55 mm (non-rebated system)


door higher by 50 mm or 100 mm

(third hinge in the door leaf (slab) is required)

door higher by 150 mm or 200 mm

(third hinge in the door leaf (slab) is required)

ventilation trim (p. 159)



VILANO



VILANO door, W00 version, SYSTEM DIN adjustable door frame

- **solid construction – wooden rail and stile set**
- **3 - layer painting system** - colour fastness for many years
- **wide RAL and NCS colours palette**
- **security glass pane**, white matt thickness: 6 mm
- K and C type adjustable and DUO type concealed hinges



DUO concealed hinge, white – option for non-rebated system



frame profile



VILANO door, W00 version, SYSTEM DIN adjustable door frame



VERSION

W00 / V01

OSD / V1SD

COLOURS





Applicable to Vilano W00 leaves and DIN, DIN DUO and Vertigo frames.

OPTIONAL COLOURS



RAL and NCS colours (except the metallic ones)

DOOR FRAMES




EQUIPMENT

STANDARD

white matt tempered glass, thickness: 6 mm
transparent pane cannot be used
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)
door closer is not available

ADDITIONAL (available at an extra charge)

size "100"
recuperation trim
REVES system (version W00) (the door opening angle is 88° above ZW4 range)
third hinge in the door leaf (slab):
type K, type C, type M for a width of "60"- "80"
concealed DUO type for a width of "60"- "80"
the DUO hinge replaced with white or black colour
rebated system BLACK collection
the lock colour replaced with black colour
bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
door lower by 50 mm (rebated system)
door lower by 55 mm (non-rebated system)
door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
ventilation trim (p. 159)



for door leaves with ventilation option



MODERN door, 02 version, SYSTEM DIN adjustable door frame


MODERN



- **solid construction – wooden rail and stile set**
- **3 - layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- K and C type adjustable and DUO type concealed hinges



rail and stile set profile



DUO concealed hinge, white – option for non-rebated system



painted architrave and crown



MODERN door, 02 version with a crown, SYSTEM DIN adjustable door frame




VERSION **01 / V01** **01S6 / V1S6** **02 / V02** **02S6 / V2S6**



VERSION **05 / V05** **05S8 / V5S8** **08 / V08** **08S10 / V8S10**

COLOURS



Applicable to Modern 01, 02, 05, 08 leaves and DIN, DIN DUO and Vertigo frames.

OPTIONAL COLOURS



RAL and NCS colours (except the metallic ones)

DOOR FRAMES



POL-SKONE system fixed frame



DIN system adjustable frame



metal fixed frame




metal adjustable frame




DUO fixed frame



DIN DUO adjustable frame



VERTIGO adjustable frame



metal fixed frame



metal adjustable frame


EQUIPMENT

STANDARD

white matt or transparent 4 mm thick glass
wooden muntins
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)
door closer is not available
BLACK collection: standard magnetic lock face plate and DUO hinges are in the colour of black

ADDITIONAL (available at an extra charge)

size "100"
recuperation trim
REVES system (version 01, 02, 05, 08)
third hinge in the door leaf (slab): type K, type M for a width of "60"- "80"
concealed DUO type for a width of "60"- "80"
the DUO hinge replaced with white or black colour
rebated system BLACK collection
the lock colour replaced with black colour
bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
door lower by 50 mm (rebated system)
door lower by 55 mm (non-rebated system)
door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
ventilation trim (p. 159)



for door leaves
with ventilation
option



MODENA door, 02 version, SYSTEM DIN adjustable door frame

MODENA

- **solid construction – wooden rail and stile set**
- **3 - layer painting system** - colour fastness for many years
- wide **RAL and NCS colours palette**
- K and C type adjustable and DUO type concealed hinges



rail and stile set profile




MODENA door, 08 version, SYSTEM DIN adjustable door frame



VERSION	02 / V02	05 / V05	08 / V08
---------	----------	----------	----------

COLOURS



Applicable to DIN, DIN DUO and Vertigo frames.

OPTIONAL COLOURS



RAL and NCS colours (except the metallic ones)

DOOR FRAMES



POL-SKONE system fixed frame

DIN system adjustable frame

DUO fixed frame

DIN DUO adjustable frame

VERTIGO adjustable frame

EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	size "100"
hinges: K type – for the DIN system door frame, C type – for the wooden door frame or the satin nickel DUO concealed ("60"- "80" – 2 pcs, "90" – 3 pcs)	recuperation trim
door closer is not available	REVES system
	third hinge in the door leaf (slab): type K, type C for a width of "60"- "80" concealed DUO type for a width of "60"- "80"
	the DUO hinge replaced with white or black colour
	ventilation trim (p. 159)
	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
	door lower by 50 mm or 100 mm (rebated system)
	door lower by 55 mm or 100 mm (non-rebated system)
	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)



for door leaves
with ventilation
option

RAL 7035



MODESTO door, W01 version, SYSTEM DIN adjustable door frame

MODESTO

NEW

- **solid construction – wooden rail and stile set**
- 3 - layer **painting system - colour fastness** for many years
- panel thickness: 12 mm
- wide **RAL and NCS colours palette**
- **K and C type adjustable** and **DUO type concealed hinges**



MODESTO door, W04 version, SYSTEM DIN adjustable door frame










VERSION	W00	W01	W02	W03	W04
---------	-----	-----	-----	-----	-----

COLOURS


PAINTED	001	0M6	0M5	002	NEW 003
	white (RAL 9003)	beige matt (NCS s2005 Y50R)	grey matt (RAL 7047)	black (RAL 9005)	sage (NCSs4010-G50Y)

DOOR FRAMES

<div>rebated SYSTEM</div> 			
	POL-SKONE system fixed frame	DIN system adjustable frame	
<div>non-rebated SYSTEM</div> 			
	DUO fixed frame	DIN DUO adjustable frame	VERTIGO adjustable frame

EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	size "100"
hinges: type K – for the DIN system door frame; type C – for the wooden door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)	REVES system
door closer is not available	recuperation trim
	third hinge in the door leaf (slab): type C for a width of "60"- "80" type K for a width of "60"- "80" concealed DUO type for a width of "60"- "80"
	the DUO hinge replaced with white or black colour
	ventilation trim
	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
	door lower by 50 mm or 100 mm (rebated system)
	door lower by 55 mm or 100 mm (non-rebated system)
	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)



LOFTY



- **solid construction – wooden rail and stile set**
- stable solid **chipboard in-fill**
- adjustable reinforced hinge type T and adjustable DUO type in black

LOFTY door, W00 version, SYSTEM DIN adjustable door frame in black 244



LOFTY door, W00 version, SYSTEM DIN adjustable door frame in black 244



SET PRICE

=

DOOR Leaf (slab) PRICE

+

DIN / DIN DUO DOOR FRAME PRICE
(black 244 or 644)

or

HARMONY CONCEALED DOOR
FRAME PRICE (BLACK RAL 9005)

or

METAL FRAME PRICE

VERSION

W00 / V00

COLOURS

ECO TOP

121

oak

141

Salinas oak

159

delano oak

160

sonoma oak

161

halif oak

SILKSTONE

230

gran oak

276

Polish oak

LAMISTONE
CPL

231

halif oak

243

delano oak

250

terra oak

VENEERED
GROUP A

311

bright oak

334

European oak

VENEERED
GROUP D

460

makassar

DOOR FRAMES



rebated
SYSTEM

DIN system
adjustable frame

metal fixed frame

metal adjustable
frame

non-rebated
SYSTEM



DIN DUO
adjustable frame

metal fixed frame

metal adjustable
frame

EQUIPMENT

STANDARD	
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	type T in black for a width of "60"- "80"
hinges: type T - for the metal frame or concealed DUO in black ("60"- "80" - 2 pcs., "90" - 3 pcs.)	concealed DUO type in black for a width of "60"- "80"
in case of door leaf (slab) with door closer and DIN system or metal frame T type hinges should be used ("60"- "80" - 3 pcs, "90"- "110" - 4 pcs) - replacement of standard hinges with hinge type T for an extra charge	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)
	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis)
	reinforcement for door closer
	bottom rail and stile set protection against excessive moisture impact
	door lower by 50 mm or 100 mm (rebated system)
	door lower by 55 mm or 100 mm (non-rebated system)
	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
	ventilation trim (p. 159)
	leaf (slab) laminated edge in the colour of black
	ABS edging in black or Polish oak (rebated system)
ADDITIONAL (available at an extra charge)	
size "100"	
size "110"	
recuperation trim	
REVES system	
third hinge in the door leaf (slab) or adjustable pivot hinge:	



for door leaves with ventilation option



ARCO door, W03P version, SYSTEM DIN adjustable door frame

ARCO



- **constructed with a high quality** MDF rail and stile set
- FSC® Mix certificate only available upon request
- door available in **10 working days** under the "fast delivery" promotion



rail and stile set - vertical wood grain, cross rails and panel - horizontal wood grain



panels, glazing



available at an extra charge: **VSG 22.1 laminated glass in the colour of black**



ARCO door, W02 version (door on the left side and the right side), DIN adjustable door frame



The mark of responsible forestry

ARCO certified FSC® Mix available only on customer's request




VERSION	W02P / V02	W2S / V2S2	W02 / V2S5	W2D / V1SD	W03P / V03	W3S / V3S2	W03 / V3S5	W5P / V4S2	W5S / V4S4	W05 / V4S3
---------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------




VERSION	W06 / V05	W6S1 / V5S1	W6S2 / V5S2	W6S3 / V5S3	W07 / V06	W07S1 / V6S1	W07S3 / V6S3	W08 / V07	W08S1 / V7S1	W08S4 / V7S4
---------	-----------	-------------	-------------	-------------	-----------	--------------	--------------	-----------	--------------	--------------

COLOURS



DOOR FRAMES



EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
white/brown matt or transparent 4 mm glass	recuperation trim (only standard height)
models W2D, W5S, W05, W6S1, W6S2, W6S3 standard: tempered glass	door lower by 50 mm (rebated system)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	door lower by 55 mm (non-rebated system)
hinges: type B – for the DIN system door frame, type D – for the MDF, type M – for the metal door frame or the concealed DUO satin nickel ("60"-/90" – 3 pcs)	ventilation trim (p. 159)
door closer is not available	VSG 22.1 laminated white or transparent glass: version W02, W08, W03
drop seal is not available	tempered transparent 4 mm thick glass
	VSG 22.1 laminated black glass: version W02, W08, W03



INTER-AMBER

- **solid construction – wooden rail and stile set**
- **abundant colours** of ECO TOP and HIGH TOP surface finish
- **tempered glass pane** in AS4 and 03SD version in white or brown matt colour, thickness: 4 mm



INTER-AMBER door, F00 version, SYSTEM DIN adjustable door frame

muntin AS4



INTER-AMBER door, F06 version (door on the left side), A00 version (door on the right side), SYSTEM DIN adjustable door frame

VERSION	A00 / V00	A01 / V2S	AS4 / V2SD	03SD / V3SD	C00 / V03	C01 / V3S1	C02 / V3S2	C03 / V3S3

VERSION	F00 / V06	F01 / V6S1	F02 / V6S2	F06 / V6S6	04SD / V4SD	05SD / V5SD

COLOURS


ECO TOP	120 white	121 oak	132 walnut	135 English oak	141 Salinas oak	158 honey oak	159 delano oak	160 sonoma oak	161 halif oak
HIGH TOP	148 coffee ash								

DOOR FRAMES

		POL-SKONE system fixed frame	MDF fixed type	DIN system adjustable frame	metal fixed frame	metal adjustable frame
		DIN DUO adjustable frame	metal fixed frame	metal adjustable frame		

EQUIPMENT

STANDARD	solid chipboard in-fill (third hinge recommended)
white/brown matt or transparent 4 mm glass	third hinge in the door leaf (slab) (slab) or adjustable pivot hinge:
version AS4, 03SD standard - tempered glass pane	type B, type D, type K, type C, type M for a width of "60"- "80"
white/brown matt 4 mm	concealed DUO type for a width of "60"- "80"
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)
hinges: type B – for the DIN system door frame, type D – for the wooden or MDF door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis)
in case of door leaf (slab) (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "110" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge	reinforcement for door closer
ADDITIONAL (available at an extra charge)	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
size "100" (glazing decoration as in "90")	door lower by 50 mm or 100 mm (rebated system)
size "110" (glazing decoration as in "90")	door lower by 55 mm or 100 mm (non-rebated system)
REVES system (version A00, C00, F00)	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required) (not applicable to the fixed MDF frame)
recuperation trim	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required) (not applicable to the fixed MDF frame)
perforated chipboard in-fill	ventilation trim (p. 159)
	tempered glass:
	version C, F, 04SD, 05SD
	tempered transparent 4 mm thick glass



SEDO door, W01S8 version, SYSTEM DIN adjustable door frame

SEDO

- **constructed with a high quality** MDF rail and stile set
- **large UNI MAT PLUS surface**, characterised by a silky haptics and special coating resistant to fingerprints



muntin bar profile



SEDO door, W01S8 version, SYSTEM DIN adjustable door frame

NEW!
BLACK MUNTIN BARS
AVAILABLE



VERSION	W00 / V00	W01S8 / V1S8	W01S8 black muntin bars	W01 / V1SD	W02 / V02
---------	-----------	--------------	-------------------------	------------	-----------



VERSION	W03 / V03	W04 / V04
---------	-----------	-----------

COLOURS


UNI MAT PLUS	640 graphite	641 titano	642 white	643 beige	644 black
	645 lava	646 stone	647 indigo	648 moss	NEW 649 sage

DOOR FRAMES

Rebated SYSTEM 					
	POL-SKONE system fixed frame	DIN system adjustable frame	metal fixed frame	metal adjustable frame	
	Non-rebated SYSTEM 				
		DIN DUO adjustable frame	metal fixed frame	metal adjustable frame	

EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
version W00, W02, W03, W04 panel thickness: 12 mm	recuperation trim (only standard height)
version W01: white matt tempered glass pane, thickness: 4 mm	door lower by 50 mm (rebated system)
version W01, W01S8 transparent or white matt tempered glass pane, thickness: 4 mm	door lower by 55 mm (non-rebated system)
no possibility to use VSG 22.1, VSG 33.1 laminated glass	ventilation trim
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	version W01S8: black muntin bars
644 black, rebated system: lock in the colour of black, hinges in the colour of brushed nickel	
644 black, non-rebated system: lock and hinges in the colour of black	
hinges: type B – for the DIN system door frame, type M - for the metal door frame or the hidden DUO satin nickel ("60"- "90" – 3 pcs)	
644 black: concealed DUO hinge in the colour of black	



CREATO door, A02 version, SYSTEM DIN adjustable door frame

CREATO

- **solid construction – wooden rail and stile set**
- stable perforated **chipboard in-fill**
- **large UNI MAT PLUS surface**, characterised by a silky haptics and special coating resistant to fingerprints
- **VSG 44.2 laminated black or white glass**
- **T type reinforced and DUO type adjustable hinges**



white hinge – option



CREATO door, A01 version, SYSTEM DIN adjustable door frame



WHITE MATT OR BLACK TRANSPARENT, LAMINATED GLASS

VERSION	A01 / V1SA	A02 / V2SA	A03 / V3SA
---------	------------	------------	------------



WHITE MATT OR GRAPHITE TEMPERED GLASS, THICKNESS 6 MM










VERSION	A01 / V1SA	A02 / V2SA	A03 / V3SA
---------	------------	------------	------------

COLOURS

UNI MAT PLUS	640 graphite	641 titano	642 white	643 beige	644 black
	645 lava	646 stone	647 indigo	648 moss	NEW 649 sage

DOOR FRAMES



rebated SYSTEM					
	POL-SKONE system fixed frame	DIN system adjustable frame	metal fixed frame	metal adjustable frame	
non-rebated SYSTEM					
	DIN DUO adjustable frame	DUO fixed frame	VERTIGO adjustable frame	metal fixed frame	metal adjustable frame

EQUIPMENT


STANDARD
laminated glass 44.2 in the colour of black, transparent or white matt, 8.5 mm thick (glazing width in versions: A01 – 58 mm, A02 – 208 mm, A03 – 280 mm)*
versions with black laminated glass: lock and T and DUO type hinges in the colour of black
versions with white matt and transparent laminated glass: lock and hinges in the colour of silver
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
hinges: type T black – for the DIN system or metal door frame, type C, D silver – for the wooden door frame ("60"- "80" – 2 pcs, "90" – 3 pcs) or the concealed DUO, black for the non-rebated system ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs)
door closer is not available
bottom rail and stile set protection against excessive moisture impact is not applicable to
ADDITIONAL (available at an extra charge)
perforated chipboard in-fill (hinge in the door leaf (slab) is required)
size "100"
*+/- 2 mm tolerance

REVES system
third hinge in the door leaf (slab):
type D for a width of "60"- "80"
type C for a width of "60"- "80"
type T for a width of "60"- "80"
concealed DUO type for a width of "60"- "70"
change of standard type T hinge to the colour of black
change of standard DUO hinge to the colour of black
version A01, A02, A03 door lower by 50 mm (rebated system)
version A01, A02, A03 door lower by 55 mm (non-rebated system)
version A01, A02, A03 door higher by 100 mm (third hinge required at extra charge)
version A01, A02, A03 door higher by 200 mm (third hinge required at extra charge)
leaf (slab) edge in the colour of black
sliding system (not applicable to the version A01)
ventilation trim A01 with the "60" - "100" widths
ventilation trim A02, A03 with the "70" - "100" widths

p. 114-119

p. 159

p. 159



HAPTIC




- **solid construction – wooden rail and stile set**
- **large UNI MAT PLUS surface**, characterised by a silky haptics and special coating resistant to fingerprints
- K and C type adjustable and DUO type concealed hinges

HAPTIC door, 00 version, SYSTEM DIN adjustable door frame



HAPTIC door, 00 version, SYSTEM DIN adjustable door frame




VERSION	00 / V00	02 / V2S	04 / V4SD	05 / V5SD	03SD / V3SD
---------	----------	----------	-----------	-----------	-------------


ABS EDGING



COLOURS




DOOR FRAMES



EQUIPMENT

STANDARD	
white/brown matt or transparent 4 mm glass	the DUO lock colour replaced with black or golden gloss colour
model 03SD standard: white/brown tempered glass, thickness: 4 mm	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis)
hinges: type K – for the DIN system door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)	reinforcement for door closer
in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "110" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
ADDITIONAL (available at an extra charge)	door lower by 50 mm or 100 mm (rebated system)
size "100" (glazing decoration as in "90")	door lower by 55 mm or 100 mm (non-rebated system)
size "110" (glazing decoration as in "90")	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
recuperation trim	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
REVES system (version 00)	ventilation trim (p. 159)
perforated chipboard in-fill	tempered glass: version 02, 04, 05
solid chipboard in-fill (third hinge recommended)	tempered transparent 4 mm thick glass
third hinge in the door leaf (slab) or adjustable pivot hinge: type K, type M for a width of "60"- "80"	ABS edging in black, white, titano, Polish oak or anthracite (rebated system)
concealed DUO type for a width of "60"- "80"	



ARIA door, W01 version, SYSTEM DIN adjustable door frame

ARIA

NEW

COMPOSE
YOUR
ARIA
choose the **colours**
of the muntins **yourself**



muntin bar



ARIA door, W02 version, SYSTEM DIN adjustable door frame





VERSION	W01/V01	W01S*/V1SD	W02/V02	W02S*/V2SD	W03/V03	W03S*/V3SD
---------	---------	------------	---------	------------	---------	------------

*glassed version

munтин:
642 white



munтин:
276 Polish oak



munтин:
644 black



munтин:
230 gran oak



munтин:
293 anthracite Royal



COLOURS



UNI MAT PLUS	640 graphite	641 titano	642 white	643 beige	644 black
	645 lava	646 stone	647 indigo	648 moss	NEW 649 sage

DOOR FRAMES

rebated SYSTEM				
	POL-SKONE system fixed frame	DIN system adjustable frame	metal fixed frame	metal adjustable frame
non-rebated SYSTEM				
	DIN DUO adjustable frame	metal fixed frame	metal adjustable frame	

EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
version W01S, W02S, W03S: white matt tempered glass pane, thickness: 4 mm	recuperation trim (only standard height)
solid construction – a high quality MDF rail and stile set	door lower by 50 mm (rebated system)
MDF rail and stile set thickness 12 mm covered with UNI MAT PLUS surface	door lower by 55 mm (non-rebated system)
vertical and horizontal rail and stile set is the same 40 mm thickness	ventilation trim
30 mm thick glued muntin bars covered with UNI MAT PLUS or SILKSTONE surface	tempered transparent 4 mm thick glass
single-point mortise lock in white zinc, 72 mm spacing (rebated system), in UNI MAT PLUS 644 black colour, single-point mortise lock in black colour, 72 mm spacing (rebated system) or magnetic lock in satin nickel colour (non-rebated system) mortise key-operated (90 mm spacing) for a cylinder (85 mm spacing) or for a bathroom lock (90 mm spacing)	
UNI MAT PLUS 644 black colour magnetic lock in black colour (non-rebated system) key-operated (spacing 90 mm) for an insert (spacing 85 mm) or for a bathroom lock (spacing 90 mm)	
silver hinges: type B – for the DIN system door frame, type M – for the metal door frame or the concealed DUO satin nickel colour ("60"- "90" – 3 pcs), in UNI MAT PLUS 644 black concealed hinges DUO in black colour	



for door leaves
with ventilation
option



ESTO

NEW

- **solid construction** – a high quality MDF rail and stile set
- 40 mm thick **vertical rail and stile set**
- 35 mm thick **horizontal rail and stile set** (upper and bottom)
- 22 mm thick **panels**

ESTO door, W01 version, SYSTEM DIN adjustable door frame



ESTO door, W01 version, SYSTEM DIN adjustable door frame






VERSION	V03	V3S1	V3S2
---------	-----	------	------



VERSION	V3S3	V3S4	V3S5
---------	------	------	------

COLOURS




DOOR FRAMES



EQUIPMENT

STANDARD
solid construction – a high quality MDF rail and stile set
40 mm thick vertical rail and stile set
35 mm thick horizontal rail and stile set (upper and bottom)
22 mm thick panels
white matt glass 4 mm thick
single-point mortise lock in white zinc, 72 mm spacing (rebated system), in 244 black colour, single-point mortise lock in black colour, 72 mm spacing (rebated system) or magnetic lock in satin nickel colour (non-rebated system) mortise key-operated (90 mm spacing) for a cylinder (85 mm spacing) or for a bathroom lock (90 mm spacing) in 244 black colour magnetic lock in black colour(non-rebated system) key-operated (spacing 90 mm) for an insert (spacing 90 mm) or for a bathroom lock (spacing 90 mm)
silver hinges: type B – for the DIN system door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "90" – 3 pcs).
in black 244 concealed hinges DUO in black colour

ADDITIONAL (available at an extra charge)
recuperation trim (only standard height)
door lower by 50 mm (rebated system)
door lower by 55 mm (non-rebated system)
ventilation trim
tempered transparent 4 mm thick glass



MODO



MODO door, W00 version, SYSTEM DIN adjustable door frame

- **solid construction** – a high quality MDF rail and stile set
- **vertical and horizontal** rail and stile set is the same 40 mm thickness
- MDF rail and stile set covered with **UNI MAT PLUS, LAMISTONE, SILKSTONE surface**
- 12 mm thick MDF panel covered with **UNI MAT PLUS, LAMISTONE, SILKSTONE surface**
- **spatial** design frame



door frame profile









MODO door, W00 version, DIN adjustable door frame

				NEW VERSION
				
VERSION	W00 / V01	W01 / V1SD	W02 / V02	W03 / V03

COLOURS

LAMISTONE CPL	250 terra oak	258 white	289 grey	531 anthracite
SILKSTONE	230 gran oak	276 Polish oak	295 merbau Royal	
UNI MAT PLUS	640 graphite	641 titano	642 white	643 beige
	645 lava	646 stone	647 indigo	648 moss
				644 black
				NEW 649 sage

DOOR FRAMES

rebated SYSTEM			
	DIN system adjustable frame	metal fixed frame	metal adjustable frame
non-rebated SYSTEM			
	DIN DUO adjustable frame	metal fixed frame	metal adjustable frame



EQUIPMENT

STANDARD

version W01 - white matt tempered glass pane, thickness: 4 mm
 single-point mortise lock in white zinc, 72 mm spacing (rebated system), in UNI MAT PLUS 644 black colour, single-point mortise lock in black colour, 72 mm spacing (rebated system) or magnetic lock in satin nickel colour (non-rebated system) mortise key-operated (90 mm spacing) for a cylinder (85 mm spacing) or for a bathroom lock (90 mm spacing)
 UNI MAT PLUS 644 black colour magnetic lock in black colour (non-rebated system) key-operated (spacing 90 mm) for an insert (spacing 85 mm) or for a bathroom lock (spacing 90 mm)
 hinges: type B – for the DIN system door frame, type M – for the metal door frame or the concealed DUO satin nickel colour ("60"- "90" – 3 pcs) in UNI MAT PLUS 644 black concealed hinges DUO in black colour
 door closer is not available
 drop seal is not available
 no possibility to use VSG 22.1, VSG 33.1 laminated glass

ADDITIONAL (available at an extra charge)

recuperation trim (only standard height)
 door lower by 50 mm (rebated system)
 door lower by 55 mm (non-rebated system)
 ventilation trim
 tempered transparent 4 mm thick glass



for door leaves
with ventilation
option



VERI door, W02 version, SYSTEM DIN adjustable door frame

VERI

- **solid construction** – a high quality MDF rail and stile set
- **vertical and horizontal** rail and stile set is the same 40 mm thickness
- MDF rail and stile set covered with **UNI MAT PLUS, LAMISTONE, SILKSTONE surface**
- 12 mm thick MDF panel covered with **UNI MAT PLUS, LAMISTONE, SILKSTONE surface**
- **spatial** design frame



door frame profile




















special bevel on the rail and stile joint









VERI door, W00 version, DIN DUO adjustable door frame

				NEW VERSION
				
VERSION	W00 / V01	W01 / V1SD	W02 / V02	W03 / V03

COLOURS

LAMISTONE CPL	 250 terra oak	 258 white	 289 grey	 531 anthracite
SILKSTONE	 230 gran oak	 276 Polish oak	 295 merbau Royal	
UNI MAT PLUS	 640 graphite	 641 titano	 642 white	 643 beige
	 645 lava	 646 stone	 647 indigo	 648 moss
				 644 black
				 649 sage

DOOR FRAMES

rebated SYSTEM			
	DIN system adjustable frame	metal fixed frame	metal adjustable frame
non-rebated SYSTEM			
	DIN DUO adjustable frame	metal fixed frame	metal adjustable frame


EQUIPMENT

STANDARD

version W01 - white matt tempered glass pane, thickness: 4 mm
 mortise single point lock in white zinc, 72 mm spacing (rebated system), in colour UNI MAT PLUS black 644 mortise single point lock in black 72 mm spacing (rebated system) or magnetic lock in satin nickel (non-rebated system) key-operated (90 mm spacing) for a cylinder (85 mm spacing) or for a bathroom lock (90 mm spacing)
 in colour UNI MAT PLUS black 644 magnetic lock in black (non-rebated system) key-operated (spacing 90 mm) for a cylinder (spacing 85 mm) or for a bathroom lock (spacing 90 mm)
 hinges: type B – for the DIN system door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"-/90" – 3 pcs)
 In black UNI MAT PLUS 644 concealed hinges DUO in black.
 door closer is not available
 drop seal is not available
 no possibility to use VSG 22.1, VSG 33.1 laminated glass

ADDITIONAL (available at an extra charge)

recuperation trim (only standard height)
 door lower by 50 mm (rebated system)
 door lower by 55 mm (non-rebated system)
 ventilation trim
 tempered transparent 4 mm thick glass



for door leaves
with ventilation
option



EGRO door, W00 version, SYSTEM DIN adjustable door frame

EGRO

- **solid construction** – a high quality MDF rail and stile set
- **vertical and horizontal** rail and stile set is the same 40 mm thickness
- MDF rail and stile set covered with **UNI MAT PLUS, LAMISTONE, SILKSTONE surface**
- 16 mm thick MDF panel covered with **UNI MAT PLUS, LAMISTONE, SILKSTONE surface**
- 16 mm thick **spatial** design frame



















spatial design frame









EGRO door, W00 version, DIN adjustable door frame

						NEW VERSIONS	
							
VERSION	W00 / V01	W01 / V1SD	W02 / V02	W03 / V2SD	W04 / V03	W05 / V3SD	

COLOURS

LAMISTONE CPL				
	250 terra oak	258 white	289 grey	531 anthracite
SILKSTONE				
	230 gran oak	276 Polish oak	295 merbau Royal	
UNI MAT PLUS				
	640 graphite	641 titano	642 white	643 beige
				
	645 lava	646 stone	647 indigo	648 moss
				
				649 sage

DOOR FRAMES

rebated SYSTEM			
	DIN system adjustable frame	metal fixed frame	metal adjustable frame
non-rebated SYSTEM			
	DIN DUO adjustable frame	metal fixed frame	metal adjustable frame

EQUIPMENT

STANDARD

version W01, W03, W05 - white matt tempered glass pane, thickness: 4 mm

version W00, W02, W04 - spatial design frame thickness 16 mm

mortise single point lock in white zinc, 72 mm spacing (rebated system), in colour UNI MAT PLUS black 644 single point mortise lock in black 72 mm spacing (rebated system) or magnetic lock in satin nickel (non-rebated system) key-operated (90 mm spacing) for a cylinder (85 mm spacing) or for a bathroom lock (90 mm spacing) in colour UNI MAT PLUS black 644 magnetic lock in black (non-rebated system) key-operated (spacing 90 mm) for a cylinder (spacing 85 mm) or for a bathroom lock (spacing 90 mm)

hinges: type B – for the DIN system door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"-/90" – 3 pcs)

In black UNI MAT PLUS 644 concealed hinges DUO in black.

door closer is not available

drop seal is not available

no possibility to use VSG 22.1, VSG 33.1 laminated glass

ADDITIONAL (available at an extra charge)



recuperation trim (only standard height)

door lower by 50 mm (rebated system)

door lower by 55 mm (non-rebated system)

ventilation trim

tempered transparent 4 mm thick glass



for door leaves
with ventilation
option



FIORI door, W02S2P version, SYSTEM DIN adjustable door frame

FIORI

- constructed with a high quality **MDF** rail and stile set
- vertical and horizontal **rail and stile set** is the same 40 mm thickness



special bevel on the rail and stile joint



available at an extra charge: **VSG 22.1**
laminated glass in the colour
of black



FIORI door, W02 version, DIN adjustable door frame







VERSION	W02 / V4S4	W02P / V04	W02S2P / V4S2
---------	------------	------------	---------------

COLOURS


LAMISTONE CPL	244 black	250 terra oak	258 white	289 grey	531 anthracite
SILKSTONE	230 gran oak	276 Polish oak	295 merbau Royal		

DOOR FRAMES

rebated SYSTEM		
	POL-SKONE system fixed frame	DIN system adjustable frame
non-rebated SYSTEM		
	DUO fixed frame	DIN DUO adjustable frame

EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
white/brown matt or transparent 4 mm glass	recuperation trim (only standard height)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	black-coloured lock rebated system
hinges: type B – for the DIN system door frame, type D – for the wooden door frame or the concealed DUO satin nickel ("60"-/90" – 3 pcs)	the DUO hinge replaced with white or black colour
door closer is not available	door lower by 50 mm (rebated system)
drop seal is not available	door lower by 55 mm (non-rebated system)
	ventilation trim (p. 159)
	VSG 22.1 laminated glass in the colour of black (applicable to 1 glass pane): version W02, W02S2P
	VSG 22.1 laminated white or transparent glass (applicable to 1 glass pane)
	tempered transparent 4 mm thick glass
	the DUO lock colour replaced with golden gloss colour



IMPULS door, W06 version, SYSTEM DIN adjustable door frame

IMPULS



- **solid construction – wooden rail and stile set**
- door available in **10 working days** under the “fast delivery” promotion
- **large LAMISTONE CPL and SILKSTONE** surface finish
- K and C type adjustable and DUO type concealed hinges



spacer frame profile



door frame



IMPULS door, W13 version (door on the left side), W01 version (door on the right side), SYSTEM DIN adjustable door frame



ETIUDA door, B1 version, SYSTEM DIN adjustable door frame

ETIUDA

- **solid construction – wooden rail and stile set**
- **large LAMISTONE CPL and SILKSTONE** surface finish
- white matt and graphite **tempered glass**, thickness: 6 mm
- aluminium decorative strips in the colour of silver or black
- K and C type adjustable and DUO type concealed hinges




aluminium decorative strips



option: aluminium glazing strips in the colour of black




option: aluminium decorative strips in the colour of black



top door leaf (slab) edge without a rebate



ETIUDA door, B1 version (door on the left side), A01 version (door on the right side), POL-SKONE system fixed door frame




VERSION **B0 / V00** **B1 / VD11** **A01 / V1SA** **A02 / V2SA** **A03 / V3SA**

COLOURS




DOOR FRAMES



EQUIPMENT

STANDARD	
white/brown matt tempered glass, thickness: 6 mm	reinforcement for door closer (not applicable to the version A01, A02, A03)
black-coloured glass pane is not available	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim) (not applicable to versions A01, A02, A03)
glazing width in the A01 version – 54 mm; A02 – 205 mm, A03 – 276 mm*	door lower by 50 mm or 100 mm (rebated system) (not applicable to versions A01, A02, A03)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	door lower by 55 mm or 100 mm (non-rebated system) (not applicable to versions A01, A02, A03)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)	door higher by 50 mm or 100 mm (not applicable to versions A01, A02, A03) (third hinge in the door leaf (slab) is required)
in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "110" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge	door higher by 150 mm or 200 mm (not applicable to versions A01, A02, A03) (third hinge in the door leaf (slab) is required)
ADDITIONAL (available at an extra charge)	version A01, A02, A03 door lower by 50 mm (rebated system)
size "100"	version A01, A02, A03 door lower by 55 mm (non-rebated system)
size "110" (applicable to the version B0, B1)	version A01, A02, A03 door higher by 100 mm (third hinge in the door leaf (slab) is required)
perforated chipboard in-fill (versions B0, A01, A02, A03)	version A01, A02, A03 door higher by 200 mm (third hinge in the door leaf (slab) is required)
solid chipboard in-fill (versions B0, A01, A02, A03) (third hinge recommended)	ventilation trim (applicable to versions B0, B1) (p. 159)
third hinge in the door leaf (slab) or adjustable pivot hinge: type K, type C, type M for a width of "60"- "80" concealed DUO type for a width of "60"- "80"	ventilation trim A01 with the "60" - "100" widths (p. 159)
the DUO lock colour replaced with black or golden gloss colour	ventilation trim A02, A03 with the "70" - "100" widths (p. 159)
rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis) (applicable to versions B0)	tempered 6 mm glass in the colour of graphite or transparent
rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis) (applicable to versions B0)	change of colour of decorative strips to black:
*+/- 2 mm tolerance	version B1
	version A01-A03
	sliding system (not applicable to version A01)



SONATA door, W4 version, SYSTEM DIN adjustable door frame

SONATA



- **solid construction – wooden rail and stile set**
- stable perforated **chipboard in-fill**
- **large LAMISTONE CPL and SILKSTONE** surface finish
- K and C type adjustable and DUO type concealed hinges



aluminium decors on the leaf (slab) surface in the colour of matt chrome (standard)



VERTIGO door frame, upper panel



aluminium decors on the leaf (slab) surface in the colour of black, golden gloss, chrome gloss (option) – p. 163



leaf (slab) laminated edge in the colour of black, graphite or grey – option (not applicable to the BLACK surface)













SONATA door, W2 version, VERTIGO adjustable door frame

							
VERSION	W1 / VD1	W2 / VD2	W4 / VD4	W5 / VD5	W6 / VD6	W7 / VD7	W8 / VD8

COLOURS














LAMISTONE CPL				
	240 whitewashed elm V	241 sand elm V	242 grey elm V	247 industry 1
SILKSTONE				
	276 Polish oak			

NEW COLOURS

									
UNI MAT PLUS	640 graphite	641 titano	642 white	643 beige	644 black	645 lava	646 stone	647 indigo	648 moss

DOOR FRAMES



<div>rebated SYSTEM</div> 						
	POL-SKONE system fixed frame	DIN system adjustable frame	POL-SKONE system adjustable frame	metal fixed frame	metal adjustable frame	
<div>non-rebated SYSTEM</div> 						
	DUO fixed frame	DIN DUO adjustable frame	DUO adjustable frame	VERTIGO adjustable frame	metal fixed frame	metal adjustable frame

EQUIPMENT

STANDARD

single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)

hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame ("60"- "80" – 2 pcs, "90" – 3 pcs) or the concealed DUO satin nickel ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs)

in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "100" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge

version W8: no possibility to use a ventilation slot or a ventilation grill

ADDITIONAL (available at an extra charge)

size "100"

REVES system

perforated chipboard in-fill (hinge in the door leaf (slab) is required)

recuperation trim

third hinge in the door leaf (slab):

type K, type C, type M for a width of "60"- "80"

concealed DUO type for a width of "60"- "70"

rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis) (not applicable to version W8)

rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis) (not applicable to version W8)

reinforcement for door closer

bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)

door lower by 50 mm or 100 mm (rebated system)

door lower by 55 mm or 100 mm (non-rebated system)

door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)


door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)

ventilation trim (p. 159)

aluminium edge (non-rebated system)

aluminium decors in black, chrome gloss, golden gloss

leaf (slab) edge in the colour of black, grey or graphite



for door leaves
with ventilation
option

FORTIMO



FORTIMO door, W01S1 version, SYSTEM DIN adjustable door frame

- **solid construction – wooden rail and stile set**
- **large LAMISTONE CPL and SILKSTONE** surface finish
- leaf (slab) stiles - vertical wood grain; panel – vertical wood grain
- white matt, brown matt, graphite or transparent **tempered glass**, thickness: 4 mm



glazing



FORTIMO door, W01S1 version, SYSTEM DIN adjustable door frame




VERSION **W01 / V01** **W01S1 / V1S** **W03 / V02** **W03S1 / V2S**

COLOURS





DOOR FRAMES



EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
white matt tempered glass, thickness: 4 mm	size "100"
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	recuperation trim (only standard height)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("70"-80" – 2 pcs, "90" – 3 pcs)	size "60" (applicable to W01, W01S1)
door closer is not available	third hinge in the door leaf (slab): type K, type C, type M for a width of "70"-80"
	concealed DUO type for a width of "70"-80"
	door lower by 50 mm (rebated system)
	door lower by 55 mm (non-rebated system)
	ventilation trim (p. 159)
	VSG 22.1 laminated matt or transparent glass
	VSG 22.1 laminated black glass
	brown/graphite or transparent tempered 4 mm thick glass



INVERNO



INVERNO door, 01 version, SYSTEM DIN adjustable door frame

- **solid construction – wooden rail and stile set**
- stable solid **chipboard in-fill**
- **large LAMISTONE CPL, SILKSTONE and UNI MAT PLUS** surface finish
- K and C type adjustable and DUO type concealed hinges



strip profile




INVERNO door, 00 version, SYSTEM DIN adjustable door frame




VERSION	00 / V01	0SD / V1SD	01 / V02	01SD / V2SD
---------	----------	------------	----------	-------------

COLOURS




DOOR FRAMES



EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
versions 0SD, 01SD: white matt tempered glass, thickness: 4 mm	size "100" (glazing decoration as in "90")
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	REVES system (version 00, 01) (the door opening angle is 88° above ZW4 range)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs) in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "100" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge	recuperation trim
rebated system, 244, 644 black colour: hinges in the colour of silver, lock in the colour of black	third hinge in the door leaf (slab): type K, type C, type M for a width of "60"- "80" concealed DUO type for a width of "60"- "80"
non-rebated system, 244, 644 black colour: hinges and lock in the colour of black	change of standard DUO hinge to the colour of white or black
transparent pane cannot be used	reinforcement for door closer
	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
	door lower by 50 mm or 100 mm (rebated system)
	door lower by 55 mm or 100 mm (non-rebated system)
	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
	ventilation trim (p. 159)



NOSTRE door, 03 version, SYSTEM DIN adjustable door frame

NOSTRE

- **solid construction – wooden rail and stile set**
- stable solid **chipboard in-fill**
- **large LAMISTONE CPL and SILKSTONE** surface finish
- K and C type adjustable and DUO type concealed hinges



NOSTRE door leaf (slab) decorative strip



NOSTRE door, 03 version, SYSTEM DIN adjustable door frame



VERSION **00 / V01** **OSD / V1SD** **01 / V02** **01SM / V2SM** **01SD / V2SD**




VERSION **02 / V03** **02S1 / V3S1** **02S3 / V3S3** **03 / V04** **03SD / V4SD**

COLOURS



DOOR FRAMES





EQUIPMENT

STANDARD

white matt glass, thickness: 4 mm
 pattern OSD, 01SD, 03SD tempered glass pane white matt, thickness: 4 mm
 single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
 hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame ("60"-80" – 2 pcs, "90" – 3 pcs) or the concealed DUO satin nickel ("60"-70" – 2 pcs, "80" – "90" – 3 pcs)
 in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"-80" – 3 pcs, "90"-100" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge
ADDITIONAL (available at an extra charge)
 size "100" (glazing decoration as in "90")
 REVES system (version 00, 01, 02, 03)
 (the door opening angle is 88° above ZW4 range)

third hinge in the door leaf (slab):
 type K, type C, type M for a width of "60"-80"
 concealed DUO type for a width of "60"-80"
 recuperation trim
 reinforcement for door closer
 bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
 door lower by 50 mm or 100 mm (rebated system)
 door lower by 55 mm or 100 mm (non-rebated system)
 door higher by 50 mm or 100 mm
 (third hinge in the door leaf (slab) is required)
 door higher by 150 mm or 200 mm
 (third hinge in the door leaf (slab) is required)
 ventilation trim (p. 159)



for door leaves with ventilation option



MONA door, W02 version, SYSTEM DIN DUO adjustable door frame

MONA

- **solid construction – wooden rail and stile set**
- **large LAMISTONE CPL** surface finish
- cross rail with vertical woodgrain, black colour panel (W01, W02 version), black laminated glass (W01S1, W02S2 version)
- VSG 22.1 laminated non-transparent black glass



black matt panel



black pane



MONA door, W02 version, SYSTEM DIN DUO adjustable door frame




VERSION **W01** / V01 with black panel **W02** / V02 with black panel **W01S1** / V1S with black pane **W02S2** / V2S with black pane

COLOURS



DOOR FRAMES






EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
VSG 22.1 laminated non-transparent black 4.2 mm thick glass	size "100"
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	recuperation trim (only standard height)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)	size "60" and "60" + "60" (applicable to W01, W01S1)
	third hinge in the door leaf (slab): type K, type C, type M for a width of "70"- "80"
	silver or black concealed DUO type for a width of "70"- "80"
	door lower by 50 mm (rebated system)
	door lower by 55 mm (non-rebated system)
	ventilation trim
	sliding system

p. 159

p. 114-119



for door leaves with ventilation option



SEMPRE door, W02 version, SYSTEM DIN adjustable door frame

SEMPRE



- **solid construction – wooden rail and stile set**
- **large LAMISTONE CPL and SILKSTONE** surface finish
- leaves available with a **one-sided magnetic board (Z/AZ)** and a **one-sided mirror (WL Z, WL A/Z)**
- K and C type adjustable and DUO type concealed hinges
- door available in **10 working days** under the “fast delivery” promotion



glazing



available at an extra charge: VSG 22.1 laminated glass in the colour of black



SEMPRE door, W02 version (door on the left side), SYSTEM DIN adjustable door frame, W02A version (door on the right side), POL-SKONE fixed door frame



VERSION W00 / V01 W01 / V1SD W04 / V4SM W05 / V4SD board* mirror* Z A/Z WLZ WLA/Z W02P / V02 W02 / V2S5 W02S1 / V2S1 W02S2 / V2S2



VERSION W02S3 / V2S3 W02S4 / V2S4 W02A / V2SA W03P / V03 W03 / V3S5 W03S1 / V3S1 W03S2 / V3S2 W03S3 / V3S3 W03S4 / V3S4 W03A / V3SA




VERSION W06 / V05 W07 / V06 W05 VERSE / V6SD

* Z, WLZ - board/mirror on the hinge side, A/Z, WLA/Z - board/mirror on the side opposite to the hinge side

COLOURS






DOOR FRAMES



EQUIPMENT

STANDARD	
white/brown/graphite or transparent 4 mm glass	recuperation trim (only standard height)
version W01, W05 tempered glass 4 mm	third hinge in the door leaf (slab):
version W00, W06, W07, panel thickness: 12 mm	type K, type C, type M for a width of "60"- "80"
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	concealed DUO type for a width of "60"- "70"
hinges: type K satin nickel – for the DIN system door frame, type C satin nickel – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)	door lower by 50 mm (rebated system) (not applicable to WLZ, WLA/Z)
door closer is not available	door lower by 55 mm (non-rebated system) (not applicable to WLZ, WLA/Z)
drop seal is not available	door higher by 50 mm or 100 mm (not applicable to WLZ, WLA/Z, W05 VERSE) (third hinge in the door leaf (slab) is required)
version W05 VERSE - applicable to "70" - "100" width	ventilation trim (p. 159)
ADDITIONAL (available at an extra charge)	VSG 22.1 laminated black glass:
size "100"	version W02, W03
	tempered transparent 4 mm thick glass



DECO door, 00 version, SYSTEM DIN adjustable door frame

DECO



- solid construction – wooden rail and stile set
- surface is covered with a 0.2 mm, 0.5 mm or 0.7 mm thick CPL laminate, which is resistant to abrasion and chemicals
- door available also in III mechanical class
- K and C type adjustable and DUO type concealed hinges



spacer frame



glazing



DECO door, 05 version, SYSTEM DIN adjustable door frame



VERSION	00 / V00	02 / V2S	03SD / V3SD	04 / V4SD	05 / V5SD
---------	----------	----------	-------------	-----------	-----------

To obtain mechanical class III, you need to order the door leaf (slab) with a metal door frame, a wooden door frame or an adjustable DIN mechanical class III frame.
DIN system door frame in III mechanical class, contains reinforcement under the catch plate in the form of a pine bar.
Angular catch plate at extra charge added to the adjustable DIN system door frame price.

COLOURS

SILKSTONE
CPL
0,5 mm

976

Polish oak

993

Royal anthracite

994

Royal ash

995

Royal merbau

996

Polish ash

997

Royal nougat

LAMINATED
CPL
0,2 mm

820

white

222

grey

229

oak

821

anthracite

863

premium walnut

849

industry 3

225

terra oak

227

delano oak

844

black

280

halif oak

228

segato walnut

LAMINATED
CPL
0,5 mm*

945

white structure

252

oak

922

grey structure

926

anthracite structure

965

wenge

963

premium walnut

946

black structure

961

halif oak

LAMINATED
CPL
0,7 mm*

745

white structure

722

grey structure

779

oak

726

anthracite structure

765

wenge

763

premium walnut

746

black structure

761

halif oak

LAMINATED
HPL*

*available upon consultation with the sales department

For door leaves with structure laminate, frame surface with plain laminate.

DOOR FRAMES

rebated
SYSTEM

REVES
SYSTEM

non-rebated
SYSTEM

POL-SKONE
system fixed frame

DIN system
adjustable frame

POL-SKONE system
adjustable frame

metal fixed frame

metal adjustable
frame

DIAGONAL metal

DUO fixed frame

DIN DUO
adjustable frame

DUO adjustable
frame



metal fixed frame

metal adjustable
frame

EQUIPMENT

STANDARD	
white matt or transparent 4 mm thick glass	third hinge in the door leaf (slab) or adjustable pivot hinge:
white matt tempered glass plate (version 03SD, leaves - mechanical class III)	type K, type C, type M for a width of "60"- "80"
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	type T
lock with stainless steel face plate (leaves - mechanical class III)	concealed DUO type for a width of "60"- "70"
hinges: type K - for the DIN system door frame, type C - for the wooden door frame, type M - for the metal door frame or the concealed DUO satin nickel ("60"- "80" - 2 pcs, "90" - 3 pcs)	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)
hinges: type K (leaves - mechanical class III) - 3 pcs	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis)
in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" - 3 pcs, "90"- "110" - 4 pcs) - replacement of standard hinges with hinge type T for an extra charge	reinforcement for door closer
ADDITIONAL (available at an extra charge)	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
size "100" (glazing decoration as in "90")	door lower by 50 mm or 100 mm (rebated system)
size "110" (glazing decoration as in "90")	door lower by 55 mm or 100 mm (non-rebated system)
REVES system (version 00)	non-standard height
recuperation trim	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
CPL laminate available at an extra charge 0.5 mm, 0.7 mm ("60" - "90")*	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
CPL laminate available at an extra charge 0.5 mm, 0.7 mm ("90" - "110")*	ventilation trim (p. 159)
extra charge for SILKSTONE CPL colours	tempered glass (version 02, 04, 05)
perforated chipboard in-fill	tempered transparent 4 mm thick glass
solid chipboard in-fill (third hinge recommended)	edges in other colours - black, grey, graphite - are available
	ABS edging in black, white, titano, polish oak or anthracite (rebated system) (not applicable to REVES)
	*an extra charge to the standard height

91



SEMPRE LUX door, W04 version, SYSTEM DIN adjustable door frame

SEMPRE LUX



- **solid construction – wooden rail and stile set**
- **natural veneers** surface finish
- **ecological UV varnish** ensures incredible permanence of colour and scratch resistance
- leaves available with a **one-sided magnetic board** (Z/AZ) and a **one-sided mirror** (WL Z, WL A/Z)
- K and C type adjustable and DUO type concealed hinges



rail and stile set wood grain



wood grain of panels - horizontal



SEMPRE LUX door, W03S4 version, POL-SKONE SYSTEM adjustable door frame



VERSION **W00** / V01 **W01** / V1SD **W04** / V4SM **W05** / V4SD board* mirror* **W02P** / V02 **W02** / V2S5 **W02S1** / V2S1 **W02S2** / V2S2



VERSION **W02S3** / V2S3 **W02S4** / V2S4 **W02A** / V2SA **W03P** / V03 **W03** / V3S5 **W03S1** / V3S1 **W03S2** / V3S2 **W03S3** / V3S3 **W03S4** / V3S4 **W03A** / V3SA


* Z, WLZ - board/mirror on the hinge side, A/Z, WLA/Z - board/mirror on the side opposite to the hinge side

COLOURS



VERSION **W06** / V05 **W07** / V06 **W05 VERSE** / V6SD

DOOR FRAMES




EQUIPMENT

STANDARD

white/brown/graphite or transparent 4 mm glass
version W01, W05 – tempered glass pane 4 mm
version W00, panel thickness: 12 mm
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
hinges: type K satin nickel – for the DIN system door frame, type C satin nickel – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)
door closer is not available
drop seal is not available
version W05 VERSE - applicable to "70" - "100" width
ADDITIONAL (available at an extra charge)
size "100"

recuperation trim (only standard height)
third hinge in the door leaf (slab):
type K, type C, type M for a width of "60"- "80"
concealed DUO type for a width of "60"- "80"
door lower by 50 mm (rebated system) (not applicable to WLZ, WLA/Z)
door lower by 55 mm (non-rebated system) (not applicable to WLZ, WLA/Z)
door higher by 50 mm or 100 mm (not applicable to WLZ, WLA/Z) (third hinge in the door leaf (slab) is required)
ventilation trim (p. 159)
VSG 22.1 laminated black glass:
version W02, W03
tempered transparent 4 mm thick glass



TEO

NEW

- door covered with **natural veneer**
- ecological **UV varnish** ensures incredible **permanence of colour** and **scratch resistance**
- an unique **decorative milling** in the colour of **black**, **protected with varnish**

TEO door, VF1 version, SYSTEM DIN adjustable door frame



TEO door, VF6 version, SYSTEM DIN adjustable door frame




VERSION	VF1	VF2	VF3	VF4
---------	-----	-----	-----	-----




VERSION	VF5	VF6	VF7
---------	-----	-----	-----

COLOURS





DOOR FRAMES



EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
wooden rail and stile set topped with two HDF boards with the veneered surface with decorative milled in the colour of black	size "100"
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm) in the colour of black	third hinge in the door leaf (slab): type T for a width of "60"- "80" concealed DUO type for a width of "60"- "70"
black hinges: type T – for the DIN system door frame and the metal door frame, ("60"- "80" – 2 pcs, "90" – 3 pcs) or the concealed DUO ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs)	the lock colour replaced with silver colour
	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)
	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis)
	reinforcement for door closer
	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
	ventilation trim



ESPINA door, W03 version, SYSTEM DIN adjustable door frame

ESPINA



- **solid construction – wooden rail and stile set**
- stable perforated **chipboard in-fill**
- **perfect combination** of black and natural veneer
- ecological UV varnish ensures incredible permanence of colour and scratch resistance
- white matt **tempered glass**, thickness: 6 mm or laminated glass VSG 44.2 in the colour of black, 8.5 mm thick
- K and C type adjustable and DUO type concealed hinges







wood grain














ESPINA door, W03 version, SYSTEM DIN door frame

NEW VERSIONS					
VERSION	W00 / V00	W01 / V1S	W01 / V1S	W02 / V01	W03 / V03
					

COLOURS

VENEERED GROUP A		334 European oak
VENEERED GROUP B		404 dark walnut
		405 bright walnut
VENEERED GROUP D		460 makassar

DOOR FRAMES

<div>REVES SYSTEM</div>	<div>rebated SYSTEM</div>						
	<div>non-rebated SYSTEM</div>						
		DUO fixed frame	DIN DUO adjustable frame	DUO adjustable frame	VERTIGO adjustable frame	metal fixed frame	metal adjustable frame

EQUIPMENT



STANDARD

white matt tempered glass, thickness: 6 mm
laminated glass 44.2 in the colour of black, 8.5 mm thick
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame ("60"- "80" – 2 pcs, "90" – 3 pcs) or the concealed DUO satin nickel ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs)
in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "110" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge

ADDITIONAL (available at an extra charge)

size "100"
size "110" (applicable to version W00, W02, W03)
REVES system (version W00, W01, W02, W03)
recuperation trim
perforated chipboard in-fill (third hinge in the door leaf (slab) is required)

third hinge in the door leaf (slab):
type K, type C, type M for a width of "60"- "80"
concealed DUO type for a width of "60"- "80"
rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis) not applicable to W01
rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis) not applicable to W01
reinforcement for door closer (not applicable to W01 version)
bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
door lower by 50 mm or 100 mm (rebated system)
door lower by 55 mm or 100 mm (non-rebated system)
door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
ventilation trim (version W00, W01, W02, W03) (p. 159)



DECO LUX

with the Soft frame



- **solid construction – wooden rail and stile set**
- door covered with **natural veneers**
- **ecological UV varnish** ensures incredible permanence of colour and scratch resistance
- K and C type adjustable and DUO type concealed hinges

DECO LUX door, 00 version, SYSTEM DIN adjustable door frame

















DECO LUX door, 00 version, SYSTEM DIN door frame
















VERSION	00 / V00	02 / V2S	03SD / V3SD	04 / V4SD	05 / V5SD
---------	----------	----------	-------------	-----------	-----------

COLOURS

VENEERED GROUP A	 311 bright oak	 312 swiss pine	 334 European oak	
	 323 rustic oak	 340 ebony	 376 steel oak	 390 natural walnut
	 404 dark walnut	 405 bright walnut	 421 cappuccino	 422 mocca
VENEERED GROUP C	 370 white-stained oak	 450 white matt	 451 black matt	
				VENEERED GROUP D



DOOR FRAMES



<div>rebated SYSTEM</div> 	 POL-SKONE system fixed frame	 DIN system adjustable frame	 POL-SKONE system adjustable frame	 metal fixed frame	 metal adjustable frame	
<div>non-rebated SYSTEM</div> 	 DUO fixed frame	 DIN DUO adjustable frame	 DUO adjustable frame	 VERTIGO adjustable frame	 metal fixed frame	 metal adjustable frame

EQUIPMENT

STANDARD	
white matt or transparent 4 mm thick glass	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis)
version 03SD: white matt tempered glass	rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	reinforcement for door closer
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "110" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge	door lower by 50 mm or 100 mm (rebated system)
ADDITIONAL (available at an extra charge)	door lower by 55 mm or 100 mm (non-rebated system)
size "100" (glazing decoration as in "90")	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
size "110" (glazing decoration as in "90")	door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)
REVES system (version 00)	ventilation trim (p. 159)
recuperation trim	tempered glass (version 02, 04, 05)
perforated chipboard in-fill	tempered transparent 4 mm thick glass
solid chipboard in-fill (third hinge recommended)	DECO LUX door in mechanical class III available on request
third hinge in the door leaf (slab): type K, type C, type M for a width of "60"- "80"	technical door catalogue
concealed DUO type for a width of "60"- "80"	




ETIUDA LUX door, A01 version, SYSTEM DIN adjustable door frame

ETIUDA LUX

- **solid construction – wooden rail and stile set**
- door covered with **natural veneers**
- **ecological UV varnish** ensures incredible permanence of colour and scratch resistance
- white matt or graphite **tempered glass**, thickness: 6 mm
- aluminium decorative strips in the colour of silver or black
- K and C type adjustable and DUO type concealed hinges



aluminium decorative strips in the colour of silver or black



top door leaf (slab) edge without a rebate



option: aluminium decorative strips in the colour of black



ETIUDA LUX door, A02 version, SYSTEM DIN adjustable door frame














VERSION	B0 / V00	B1 / VD11	A01 / V1SA	A02 / V2SA	A03 / V3SA
---------	----------	-----------	------------	------------	------------

COLOURS




VENEERED GROUP A						
	311 bright oak	312 swiss pine	334 European oak			
VENEERED GROUP B						
	323 rustic oak	340 ebony	351 marrone	376 steel oak		
						
	390 natural walnut	404 dark walnut	405 bright walnut	421 cappuccino	422 mocca	424 teak

DOOR FRAMES

rebated SYSTEM						
	POL-SKONE system fixed frame	DIN system adjustable frame	POL-SKONE system adjustable frame	metal fixed frame	metal adjustable frame	
non-rebated SYSTEM						
	DUO fixed frame	DIN DUO adjustable frame	DUO adjustable frame	VERTIGO adjustable frame	metal fixed frame	metal adjustable frame

EQUIPMENT

STANDARD	
white/brown matt tempered glass, thickness: 6 mm	reinforcement for door closer (not applicable to version A01, A02, A03)
black-coloured glass pane is not available	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim) (not applicable to version A01, A02, A03)
glazing width in the A01 version – 54 mm; A02 – 205 mm, A03 – 276 mm*	door lower by 50 mm or 100 mm (rebated system) (not applicable to version A01, A02, A03)
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	door lower by 55 mm or 100 mm (non-rebated system) (not applicable to version A01, A02, A03)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs)	door higher by 50 mm or 100 mm (not applicable to version A01, A02, A03) (third hinge in the door leaf (slab) is required)
ADDITIONAL (available at an extra charge)	door higher by 150 mm or 200 mm (not applicable to version A01, A02, A03) (third hinge in the door leaf (slab) is required)
size "100"	version A01, A02, A03 door lower by 50 mm (rebated system)
size "110" (applicable to version B0, B1)	version A01, A02, A03 door lower by 55 mm (non-rebated system)
solid chipboard in-fill (version B0, A01, A02, A03) (third hinge recommended)	version A01, A02, A03 door higher by 100 mm (third hinge in the door leaf (slab) is required)
third hinge in the door leaf (slab): type K, type C, type M for a width of "60"- "80" concealed DUO type for a width of "60"- "80"	version A01, A02, A03 door higher by 200 mm (third hinge in the door leaf (slab) is required)
rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis) (applicable to version B0)	ventilation trim (applicable to versions B0) (p. 159)
rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis) (applicable to version B0)	ventilation trim A01 with the "60" - "100" widths (p. 159)
change of colour of decorative strips to black:	ventilation trim A02, A03 with the "70" - "100" widths (p. 159)
version B1	tempered 6 mm glass in the colour of graphite or transparent
version A01-A03	sliding system (not applicable to version A01)
*+/- 2 mm tolerance	



for door leaves with ventilation option



FORTIMO LUX door, W03 version, SYSTEM DIN adjustable door frame

FORTIMO LUX

- **solid construction – wooden rail and stile set**
- door covered with **natural veneers**
- **ecological UV varnish** ensures incredible permanence of colour and scratch resistance
- cross rails come with a **vertical wood grain**
- white and brown matt, graphite or transparent **tempered glass**, thickness: 4 mm
- K and C type adjustable and DUO type concealed hinges



glazing, panel



interconnection of architraves at the 45° angle



FORTIMO LUX door, W03S1 version, SYSTEM VERTIGO adjustable door frame



VERSION	W01 / V01	W01S1 / V1S	W03 / V02	W03S1 / V2S
---------	-----------	-------------	-----------	-------------

COLOURS

VENEERED GROUP A

311
bright oak

312
swiss pine

334
European oak

VENEERED GROUP B

323
rustic oak

340
ebony

351
marrone

376
steel oak

390
natural walnut

404
dark walnut

405
bright walnut

421
cappuccino

422
mocca

424
teak

VENEERED GROUP C

370
white-stained oak

DOOR FRAMES

rebated SYSTEM

POL-SKONE system fixed frame

DIN system adjustable frame

POL-SKONE system adjustable frame

metal fixed frame

metal adjustable frame

non-rebated SYSTEM

DUO fixed frame

DIN DUO adjustable frame

DUO adjustable frame





VERTIGO adjustable frame

metal fixed frame

metal adjustable frame

EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
white matt tempered glass, thickness: 4 mm	size "100"
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)	recuperation trim (only standard height)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("70"- "80" – 2 pcs, "90" – 3 pcs)	size "60" (applicable to W01, W01S1)
	third hinge in the door leaf (slab): type K, type C, type M for a width of "60"- "80" concealed DUO type for a width of "60"- "80"
	door lower by 50 mm (rebated system)
	door lower by 55 mm (non-rebated system)
	laminated glass VSG 22.1 matt, transparent or black
	ventilation trim (p. 159)
	brown/graphite or transparent tempered 4 mm thick glass



SONATA LUX




SONATA LUX door, W5 version, SYSTEM DIN adjustable door frame


- **solid construction – wooden rail and stile set**
- **stable perforated chipboard in-fill**
- door covered with **natural veneers**
- **ecological UV varnish** ensures incredible permanence of colour and scratch resistance
- **aluminium decors** on the leaf (slab) surface in the colour of black, golden gloss, chrome gloss
- K and C type adjustable and DUO type concealed hinges



SONATA LUX door, W2 version, DIN adjustable door frame




VERSION **W1 / VD1** **W2 / VD2** **W4 / VD4** **W5 / VD5**




VERSION **W6 / VD6** **W7 / VD7** **W8 / VD8**

COLOURS



DOOR FRAMES



EQUIPMENT

STANDARD

single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – for the metal door frame or the concealed DUO satin nickel ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs) in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90"- "100" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge
version W8: no possibility to use a ventilation slot or a ventilation grill

ADDITIONAL (available at an extra charge)

size "100"
REVES system
recuperation trim
solid chipboard in-fill (third hinge recommended)
third hinge in the door leaf (slab):
type K, type C, type M for a width of "60"- "80"
concealed DUO type for a width of "60"- "70"
the type T hinge in colour of black (rebated system)
the DUO hinge colour replaced with black colour (non-rebated system)

the DUO lock colour replaced with black colour (non-rebated system)

rail and stile set (allowing the user to shorten the door leaf (slab) by max. 50 mm on a do-it-yourself basis) (not applicable to version W8)

rail and stile set (allowing the user to shorten the door leaf (slab) by max. 90 mm on a do-it-yourself basis) (not applicable to version W8)

reinforcement for door closer

bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)

door lower by 50 mm (rebated system)

door lower by 55 mm (non-rebated system)


door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)

door higher by 150 mm or 200 mm (third hinge in the door leaf (slab) is required)

ventilation trim (p. 159)

aluminium decors in black, chrome gloss, golden gloss

leaf (slab) edge in the colour of black



for door leaves with ventilation option



INTERSOLID door, 02 version, SYSTEM DIN adjustable door frame

INTERSOLID



- **solid construction – wooden rail and stile set**
- door covered with **natural veneers**
- **ecological UV varnish** ensures incredible permanence of colour and scratch resistance
- K and C type adjustable hinges



INTERSOLID frame












INTERSOLID door, 05 version (door on the left side), 05 S8 version (door on the right side), SYSTEM DIN adjustable door frame



VERSION	02 / V02	02S6 / V2S6	05 / V05	05S8 / V5S8	08 / V08	08S10 / V8S10
---------	----------	-------------	----------	-------------	----------	---------------

COLOURS


VENEERED GROUP A							
	311 bright oak	312 swiss pine	334 European oak				
VENEERED GROUP B							
	323 rustic oak	340 ebony	404 dark walnut	405 bright walnut	421 cappuccino	422 mocca	424 teak

DOOR FRAMES

	POL-SKONE system fixed frame	DIN system adjustable frame	POL-SKONE system adjustable frame	metal fixed frame	metal adjustable frame

EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
white matt or transparent 4 mm thick glass	size "100"
single-point mortise lock, spacing: 72 mm key-operated or cylinder type, for a cylinder or a bathroom lock	third hinge in the door leaf (slab): type K, type C, type M for a width of "60"- "80"
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – door leaf (slab) for the metal door frame ("60"- "80" – 2 pcs, "90" – 3 pcs)	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
	door lower by 50 mm
	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
	ventilation trim (p. 159)
	white matt or transparent tempered 4 mm thick glass



for door leaves with ventilation option



INTERSOLID II door, 02 S6 version, SYSTEM DIN adjustable door frame

INTERSOLID II



- **solid construction – wooden rail and stile set**
- door covered with **natural veneers**
- **ecological UV varnish** ensures incredible permanence of colour and scratch resistance
- **milled panel**
- K and C type adjustable hinges



wooden muntin



door leaf (slab) profile



INTERSOLID II door, 02 version, adjustable door frame



VERSION	01 / V01	01S6 / V1S6	02 / V02	02S6 / V2S6	03 / V03	03S6 / V3S6	04 / V04	04S8 / V4S8	05 / V05
---------	----------	-------------	----------	-------------	----------	-------------	----------	-------------	----------




VERSION	05S8 / V5S8	06 / V06	06S8 / V6S8	07 / V07	07S10 / V7S10	08 / V08	08S10 / V8S10	09 / V09	09S10 / V9S10
---------	-------------	----------	-------------	----------	---------------	----------	---------------	----------	---------------

COLOURS





DOOR FRAMES



EQUIPMENT


STANDARD	ADDITIONAL (available at an extra charge)
white matt or transparent 4 mm thick glass	size "100"
single-point mortise lock, spacing: 72 mm key-operated or cylinder type, for a cylinder or a bathroom lock	third hinge in the door leaf (slab): type K, type C, type M for a width of "60"- "80"
hinges: type K – for the DIN system door frame, type C – for the wooden door frame, type M – door leaf (slab) for the metal door frame ("60"- "80" – 2 pcs, "90" – 3 pcs)	bottom rail and stile set protection against excessive moisture impact (not applicable to leaves with ventilation trim)
	door lower by 50 mm
	door higher by 50 mm or 100 mm (third hinge in the door leaf (slab) is required)
	ventilation trim (p. 159)
	white matt or transparent tempered 4 mm thick glass



PASSO



- **solid construction – wooden rail and stile set**
- large LAMISTONE CPL, SILKSTONE and **natural veneers**
- **surface finish**
- stile - vertical or horizontal wood grain (version H), horizontal cross rails
- 24 mm thick panels
- K and C type adjustable and DUO type concealed hinges



rail and stile set, cross rails and glass pane connection



top door leaf (slab) edge without a rebate

PASSO door, W05 version, SYSTEM DIN DUO adjustable door frame



PASSO door, W03 version (door on the left side), W02 (door on the right side), DUO adjustable door frame



VERSION	W01 / V01	W02 / V1S1	W03 / V1S2	W04 / V1S3	W05 / V1S4	W06 / V2SD	W07 / V3SD
---------	-----------	------------	------------	------------	------------	------------	------------

COLOURS


LAMISTONE CPL	231 halif oak	243 delano oak	244 black	250 terra oak	258 white	260 white oak
	263 premium walnut	265 wenge	289 grey	531 anthracite	232 segato walnut	
SILKSTONE	230 gran oak	254 Royal anthracite H	255 Polish ash H	276 Polish oak	293 Royal anthracite	294 Royal ash
	295 Royal merbau	296 Polish ash	297 Royal nougat	299 Royal ash H		
VENEERED GROUP A	312 swiss pine	334 European oak				
VENEERED GROUP B	340 ebony	376 steel oak	404 dark walnut	405 bright walnut	421 cappuccino	422 mocca
					424 teak	

DOOR FRAMES

rebated SYSTEM				
	POL-SKONE system fixed frame	DIN system adjustable frame	POL-SKONE system adjustable frame	
non-rebated SYSTEM				
	DUO fixed frame	DIN DUO adjustable frame	DUO adjustable frame	VERTIGO adjustable frame

EQUIPMENT

STANDARD	ADDITIONAL (available at an extra charge)
<p> painted white/brown matt or transparent 4 mm glass single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm) hinges: type K – for the DIN system door frame, type C – for the wooden door frame or the concealed DUO satin nickel ("60"- "80" – 2 pcs, "90" – 3 pcs) door closer is not available drop seal is not available </p>	<p> third hinge in the door leaf (slab): type K, type C for a width of "60"- "80" concealed DUO type for a width of "60"- "80" door lower by 55 mm (non-rebated system) door lower by 50 mm (rebated system) ventilation trim (p. 159) tempered transparent 4 mm thick glass </p>



ESTATO LUX

- **solid construction – wooden rail and stile set**
- **stable perforated chipboard** in-fill
- door covered with **natural veneers**
- **ecological UV varnish** ensures incredible permanence of colour and scratch resistance
- **vertical wood grain**
- **security, tempered** glass pane, white/brown matt, thickness: 6 mm or **VSG 44.2 laminated glass** in the colour of black, thickness: 8,5 mm



ESTATO LUX door, A01 version, SYSTEM DIN adjustable door frame

black pane



ESTATO LUX door, A01 version, SYSTEM DIN DUO adjustable door frame



WHITE/BROWN MAT TEMPERED GLASS

BLACK LAMINATED GLASS

VERSION	A01 / V1SA	A02 / V2SA	A03 / V3SA	A01 / V1SA black glass	A02 / V2SA black glass	A03 / V3SA black glass
---------	------------	------------	------------	------------------------	------------------------	------------------------




WHITE MATT LAMINATED GLASS

VERSION	A01 / V1SA	A02 / V2SA	A03 / V3SA
---------	------------	------------	------------

COLOURS



DOOR FRAMES



EQUIPMENT

STANDARD
white/brown matt tempered glass, thickness: 6 mm (versions A01-58 mm, A02-208 mm, A03-280 mm)*
laminated glass 44.2 in the colour of black or white matt, 8.5 mm thick
single-point mortise lock, spacing: 72 mm (rebated system) or magnetic mortise lock (non-rebated system), key-operated (spacing: 90 mm), for a cylinder (spacing: 85 mm) or a bathroom lock (spacing: 90 mm)
hinges: type T – for the DIN system door frame or for the metal door frame, type C – for the wooden door frame ("60"- "80" – 2 pcs, "90" – 3 pcs) or the concealed DUO satin nickel for non-rebated system ("60"- "70" – 2 pcs, "80"- "90" – 3 pcs)
door closer is not available
ADDITIONAL (available at an extra charge)
size "100"
REVES system
solid chipboard in-fill (third hinge recommended)
*+/- 1-2 mm tolerance

third hinge in the door leaf (slab): type C for a width of "60"- "80" type T for a width of "60"- "80" concealed DUO type for a width of "60"- "70"
version A01, A02, A03 door lower by 50 mm (rebated system)
version A01, A02, A03 door lower by 55 mm (non-rebated system)
version A01, A02, A03 door higher by 100 mm (third hinge in the door leaf (slab) is required)
version A01, A02, A03 door higher by 200 mm (third hinge in the door leaf (slab) is required)
ventilation trim (not applicable to versions A02, A03) (p. 159)
ventilation trim A01 with the "60" - "100" widths (p. 159)
ventilation trim A02, A03 with the "70" - "100" widths (p. 159)
tempered 6 mm glass in the colour of graphite or transparent
sliding system (not applicable to the version A01)

p. 114-119


SLIDING SYSTEM FOR IN-WALL INSTALLATION

EQUIPMENT

hook lock (chrome) for the privacy lock	
system brushes	
door leaf (slab) alone for the sliding system	
replacement of the regular lock with a key-operated bathroom lock (WC)	
cassettes for the in-wall sliding door system*	
pull handles for sliding doors for the in-wall installation	p. 163
SP60 closer** for the single leaf (slab) door	
SP60 closer** for the double leaf (slab) door	

An encasement and cassette higher by 100 mm and 200 mm are available on request.
A non-symmetrical installation is available upon consultations with the POL-SKONE sales department.

BUILT-IN SLIDING DOOR, RIGHT-LEFT SYMMETRICAL



single cassette (100 or 125 mm)
leaf (slab) dimensions
"60" (G/60)
"70" (G/70)
"80" (G/80)
"90" (G/90)
"100" (G/100)
extra charge
cassette higher by 100 mm Ho=2175 mm
cassette higher by 200 mm Ho=2275 mm
for the synchronisation (simultaneous opening) system in double leaf (slab) doors

double cassette (100 or 125 mm)
leaf (slab) dimensions
"60"+"60" (GG/60)
"70"+"70" (GG/70)
"80"+"80" (GG/80)
"90"+"90" (GG/90)
"100"+"100" (GG/100)
auxiliary products
white brush SB 01
black brush SB 03

* Cassettes for the in-wall sliding door system (the minimum thickness of the single or double cassette with the G/K encasement is: 100 mm for flat leaves; 125 mm for leaves with a decor and glazed with frames)

** Equipped with the SP60 closer for the system concealed in the wall:
- single leaf (slab) door width "60" – "100"
- double leaf (slab) door width "60" + "60" – "90" + "90" without the leaf (slab) or double leaf (slab) door closing synchronisation width
"80" + "80" – "90" + "90" with the leaf (slab) closing synchronization.
Due to the specific installation procedure, the SP60 door closer cannot be used in the following door models: ETIUDA/ETIUDA LUX – A02, A03; PASSO, ESTADO/ESTATO LUX – A02, A03.



Sliding system for in-wall installation

IN-WALL ENCASEMENT SYSTEM

In-wall system price = selected leaf (slab) price + cassette price + price of the single leaf (slab) door in-wall set acc. to the table below. DUO in-wall system price = DUO price + cassette price + price of the single leaf (slab) door in-wall set acc. to the table below.

Complete single leaf (slab) door in-wall system for the 100 mm cassette


I

For leaves: ARCO, ETIUDA, ETIUDA LUX, MODERN, INTERSOLID II, SEMPRE, SEMPRE LUX, FORTIMO, FORTIMO LUX, SONATA, ESTATO, FIORI, SEDO, EGRO, VERI, MODO, SUBITO.

For flush leaves: INTER-AMBER, IMPULS, SIMPLE, FIORD, DECO LUX, SUBLIME, HAPTIC, ESTATO LUX, TIARA, CAMBIO, DECO, ESPINA, MONA, PASSO.

single leaf (slab) door	ECO TOP	UNI MAT PLUS	PAINTED* white	for the laminated type	VENEERED		
				HIGH TOP			
				LAMISTONE CPL			
				SILKSTONE	GROUP A	GROUP B	GROUP C, D
range in mm 100-106							

Variant I – Table I




Complete single leaf (slab) door in-wall system for the 125 mm cassette (flush or glazed versions)

II

For leaves: ARCO, INTER-AMBER, IMPULS, ETIUDA, ETIUDA LUX, DECO, SIMPLE, FIORD, CAMBIO, MODERN, SEMPRE, SEMPRE LUX, INTERSOLID II, FORTIMO, FORTIMO LUX, SONATA, SUBLIME, ESTATO, FIORI, ESTATO LUX, VILANO, HAPTIC, TIARA, VERTIGO, DECO LUX, ESPINA, MONA, PASSO, SEDO, CREATO, EGRO, VERI, MODO, SUBITO.

single leaf (slab) door	ECO TOP	UNI MAT PLUS	PAINTED* white	for the laminated type	VENEERED		
				HIGH TOP			
				LAMISTONE CPL			
				SILKSTONE	GROUP A	GROUP B	GROUP C, D
range in mm 125-320							

Variant II – Table II




Complete single leaf (slab) door in-wall system for the 125 mm cassette (leaves with decoration)

III

For leaves: NOSTRE, INTERSOLID, INVERNO

single leaf (slab) door	ECO TOP	PAINTED* white	for the laminated type	VENEERED		
			HIGH TOP			
			LAMISTONE CPL			
			SILKSTONE	GROUP A	GROUP B	GROUP C, D
range in mm 125-300						

Variant III – Table III



EXTRA CHARGES

for double leaf (slab) doors
width "100"
architraves 80 mm
architraves interconnected at the 90° angle

WIDTH													
single leaf (slab) door Dimensions on the external side of: leaves (Ssb, Hsb), door (Sd, Hd)							double leaf (slab) door Dimensions on the external side of: leaves (Ssb, Hsb), door (Sd, Hd)						
TABLE I, II, III													
type	Ssb	Sd	So	Sk	Sp	Sop	type	Ssb	Sd	So	Sk	Sp	Sop
"60"	644	625	650	1307	510	725	"60"+"60"	1288	1216	1250	2520	1030	1316
"70"	744	725	750	1507	610	825	"70"+"70"	1488	1416	1450	2920	1230	1516
"80"	844	825	850	1707	710	925	"80"+"80"	1688	1616	1650	3320	1430	1716
"90"	944	925	950	1907	810	1025	"90"+"90"	1888	1816	1850	3720	1630	1916
"100"	1044	1025	1050	2107	910	1125							
HEIGHT								Hsb	Hd	Ho	Hk	Hp	Hop
								2033	2038	2075	2116	2016	2088

Ssb - door leaf (slab) external width
Sd - door frame external width
So - door frame installation hole width
Sk - cassette external width
Sp - clear opening width
Sop - architrave external width
Hsb - door leaf (slab) external height
Hd - door frame external height
Ho - door frame installation hole height
Hk - cassette external height
Hp - clear opening height
Hop - architrave external height

*RAL and NCS colours (except the metallic ones)
– available at an extra charge according to the colour specification table for particular models


SLIDING system ON-WALL

EQUIPMENT ON-WALL SYSTEM	
standard:	p. 163
long brass pull handle chrome satin (U4)	

optional:	p. 163
pull handles or hook lock	
SP60 closer* for the single leaf (slab) door	
SP60 closer* for the double leaf (slab) door	
BIAS closer for the single leaf (slab) door	
BIAS closer for the double leaf (slab) door	

*Equipped with the SP60 closer for the on-wall system:
 - single leaf (slab) door width "60 – 100"
 - double leaf (slab) door width "60 + 60" – "90 + 90"
 Due to the specific installation procedure, the SP60 door closer cannot be used in the following door models: ETIUDA /ETIUDA LUX – A02, A03; PASSO; ESTADO/ESTATO LUX – A02, A03.

In glazed doors – ornament on the outside, in doors with a lock - privacy lock on the inside.
 In double leaf (slab) right-hand doors – the lock in the right leaf (slab);
 in double leaf (slab) left-hand doors - the lock in the left leaf (slab).



LENGTHS OF MASKING STRIPS FOR THE ON-WALL SYSTEM

"60" – 1795 mm	"60"+"60" – 3448 mm*
"70" – 1795 mm	"70"+"70" – 3448 mm*
"80" – 1795 mm	"80"+"80" – 3448 mm*
"90" – 2045 mm	"90"+"90" – 3948 mm*
"100" – 2295 mm	

* The masking strip is combined of two elements;
 the masking strip height: 110 mm.



on-wall system guide rail



masking panel and stop post of the on-wall system





door in the SLIDING ON-WALL system

ON-WALL SYSTEM
the price includes: the guide, the masking strip and the stop post*

single leaf (slab) door	PAINTED** white, beige, grey	ECO TOP	UNI MAT PLUS	for the laminated type	VENEERED		
				HIGH TOP	GROUP A	GROUP B	GROUP C, D
				LAMISTONE CPL			
				SILKSTONE			
		wood-like foil		wood-like laminate			
extra charge added to a selected model of interior leaf (slab)							

EXTRA CHARGES

for double leaf (slab) doors	
door lower by 50 mm	
door higher by 50 mm or 100 mm	
door higher by 150 mm or 200 mm	
architraves interconnected at the 90° angle (architraves 80 mm width only)	
architraves 80 mm width (not applicable to PAINTED)	
ventilation options	p. 159
* optionally available: a version with a wall encasement system (a "finishing tunnel") – the price depends on the wall thickness	
** RAL and NCS colours - available at an extra charge according to the colour specification table.	
The sliding system leaf (slab) is available as a separate item.	



For the on-wall system, we recommend the ZN tunnel encasement (p. 152)
If the tunnel system with 80 mm architraves is used,
the lintel architrave must be trimmed during the installation.


WIDTH					
single leaf (slab) door dimensions on the external side of leaves (Ssb, Hsb) and of the installation hole (So, Ho)			double leaf (slab) door (without stop post) dimensions on the external side of leaves (Ssb, Hsb) and of the installation hole (So, Ho)		
type	Ssb	So	type	Ssb	So
"60"	644	620	"60"+"60"	1288	1240
"70"	744	720	"70"+"70"	1488	1440
"80"	844	820	"80"+"80"	1688	1640
"90"	944	920	"90"+"90"	1888	1840
"100"	1044	1020			
HEIGHT			H _o	H _{sb}	H _m
			2020	2033	2138

WIDTH							
single leaf (slab) door dimensions on the external side of leaves (Ssb, Hsb) and of the installation hole (So, Ho)				double leaf (slab) door (without stop post) dimensions on the external side of leaves (Ssb, Hsb) and of the installation hole (So, Ho)			
type	Ssb	So	Sd	type	Ssb	So	Sd
"60"	644	670	649	"60"+"60"	1288	1305	1282
"70"	744	770	749	"70"+"70"	1488	1505	1482
"80"	844	870	849	"80"+"80"	1688	1705	1682
"90"	944	970	949	"90"+"90"	1888	1905	1882
"100"	1044	1070	1049				
HEIGHT							
				H _o	H _d	H _{sb}	H _m
				2055	2044	2033	2138

SLIDING system

ON-WALL PREMIUM

EQUIPMENT ON-WALL PREMIUM SYSTEM	
standard:	
longitudinal pull handle in the colour of chrome-satin (U4)	p. 163
optional:	
pull handles for sliding leaves	p. 163



LENGTHS OF MASKING STRIPS FOR THE ON-WALL PREMIUM SYSTEM	
"60"	1800 mm
"70"	1800 mm
"80"	1800 mm
"90"	2000 mm
"60"+"60"	1800 + 1800 mm
"70"+"70"	1800 + 1800 mm
"80"+"80"	1800 + 1800 mm
"90"+"90"	2000 + 2000 mm

Hm - door frame external height of the masking strip
Ho - installation hole height
Hsb - door leaf (slab) external height
Hd - door frame external height
So - installation hole width
Ssb - door leaf (slab) external width
Sd - door frame external width

WIDTH					
single leaf (slab) door			double leaf (slab) door		
dimensions on the external side of leaves (Ssb, Hsb) and of the installation hole (So, Ho)			dimensions on the external side of leaves (Ssb, Hsb) and of the installation hole (So, Ho)		
type	Ssb	So	type	Ssb	So
"60"	644	620	"60"+"60"	1288	1240
"70"	744	720	"70"+"70"	1488	1440
"80"	844	820	"80"+"80"	1688	1640
"90"	944	920	"90"+"90"	1888	1840
height: (Hsb) 2033, (Ho) 2020, height from the floor level to the masking strip top edge - 2103 mm					



door in the SLIDING ON-WALL PREMIUM system

SLIDING system

ON-WALL MOVI



Leaf (slab) STRUCTURE

Non-rebated system door leaf (slab). The door is made of a **wooden rail and stile set** topped with two plain HDF boards with the ECO TOP, LAMISTONE CPL and SILKSTONE surface, laminated, veneered and painted.
The standard in-fill is a honeycomb-like layer.
The rated door leaf (slab) thickness is 40 mm.

DOOR Leaf (slab) FINISH

Smooth painted, veneered, laminated surfaces or with ECO TOP, LAMISTONE CPL, SILKSTONE finishes.

ACCESSORIES

Standard equipment:

long brass pull handle chrome satin (U4)

Auxiliary equipment:

perforated chipboard in-fill

leaf (slab) lower by 50 mm

leaf (slab) higher by 50 mm

leaf (slab) higher by 100 mm

leaf (slab) higher by 150 mm

leaf (slab) higher by 200 mm



The tunnel system installation is not available for the MOVİ sliding system.


Complete MOVİ system price = MOVİ leaf (slab) price
+ MOVİ sliding system price


SLIDING ON-WALL MOVİ SYSTEM

leaf (slab) width
"70" - "100"
"110"

LEAF (SLAB) FOR MOVİ SLIDING SYSTEM

single leaf (slab) door	ECO TOP	UNI MAT PLUS	LAMISTONE CPL	laminated CPL 0,2 mm	PAINTED white, beige, grey	BLACK RAL 9005	VENEERED			ESPINA	
			SILKSTONE				GROUP A	GROUP B	GROUP C	GROUP A	GROUP B
								"70" -"90"			
								"100" -"110"			





GALIO door, S5 version, steel angle bracket door frame

GALIO



Internal doors for use in public utility buildings such as offices as well as for residential units.
Internal doors manufactured in accordance with PN-EN 14351-2:2018.








double-sided angle bracket



hinge




GALIO door, S6 version, steel angle bracket door frame



WIDTH	Ss	Sd	So
"60"	625	639	642
"70"	725	739	742
"80"	825	839	842
"90"	925	939	942
"100"	1025	1039	1042
Hs - 2040 mm, Hd - 2057 mm, Ho - 2060 mm			
- 50 mm height - Hs - 1990 mm, Hd - 2007 mm, Ho - 2010 mm			
+ 50 mm height - Hs - 2090 mm, Hd - 2107 mm, Ho - 2110 mm			
+ 100 mm height - Hs - 2140 mm, Hd - 2157 mm, Ho - 2160 mm			

STANDARD
door leaf (slab) frame made of top-quality powder-coated steel profiles, metal muntin bars
structural powder paint, structural metal muntin bars
tempered transparent or satin white glass, 4 mm thick
frosted glass on the hinge side
constructional muntins 20 mm wide
double-sided angle bracket in the same colour as the leaf (slab)
leaf (slab) closing magnet
steel angle bracket door frame
metal frame hinges ("60"- "100" - 3 pcs.)
GALIO maximum door height - 2157 mm
ADDITIONAL (available at an extra charge)
colour 053 copper structure
doors with non-standard dimensions

GALIO colours	colour of hinges	colour of glazing gasket (muntin bars)	colour of frame screws
OS1 RAL 9003 (white)	in the colour of the door leaf (slab)	white	white
OS2 RAL 9005 (black)	in the colour of the door leaf (slab)	black	black
OS0 anthracite	in the colour of the door leaf (slab)	anthracite	black
OS3 copper	in the colour of the door leaf (slab)	black	black



STALIO door, S1 version, steel angle bracket door frame

STALIO



Internal doors for use in public utility buildings such as offices as well as for residential units. Internal doors manufactured in accordance with PN-EN 14351-2:2018








lock with handle



hinge




STALIO door, S5 version, steel angle bracket door frame



DIMENSIONS			
WIDTH	Ss	Sd	So
"60"	625	643	646
"70"	725	743	746
"80"	825	843	846
"90"	925	943	946
"100"	1025	1043	1046
Hs - 2040 mm, Hd - 2057 mm, Ho - 2060 mm - 50 mm height - Hs - 1990 mm, Hd - 2007 mm, Ho - 2010 mm + 50 mm height - Hs - 2090 mm, Hd - 2107 mm, Ho - 2110 mm + 100 mm height - Hs - 2140 mm, Hd - 2157 mm, Ho - 2160 mm			

STANDARD	STALIO colours	colour of hinges	colour of glazing gasket (muntin bars)	colour of handle	colour of lock plate	colour of frame screws
door leaf (slab) frame made of top-quality powder-coated steel profiles, metal muntin bars	0S1 RAL 9003 (white)	in the colour of the door leaf (slab)	white	white	silver	white
structural powder paint, structural metal muntin bars	0S2 RAL 9005 (black)	in the colour of the door leaf (slab)	black	black	black	black
tempered transparent or satin white glass, 4 mm thick	0S0 anthracite	in the colour of the door leaf (slab)	anthracite	black	black	black
frosted glass on the hinge side	0S3 copper	in the colour of the door leaf (slab)	black	black	black	black
constructional muntins 20 mm wide						
lock with handle						
steel angle bracket door frame						
metal frame hinges ("60"- "100" - 3 pcs.)						
STALIO maximum door height - 2157 mm						
ADDITIONAL (available at an extra charge)						
colour 0S3 copper structure						
doors with non-standard dimensions						
cylinder in the colour of silver						



LUMEN



LUMEN door, I version, LUMEN adjustable door frame

The door is constructed of a tempered glass pane suspended on the adjustable LUMEN door frame available with a full range of colours: ECO TOP, LAMISTONE CPL, SILKSTONE, laminated and veneered.



handle



hinge



LUMEN door, I version, LUMEN adjustable door frame




VERSION I

width "60" – "80"

width "90"

width "100"

NEW VENTILATION TRIM



LUMEN ADJUSTABLE DOOR FRAME (ZL)



WIDTH

single leaf (slab) door

type	S _o	S _d	S _s	S _{op}
"60"	676	646	617	746
"70"	776	746	717	846
"80"	876	846	817	946
"90"	976	946	917	1046
"100"	1076	1046	1017	1146

HEIGHT


H _o	H _d	H _s	H _{op}
2053	2043	2016	2093

S_s, H_s - door leaf (slab) dimensions

S_d, H_d - door dimensions on the door frame external side

S_o, H_o - recommended installation dimension

S_{op} - architrave external width



LUMEN	ECO TOP	UNI MAT PLUS	for the laminated type	PAINTED* white, beige, grey	BLACK	VENEERED		
			HIGH TOP			GROUP A	GROUP B	GROUP C
			LAMISTONE CPL					
			SILKSTONE					
adjustment range (mm) ZL 75-300								

***Lumen door frame in the PAINTING colour palette is only available with an 80 mm architrave**
Architraves interconnected at 90° are not available.

EQUIPMENT

STANDARD

tempered white/brown/graphite satin or transparent 8 mm thick glass

ornament on the side opposite to the hinges

height of handle for the glass pane standard height – 1040 mm from the glass pane bottom edge

ADDITIONAL (available at an extra charge)

fixed and adjustable metal frame

ventilation trim (p. 159)

glass pane with a non-standard height 1967 mm

electric strike in NC version JiS type 1710 12-24 V AC/DC (including a catch plate and a cut for the electric strike)

electric strike in NC version BIRA HARTE XS12U 12V AC/DC (including a catch plate and a cut for the electric strike)

electric strike in NC version with switch BIRA HARTE XS12UW 12V AC/DC (including a catch plate and a cut for the electric strike)

electric strike in NO version BIRA HARTE XS12R 12V DC (including a catch plate and a cut for the electric strike)

DORMA hardware


DORMA
hardware



aluminium
EV1-Deco 114



aluminium
stainless steel
107



black **

handle + lock + hinges

handle + WB + hinges

handle + WC + hinges


knob type handle + small lock + hinges*

* ref. to the door plus electric strike set


** bottom hinges leaf (slab) is with cpas, top hinges leaf (slab) is painted black

WB – cylinder type

WC – bathroom privacy lock type



LUMEN LOFT



- **tempered 8 mm thick glass**
- **decor in the colour of black or white**

The door is constructed of a tempered glass pane suspended on the adjustable LUMEN door frame available with a full range of colours: ECO TOP, LAMISTONE CPL, SILKSTONE, laminated and veneered.



handle



hinge


LUMEN LOFT door, V4 version, LUMEN adjustable door frame



LUMEN LOFT door, V2 version, LUMEN adjustable door frame



VERSION	V1	V2	V3	V4
		"60" - "80"		"90"



DOOR FRAMES



LUMEN metal
fixed frame

LUMEN metal
adjustable frame

LUMEN
DIN system
adjustable frame

**detailed dimensions of the LUMEN
adjustable frame – p. 125**

EQUIPMENT

STANDARD
8 mm thick, toughened glass with a single black or white screen-printed decoration
height of handle for the glass pane standard height – 1040 mm from the glass pane bottom edge
ADDITIONAL (available at an extra charge)
fixed and adjustable metal frame
ventilation trim
electric strike in NC version JIS type 1710 12-24 V AC/DC (including a catch plate and a cut for the electric strike)
electric strike in NC version BIRA HARTE XS12U 12V AC/DC (including a catch plate and a cut for the electric strike)
electric strike in NC version with switch BIRA HARTE XS12UW 12V AC/DC (including a catch plate and a cut for the electric strike)
electric strike in NO version BIRA HARTE XS12R 12V DC (including a catch plate and a cut for the electric strike)
DORMA hardware

DORMA hardware	aluminium EV1-Deco 114	aluminium stainless steel 107	black **
handle + lock + hinges			
handle + WB + hinges			
handle + WC + hinges			
knob type handle + small lock + hinges*			

* ref. to the door plus electric strike set
** bottom hinges leaf (slab) is with cpas, top hinges leaf (slab) is painted black



FOLDING



Door leaf (slab) constructed of a **wooden rail and stile set** topped with two plain laminated, veneered HDF boards. The standard in-fill is a honeycomb-like layer.




FOLDING door, 00 version, SYSTEM DIN DUO adjustable door frame


pull handle




FOLDING door, 00 version, DIN DUO adjustable door frame



VERSION 00 / V00 00 / V00 double leaf (slab) door




COLOURS



*not applicable to the fixed DUO frame
**not applicable to the adjustable DUO frame

DOOR FRAMES



Folding door DIN DUO door frame							
single leaf (slab) door				double leaf (slab) door			
type	S _o	S _d	S _{op}	type	S _o	S _d	S _{op}
"60"	690	652	792	"60"+"60"	1305	1267	1407
"70"	790	752	892	"70"+"70"	1505	1467	1607
"80"	890	852	992	"80"+"80"	1705	1667	1807
"90"	990	952	1092	"90"+"90"	1905	1867	2007
HEIGHT	H _o		H _d	H _s	H _{op}		
	2085		2079	2040	2133		

Folding door DUO wooden fixed door frame					
single leaf (slab) door			double leaf (slab) door		
type	S _o	S _d	type	S _o	S _d
"60"	713	693	"60"+"60"	1328	1308
"70"	813	793	"70"+"70"	1528	1508
"80"	913	893	"80"+"80"	1728	1708
"90"	1013	993	"90"+"90"	1928	1908
HEIGHT	H _o		H _d	H _s	
	2093		2083	2040	

Folding door DUO wooden adjustable door frame							
single leaf (slab) door				double leaf (slab) door			
type	S _o	S _d	S _{op}	type	S _o	S _d	S _{op}
"60"	713	693	836	"60"+"60"	1328	1308	1451
"70"	813	793	936	"70"+"70"	1528	1508	1651
"80"	913	893	1036	"80"+"80"	1728	1708	1851
"90"	1013	993	1136	"90"+"90"	1928	1908	2051
HEIGHT	H _o		H _d	H _s	H _{op}		
	2093		2083	2040	2154		

Hs - door leaf (slab) height
Sd, Hd - door dimensions on the door frame external side
So, Ho - recommended installation dimension
Sop, Hop - architrave external dimension

EQUIPMENT

STANDARD
guide rail and concealed adjustable hinges in the door leaf (slab)
adjustable concealed hinges "60" - "80" - 2 pcs; "90" - 3 pcs
round plastic pull handle
ADDITIONAL (available at an extra charge)
perforated chipboard in-fill
solid chipboard in-fill (third hinge recommended)

door lower by 55 mm
door higher by 50 mm, 100 mm
door higher by 150 mm, 200 mm
third hinge concealed in the door leaf (slab) DUO for "60"- "80" widths
single-point mortise lock, WB hook type (one leaf (slab) door only)
pull handles for folding door leaves

p. 163



SOUNDPROOF



SOUNDPROOF door, 00 version, SYSTEM DIN adjustable door frame

Single leaf (slab) **SOUNDPROOF** door in the rebated system. The leaf (slab) structure consists of a **rail and stile set made of coniferous wood**, topped with HDF boards on both sides. The in-fill is made of solid chipboard (type A) or the special POL-SKONE structure (type B). Leaf (slab) with a drop down seal.

acoustic insulation:
 with a wooden door frame:
class Rw=27 dB (type A); class Rw=32 dB (type B)
 with a metal door frame:
class Rw=27 dB (type A); class Rw=37 dB (type B)
 with the DIN adjustable door frame:
class Rw=27 dB (type A); class Rw=37 dB (type B)
ITB technical approval: ITB-KOT-2021/2041

Single or double leaf (slab) **SOUNDPROOF DUO** non-rebated door. The leaf (slab) structure consists of a **rail and stile set made of coniferous wood**, topped with HDF boards on both sides. The in-fill is made of solid chipboard (type A) or the special POL-SKONE structure (type B). **The door is available in the single and double leaf (slab) version with a wooden frame (DUO fixed or DUO adjustable).** Leaf (slab) with a drop down seal.

acoustic insulation:
 single and double leaf (slab) door type A – **class Rw=27 dB**
 single leaf (slab) type B – **class Rw=37 dB**
 double leaf (slab) type B – **class Rw=32 dB**
mechanical class: mechanical resistance requirements class 2, i.e. average service conditions
ITB technical approval: ITB-KOT-2021/2041



handle, lock



standard interconnection of architraves at the 45° angle



SOUNDPROOF door, 00 version, SYSTEM DIN adjustable door frame




VERSION 00 / V00

COLOURS



DOOR FRAMES



EQUIPMENT

SOUNDPROOF

STANDARD

single-point key-operated or cylinder type mortise lock spacing 72 mm
adjustable pivot hinges - 3 pcs
in case of door leaf (slab) with door closer and DIN system or metal frame to be used T type hinges ("60"- "80" – 3 pcs, "90" – 4 pcs) - replacement of standard hinges with hinge type T for an extra charge
drop seal
standard width: "80", "90"

ADDITIONAL (available at an extra charge)

size "100"
size "110"
antipanic lever
surface mounted door closer
reinforcement for door closer
electronic locks
electric door strike (reverse or averse action)
decors (Type B version not available with intarsia)
plates with access control systems
door higher by 50 mm or 100 mm
door higher by 150 mm or 200 mm
door higher by 250 mm or 300 mm
(not applicable to the DIN system door frames)
door higher by 350 mm or 400 mm
(not applicable to the DIN system door frames)

p. 163

DUO SOUNDPROOF

STANDARD

concealed hinge (adjustable in 3 planes)
("60" - "70" – 2 pcs; "80" - "90" – 3 pcs)
lock:
single leaf (slab) door - key-operated or cylinder type magnetic lock spacing 85 mm
double leaf (slab) door - key-operated or cylinder type latch lock, 72 mm
drop seal

ADDITIONAL (available at an extra charge)

surface-mounted or concealed door closer
additional mortise or surface-mounted lock
surface-mounted electromagnetic coils by:
ASSA ABLOY, DORMA or GEZE
peephole
door higher by 50 mm or 100 mm
door higher by 150 mm or 200 mm
door higher by 250 mm or 300 mm
door higher by 350 mm or 400 mm

MDF FIXED door frame



single leaf (slab) door


ECO TOP

EXTRA CHARGES

double leaf (slab) type
door frame lower by 50 mm or 100 mm
"100"
"110"

OPTION

LD6 masking strips (available at an extra charge)



WIDTH						
single leaf (slab) door				double leaf (slab) door		
type	S _o	S _d	S _s	type	S _o	S _d
"60"	709	689	618	"60"+"60"	1343	1323
"70"	809	789	718	"60"+"70"	1443	1423
"80"	909	889	818	"60"+"80","70"+"70"	1543	1523
"90"	1009	989	918	"60"+"90","70"+"80"	1643	1623
				"70"+"90","80"+"80"	1743	1723
				"80"+"90"	1843	1823
				"90"+"90"	1943	1923
HEIGHT						
				H _o	H _d	H _s
				2074	2064	2020

S_s - door leaf (slab) width
S_d - door frame external width
S_o - installation hole width

H_s - door leaf (slab) height
H_d - door frame external height
H_o - installation hole height

POL-SKONE FIXED door frame



for the laminated type	PAINTED* white, beige, grey	VENEERED		
HIGH TOP		GROUP A	GROUP B	GROUP C, D
UNI MAT PLUS				
LAMISTONE CPL				
SILKSTONE				


EXTRA CHARGES

door frame lower by 50 mm or 100 mm
door frame higher by 50 mm or 100 mm
door frame higher by 150 mm or 200 mm
"100"
"110"
electric strike in NC version JiS typ 1710 12-24 V AC/DC (including a catch plate and a cut for the electric strike) **
electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a plate and a cut for the electric strike)**
electric strike in NC version with switch BIRA HARTE XS12UW 12V AC/DC (including a catch plate and a cut for the electric strike)**
electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate and a cut for the electric strike)**

OPTION

LD6 masking strip (available at an extra charge)

*environment-friendly acrylic paints, RAL and NCS colours (except metallic ones)
– available at an extra charge according to the colour groups (p. 10)
** for leaves equipped with the ECO Schulte GBS 12 lock - extra charge



WIDTH						
single leaf (slab) door				double leaf (slab) door		
type	S _o	S _d	S _s	type	S _o	S _d
"60"	709	689	618	"60"+"60"	1343	1323
"70"	809	789	718	"60"+"70"	1443	1423
"80"	909	889	818	"60"+"80"; "70"+"70"	1543	1523
"90"	1009	989	918	"60"+"90"; "70"+"80"	1643	1623
"90 plus"	1019	999	928	"70"+"90"; "80"+"80"	1743	1723
				"80"+"90"	1843	1823
				"90"+"90"	1943	1923

HEIGHT			
	H _o	H _d	H _s
	2074	2064	2020

Ss - door leaf (slab) width
Sd - door frame external width
So - installation hole width
Hs - door leaf (slab) height
Hd - door frame external height
Ho - installation hole height



DIN SYSTEM ADJUSTABLE door frame



single
leaf (slab)
door

ECO TOP	UNI MAT PLUS	HIGH TOP
		LAMISTONE CPL
		SILKSTONE
		for the laminated type

ZP, range in mm 75-300

single leaf
(slab) door

PAINTED*
white, beige, grey

VENEERED

GROUP A

GROUP B

GROUP C, D

BLACK

ZP, range in mm 75-300

EXTRA CHARGES

double leaf (slab) type

door frame lower by 50 mm or 100 mm

door frame higher by 50 mm or 100 mm

door frame higher by 150 mm or 200 mm

"100"

"110"

architraves interconnected at the 90° angle
(applies to B 90° and C 90° architraves version)

architraves with a width of 80 mm

electric strike in NC version JiS typ 1710 12-24 V AC/DC (including a catch plate and a cut for the electric strike)**

electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a plate and a cut for the electric strike)**

electric strike in NC version with switch XS12UW 12V AC/DC (including a catch plate and a cut for the electric strike)**

electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate and a cut for the electric strike)**

reinforcement for the arm/guide rail door closer***

replacement of the B type hinge with the K type hinge

three-part T type hinge


crown

p. 157

new way of architraves interconnected - p. 12

Version A: 60 mm (not applicable to the painted door)

Version B: 80 mm



WIDTH

single leaf (slab) door								double leaf (slab) door							
type	So	Sd	Ss	SopA	SopAF	SopB	SopBF	type	So	Sd	SopA	SopAF	SopB	SopBF	
"60"	676	646	618	746	748	786	788	"60"+"60"	1310	1280	1380	1382	1420	1422	
"70"	776	746	718	846	848	886	888	"60"+"70"	1410	1380	1480	1482	1520	1522	
"80"	876	846	818	946	948	986	988	"60"+"80";"70"+"70"	1510	1480	1580	1582	1620	1622	
"90"	976	946	918	1046	1048	1086	1088	"60"+"90";"70"+"80"	1610	1580	1680	1682	1720	1722	
"90 plus"	986	956	928	1056	1058	1096	1098	"70"+"90";"80"+"80"	1710	1680	1780	1782	1820	1822	
								"80"+"90"	1810	1780	1880	1882	1920	1922	
								"90"+"90"	1910	1880	1980	1982	2020	2022	

HEIGHT


	H _o	H _d	H _s	H _{opA}	H _{opB}
	2053	2043	2020	2093	2113
Ss - door leaf (slab) width					
Sd - door frame external width					
So - installation hole width					
Sop - architrave external width					
SopAF - dimension for veneered door frame					
SopBF - dimension for veneered door frame					
SopA - dimension for laminated and painted door frame					
SopB - dimension for laminated and painted door frame					
Hs - door leaf (slab) height					
Hd - door frame external height					
Ho - installation hole height					
Hop - architrave external height					

AQUA DIN ADJUSTABLE door frame




single leaf (slab) door	ECO TOP	HIGH TOP	PAINTED white 001	PAINTED beige, grey	BLACK	VENEERED		
		LAMISTONE CPL				VENEERED GROUP A	VENEERED GROUP B	VENEERED GROUP C
		SILKSTONE						
		UNI MAT PLUS						
		for the laminated type						
ZP, range in mm 75-300								

architraves interconnected at the 45° angle



door frame made of high quality
MDF board characterized by high
resistance to moisture



WIDTH

single leaf (slab) door						double leaf (slab) door				
type	So	Sd	Ss	SopB	SopF	type	So	Sd	SopB	SopF
"60"	676	646	618	786	788	"60"+"60"	1310	1280	1420	1422
"70"	776	746	718	886	888	"60"+"70"	1410	1380	1520	1522
"80"	876	846	818	986	988	"60"+"70", "70"+"70"	1510	1480	1620	1622
"90"	976	946	918	1086	1088	"60"+"90", "70"+"80"	1610	1580	1720	1722
"90 plus"	986	956	928	1096	1098	"70"+"90", "80"+"80"	1710	1680	1820	1822
						"80"+"90"	1810	1780	1920	1922
						"90"+"90"	1910	1880	2020	2022

HEIGHT

	Ho	Hd	Hs	Hop
	2053	2043	2020	2113

Ss - door leaf (slab) width
Sd - door frame external width
So - installation hole width
Sop - architrave external width
SopB - laminated or painted door frame width
SopF - veneered door frame width

Hs - door leaf (slab) height
Hd - door frame external height
Ho - installation hole height
Hop - architrave external height

POL-SKONE SYSTEM

ADJUSTABLE

door frame



single leaf (slab) door	HIGH TOP	VENEERED		
	UNI MAT PLUS			
	LAMISTONE CPL			
	SILKSTONE	GROUP A	GROUP B	GROUP C, D
	for the laminated type			


ZZ, range in mm 62-391

EXTRA CHARGES

door frame lower by 50 mm or 100 mm
door frame higher by 50 mm or 100 mm
door frame higher by 150 mm or 200 mm
double leaf (slab) type
"100"
"110"
electric strike in NC version JiS typ 1710 12-24 V AC/DC (including a catch plate and a cut for the electric strike)*
electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a plate and a cut for the electric strike)*
electric strike in NC version with switch BIRA HARTE XS12UW 12V AC/DC (including a catch plate and a cut for the electric strike)*
electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate and a cut for the electric strike)*
crown
p. 157

Door frames with ranges wider than the maximum ones provided in the table above are available (upon consultation with the Sales Department).

* for leaves equipped with the ECO Schulte GBS 12 - extra charge, architraves are pre-milled to accommodate the electric door strike



WIDTH

single leaf (slab) door					double leaf (slab) door			
type	S _o	S _d	S _s	S _{op}	type	S _o	S _d	S _{op}
"60"	715	695	618	798	"60"+"60"	1350	1330	1433
"70"	815	795	718	898	"60"+"70"	1450	1430	1533
"80"	915	895	818	998	"60"+"80","70"+"70"	1550	1530	1633
"90 plus"	1025	1005	928	1108	"60"+"90","70"+"80"	1650	1630	1733
					"70"+"90","80"+"80"	1750	1730	1833
					"80"+"90"	1850	1830	1933
					"90"+"90"	1950	1930	2033

HEIGHT

H _o	H _d	H _s	H _{op}
2077	2067	2020	2118

S_s - door leaf (slab) width
S_d - door frame external width
S_o - installation hole width
S_{op} - architrave external width

H_s - door leaf (slab) height
H_d - door frame external height
H_o - installation hole height
H_{op} - architrave external height



LUMEN METAL FIXED door frame



Dedicated for the LUMEN glass pane.
Door frame made of 1.5 mm thick sheet metal.

COLOURS

Powder-coated door frame.
Standard colours: white (RAL 9016), white (RAL 9003), grey (RAL 7047), brown (RAL 8014), beige (RAL 1001), graphite (RAL 7024), black (RAL 9005). Other RAL colours are available at an extra charge - upon consultation with the Sales Department (except the metallic and pearl ones)




single leaf (slab) door	
type	"60"÷"90"
FD12 LUMEN	

EXTRA CHARGES

compatible with the electric door strike
door frames in metallic colours (p. 11)
electric strike in NC version JiS typ 1710-12 AC (including a catch plate)
electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a catch plate)
electric strike in NC version with switch BIRA HARTE XS narrow XS12UW 12V AC/DC (including a catch plate)
electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate)

The installation hole must be enlarged for door frames equipped with an electric strike by additional 5 mm.



WIDTH FD12 LUMEN				
single leaf (slab) door				
type	S _o	S _d	S _c	S _s
"60"	681	671	697	617
"70"	781	771	797	717
"80"	881	871	897	817
"90"	981	971	997	917

HEIGHT				
	H _d	H _o	H _c	H _s
	2055	2060	2068	2017

S_s - door leaf (slab) width
S_d - door frame external width
S_o - installation hole width
S_c - total door frame width

H_s - door leaf (slab) height
H_d - door frame external height
H_o - installation hole height
H_c - total door frame height



LUMEN METAL ADJUSTABLE door frame



Dedicated for the LUMEN glass pane.
Door frame made of 1.5 mm thick sheet metal.

COLOURS

Powder-coated door frame.
Standard colours: white (RAL 9016), white (RAL 9003), grey (RAL 7047), brown (RAL 8014), beige (RAL 1001), graphite (RAL 7024), black (RAL 9005). Other RAL colours are available at an extra charge - upon consultation with the Sales Department (except the metallic and pearl ones)




single leaf (slab) door

ZO, range in mm 95-365

EXTRA CHARGES

additional ZOX adjustment system for the rebated adjustable frame (wall width range increase 635 mm)
compatible with the electric door strike
door frames in metallic colours (p. 11)
electric strike in NC version JiS typ 1710-12 AC (including a catch plate)
electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a catch plate)
electric strike in NC version with switch BIRA HARTE XS narrow XS12UW 12V AC/DC (including a catch plate)
electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate)



WIDTH FD61 LUMEN

single leaf (slab) door			
type	So	Sc	Ss
"60"	690	717	617
"70"	790	817	717
"80"	890	917	817
"90"	990	1017	917

HEIGHT

Ho	Hc	Hs
2065	2078	2017

Ss - door leaf (slab) width
So - installation hole width
Sc - total door frame width

Hs - door leaf (slab) height
Ho - installation hole height
Hc - total door frame height



POL-SKONE SYSTEM METAL DIAGONAL **FIXED** door frame



COLOURS

Powder-coated door frame.


Standard colours: white (RAL 9016), white (RAL 9003), grey (RAL 7047), brown (RAL 8014), beige (RAL 1001), graphite (RAL 7024), black (RAL 9005). Other RAL colours are available at an extra charge - upon consultation with the Sales Department (except the metallic and pearl ones)

EXTRA CHARGES

single leaf (slab) door		double leaf (slab) door	
"60"÷"90"	"100" ÷ "110"	"120"÷"150"	"160"÷"200"
FD15 plate thickness: 1.5 mm			
door frame lower by 50 mm or 100 mm			
door frame higher by 50 mm			
door frame higher by 100 mm			
door frame higher by 150 mm			
door frame higher by 200 mm			
reinforcement for the surface mounted door closer			
compatible with the electric door strike			
door frames in metallic colours (p. 11)			
electric strike in NC version JiS typ 1710-12 AC (including a catch plate)*			
electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a catch plate)*			
electric strike in NC version with switch BIRA HARTE XS narrow XS12UW 12V AC/DC (including a catch plate)*			
electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate)*			
hinge M for the metal door frame (width "60"-"80")			
replacement hinge with the T type hinge (width "60"-"80")			

* for leaves equipped with the ECO Schulte GBS 12 - extra charge

Door frame made of the highest quality 1.5 mm thick steel plate.



WIDTH

type	single leaf (slab) door		
	So	Sd	Sc
"60"	700	691	717
"70"	800	791	817
"80"	900	891	917
"90"	1000	991	1017
"90" plus	1010	1001	1027
"100"	1100	1091	1117
"110"	1200	1191	1217

HEIGHT

	Ho	Hc	Hd
	2069	2078	2065

So - installation hole width
Sd - door frame external width
Sc - total door frame width

Ho - installation hole height
Hd - door frame external height
Hc - total door frame height




Approval no. AT-15-9775/2016



HARMONY



Door frame made of the highest quality 1.5 mm thick steel plate.



140

POL-SKONE SYSTEM METAL DIAGONAL ADJUSTABLE door frame

COLOURS

Powder-coated door frame.
Standard colours: white (RAL 9016), white (RAL 9003), grey (RAL 7047), brown (RAL 8014), beige (RAL 1001), graphite (RAL 7024), black (RAL 9005). Other RAL colours are available at an extra charge - upon consultation with the Sales Department (except the metallic and pearl ones)



EXTRA CHARGES

single leaf (slab) door		double leaf (slab) door	
"60"÷"90"	"100" ÷ "110"	"120"÷"150"	"160"÷"200"
D0, range in mm 125-365			
door frame lower by 50 mm or 100 mm			
door frame higher by 50 mm			
door frame higher by 100 mm			
door frame higher by 150 mm			
door frame higher by 200 mm			
reinforcement for the surface mounted door closer			
compatible with the electric door strike			
door frames in metallic colours (p. 11)			
electric strike in NC version JiS typ 1710-12 AC (including a catch plate)*			
electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a catch plate)*			
electric strike in NC version with switch BIRA HARTE XS narrow XS12UW 12V AC/DC (including a catch plate)*			
electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate)*			
hinge M for the metal door frame (width "60"."80")			
replacement hinge with the T type hinge			

* for leaves equipped with the ECO Schulte GBS 12 - extra charge

WIDTH		
single leaf (slab) door		
type	S _o	S _c
"60"	689	717
"70"	789	817
"80"	889	917
"90"	989	1017
"90" plus	999	1027
"100"	1089	1117
"110"	1189	1217
HEIGHT		
	Ho	Hc
	2065	2078


So - installation hole width
Sc - total door frame width

Ho - installation hole height
Hc - total door frame height



Approval no. AT-15-9775/2016

POL-SKONE SYSTEM METAL FIXED door frame



* for leaves equipped with the ECO
Schulte GBS 12 - extra charge

The installation hole must be enlarged for door
frames equipped with an electric strike: by 5 mm
for FD12, by 10 mm for FD14.

Door frame made of the highest quality 1.5 mm
thick steel plate (FD12) and 1.5 mm thick (FD14).



stainless steel threshold

COLOURS

Powder-coated door frame.
Standard colours: white (RAL 9016), white (RAL 9003), grey
(RAL 7047), brown (RAL 8014), beige (RAL 1001), graphite
(RAL 7024), black (RAL 9005). Other RAL colours are
available at an extra charge - upon consultation with the
Sales Department (except the metallic and pearl ones)



	single leaf (slab) door		double leaf (slab) door	
Door frame type	"60"÷"90"	"100" ÷ "110"	"120"÷"150"	"160"÷"200"
FD14 small, FD12 big				

EXTRA CHARGES

door frame lower by 50 mm or 100 mm
door frame higher by 50 mm
door frame higher by 100 mm
door frame higher by 150 mm
door frame higher by 200 mm
stainless steel threshold for the FD12 door frame
reinforcement for the surface mounted door closer
compatible with the electric door strike
door frames in metallic colours (p. 11)
electric strike in NC version JiS typ 1710-12 AC (including a catch plate)*
electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a catch plate)*
electric strike in NC version with switch BIRA HARTE XS narrow XS12UW 12V AC/DC (including a catch plate)*
electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate)*
hinge M for the metal door frame (width "60"- "80")
replacement hinge with the T type hinge

WIDTH FD14				WIDTH FD12			
single leaf (slab) door				double leaf (slab) door			
type	S _o	S _d	S _c	type	S _o	S _d	S _c
"60"	673	633	697	"120"	1307	1267	1331
"70"	773	733	797	"130"	1407	1367	1431
"80"	873	833	897	"140"	1507	1467	1531
"90"	973	933	997	"150"	1607	1567	1631
"90"plus	983	943	1007	"160"	1707	1667	1731
"100"	1073	1033	1097	"170"	1807	1767	1831
"110"	1173	1133	1197	"180"	1907	1867	1931
				"190"	2007	1967	2031
				"200"	2107	2067	2131

HEIGHT				HEIGHT			
	H _d	H _O	H _C		H _d	H _O	H _C
	2036	2046	2068		2055	2060	2068

POL-SKONE SYSTEM METAL ADJUSTABLE door frame



COLOURS

Powder-coated door frame.
Standard colours: white (RAL 9016), white (RAL 9003), grey (RAL 7047), brown (RAL 8014), beige (RAL 1001), graphite (RAL 7024), black (RAL 9005). Other RAL colours are available at an extra charge - upon consultation with the Sales Department (except the metallic and pearl ones)


single leaf (slab) door		double leaf (slab) door	
"60"÷"90"	"100"÷"110"	"120"÷"150"	"160"÷"200"
ZO, range in mm 95-365			

EXTRA CHARGES

additional ZOZ adjustment system for the rebated adjustable frame (wall width range increase 635 mm)
door frame lower by 50 mm or 100 mm
door frame higher by 50 mm
door frame higher by 100 mm
door frame higher by 150 mm
door frame higher by 200 mm
reinforcement for the surface mounted door closer
compatible with the electric door strike
door frames in metallic colours (p. 11)
electric strike in NC version JiS typ 1710-12 AC (including a catch plate)*
electric strike in NC version BIRA HARTE XS narrow XS12U 12V AC/DC (including a catch plate)*
electric strike in NC version with switch BIRA HARTE XS narrow XS12UW 12V AC/DC (including a catch plate)*
electric strike in NO version BIRA HARTE XS narrow XS12R 12V DC (including a catch plate)*
hinge M for the metal door frame (width "60"- "80")
replacement hinge with the T type hinge

* for leaves equipped with the ECO Schulte GBS 12 - extra charge

Door frame made of the highest quality 1.5 mm thick steel plate.



WIDTH									
single leaf (slab) door					double leaf (slab) door				
type	S ₀	S _c	H ₀	H _c	type	S ₀	S _c	H ₀	H _c
"60"	689	717	2065	2078	"120"	1322	1350	2065	2078
"70"	789	817			"130"	1422	1450		
"80"	889	917			"140"	1522	1550		
"90"	989	1017			"150"	1622	1650		
"90"plus	999	1027			"160"	1722	1750		
"100"	1089	1117			"170"	1822	1850		
"110"	1189	1217			"180"	1922	1950		
					"190"	2022	2050		
					"200"	2122	2150		


S₀ - installation hole width
S_c - total door frame width

H₀ - installation hole height
H_c - total door frame height

DUO SYSTEM

FIXED

door frame




HIGH TOP	PAINTED* white, beige, grey	VENEERED		
UNI MAT PLUS		GROUP A	GROUP B	GROUP C, D
LAMISTONE CPL				
SILKSTONE				
for the laminated type				
single leaf (slab) type				
double leaf (slab) type				

EXTRA CHARGES

door frame lower by 55 mm or 100 mm
door frame higher by 50 mm or 100 mm
door frame higher by 150 mm or 200 mm
electric action door strike BIRA HARTE XS narrow with slip (reverse) XS12R-C 12V DC (including SPEC-525 catch plate and a cut for the electric strike)**
electric action door strike BIRA HARTE XS narrow with slip (averse) XS12U-C 12V AC/DC (including SPEC-525 catch plate and a cut for the electric strike)**
electric action door strike BIRA HARTE XS narrow with slip (averse with switch) XS12UW-C 12V AC/DC (including SPEC-525 catch plate and a cut for the electric strike)**

*environment-friendly acrylic paints, RAL and NCS colours (except metallic ones) – available at an extra charge according to the colour groups (p. 10)
** for leaves equipped with the ECO Schulte GBS 12 - extra charge, the installation hole width increased by 25 mm




WIDTH					
single leaf (slab) door			double leaf (slab) door		
type	S _o	S _d	type	S _o	S _d
"60"	713	693	"60"+"60"	1328	1308
"70"	813	793	"60"+"70"	1428	1408
"80"	913	893	"60"+"80", "70"+"70"	1528	1508
"90"	1013	993	"60"+"90", "70"+"80"	1628	1608
"90"plus	1038	1018	"70"+"90", "80"+"80"	1728	1708
			"80"+"90"	1828	1808
			"90"+"90"	1928	1908
HEIGHT					
			H _o	H _d	H _s
			2093	2083	2040

Ss - door leaf (slab) width
Sd - door frame external width
So - installation hole width
Hs - door leaf (slab) height
Hd - door frame external height
Ho - installation hole height

DIN DUO SYSTEM

ADJUSTABLE

door frame



new way of architraves interconnected - p. 12



single
leaf (slab)
door

ECO TOP	UNI MAT PLUS	HIGH TOP
		LAMISTONE CPL
		SILKSTONE
		for the laminated type

ZD, range in mm 75-305

single leaf (slab) door	PAINTED* white, beige, grey	VENEERED			BLACK
		GROUP A	GROUP B	GROUP C, D	

ZD, range in mm 75-305

EXTRA CHARGES

double leaf (slab) type
door frame lower by 55 mm or 100 mm
door frame higher by 50 mm or 100 mm
door frame higher by 150 mm or 200 mm
"100"
"110"
reinforcement for the arm/guide rail door closer***
architraves interconnected at the 90° angle (applies to B 90° and C 90° architraves version)
electric action door strike BIRA HARTE XS narrow with slip (reverse)
XS12R-C 12V DC (including SPEC-525 catch plate and a cut for the electric strike)**
electric action door strike BIRA HARTE XS narrow with slip (averse) XS12U-C 12V
AC/DC (including SPEC-525 catch plate and a cut for the electric strike)**
electric action door strike BIRA HARTE XS narrow with slip (averse with switch)
XS12UW-C 12V AC/DC (including SPEC-525 catch plate and a cut for the electric strike)**
crown
p. 157


The installation door width must be enlarged by 15 mm for the DUO non-rebated system door leaves equipped with the HOBES lock.
Door frames with ranges wider than the maximum ones provided in the table above are available (upon consultation with the Sales Department).

*environment-friendly acrylic paints, RAL and NCS colours (except metallic ones)

- available at an extra charge according to the colour groups (p. 10)

** for leaves equipped with the ECO Schulte GBS 12 - extra charge, the installation hole width increased by 25 mm

***NOTE! The recommended dimension of the installation hole height increased by 16 mm.



WIDTH										
single leaf (slab) door						double leaf (slab) door				
type	So	Sd	Ss	Sop	SopF	type	So	Sd	Sop	SopF
"60"	690	652	625	792	794	"60"+"60"	1305	1267	1407	1409
"70"	790	752	725	892	894	"60"+"70"	1405	1367	1507	1509
"80"	890	852	825	992	994	"60"+"80","70"+"70"	1505	1467	1607	1609
"90"	990	952	925	1092	1094	"60"+"90","70"+"80"	1605	1567	1707	1709
"90 plus"	1015	977	950	1117	1119	"70"+"90","80"+"80"	1705	1667	1807	1809
						"80"+"90"	1805	1767	1907	1909
						"90"+"90"	1905	1867	2007	2009
HEIGHT						H _o	H _d	H _s	H _{op}	
						2075	2063	2040	2133	


Ss - door leaf (slab) width
Sd - door frame external width
So - installation hole width
Sop - architrave external width
SopF - dimension for veneered door frame

Hs - door leaf (slab) height
Hd - door frame external height
Ho - installation hole height
Hop - architrave external height

AQUA DIN DUO

ADJUSTABLE

door frame



single
leaf (slab) door

ECO TOP	UNI MAT PLUS	HIGH TOP
		LAMISTONE CPL
		SILKSTONE
		for the laminated type

ZD, range in mm 75-305

single
leaf (slab) door

PAINTED
white

PAINTED
beige, grey

VENEERED

GROUP A


GROUP B

GROUP C


BLACK

ZD, range in mm 75-305

architraves interconnected at the 45° angle



door frame made of high quality
MDF board characterized by high
resistance to moisture



WIDTH

single leaf (slab) door						double leaf (slab) door				
type	So	Sd	Ss	Sop	SopF	type	So	Sd	Sop	SopF
"60"	690	652	625	792	794	"60"+"60"	1305	1267	1407	1409
"70"	790	752	725	892	894	"60"+"70"	1405	1367	1507	1509
"80"	890	852	825	992	994	"60"+"70", "70"+"70"	1505	1467	1607	1609
"90"	990	952	925	1092	1094	"60"+"90", "70"+"80"	1605	1567	1707	1709
"90 plus"	1015	977	950	1117	1119	"70"+"90", "80"+"80"	1705	1667	1807	1809
						"80"+"90"	1805	1767	1907	1909
						"90"+"90"	1905	1867	2007	2009

HEIGHT

H _o	H _d	H _s	H _{op}
2075	2063	2040	2133


Ss - door leaf (slab) width
Sd - door frame external width
So - installation hole width
Sop - architrave external width
SopB - laminated or painted door frame width
SopF - veneered door frame width

Hs - door leaf (slab) height
Hd - door frame external height
Ho - installation hole height
Hop - architrave external height

DUO SYSTEM

ADJUSTABLE

door frame



single leaf (slab)
door

HIGH TOP	VENEERED		
UNI MAT PLUS			
LAMISTONE CPL			
SILKSTONE	GROUP A	GROUP B	GROUP C, D
for the laminated type			


DI, range in mm 76-388

EXTRA CHARGES

double leaf (slab) type
door frame lower by 55 mm or 100 mm
door frame higher by 50 mm or 100 mm
door frame higher by 150 mm or 200 mm
"100"
"110"
architraves interconnected at the 90° angle
electric action door strike BIRA HARTE XS narrow with slip (reverse) XS12R-C 12V DC (including SPEC-525 catch plate and a cut for the electric strike)*
electric action door strike BIRA HARTE XS narrow with slip (averse) XS12U-C 12V AC/DC (including SPEC-525 catch plate and a cut for the electric strike)*
electric action door strike BIRA HARTE XS narrow with slip (averse with switch) XS12UW-C 12V AC/DC (including SPEC-525 catch plate and a cut for the electric strike)*
crown

p. 157

* for leaves equipped with the ECO Schulte GBS 12 - extra charge
Door frames with ranges wider than the maximum ones provided in the table above are available (upon consultation with the Sales Department).



WIDTH									
single leaf (slab) door					double leaf (slab) door				
type	So	Sd	Ss	Sop	type	So	Sd	Sop	
"60"	713	693	625	836	"60"+"60"	1328	1308	1451	
"70"	813	793	725	936	"60"+"70"	1428	1408	1551	
"80"	913	893	825	1036	"60"+"80","70"+"70"	1528	1508	1651	
"90"	1013	993	925	1136	"60"+"90","70"+"80"	1628	1608	1751	
"90 plus"	1038	1018	950	1161	"70"+"90","80"+"80"	1728	1708	1851	
					"80"+"90"	1828	1808	1951	
					"90"+"90"	1928	1908	2051	
HEIGHT					Ho	Hd	Hs	Hop	
					2093	2083	2040	2154	


Ss - door leaf (slab) width
Sd - door frame external width
So - installation hole width
Sop - architrave external width

Hs - door leaf (slab) height
Hd - door frame external height
Ho - installation hole height
Hop - architrave external height

VERTIGO ADJUSTABLE door frame

ARCHITRAVE AND CROSS RAIL CONNECTION SYSTEM

Wood grain of door frame - vertical (LAMISTONE: 241, 242; SILKSTONE: 293, 294, 295, 296)
Horizontal wood grain (SILKSTONE: 254, 255, 299)
Vertical wood grain (LAMISTONE: 241, 242; SILKSTONE: 293, 294, 295, 296)



single leaf (slab) door

symbol	range in mm	complete set (panel / adjustment architrave) in mm
ZV1	75-80	75/12
ZV2	80-85	80/12
ZV3	85-95	85/16
ZV4	95-120	95/32
ZV5	120-140	120/32
ZV6	140-160	140/32
ZV7	160-180	160/32
ZV8	180-200	180/32
ZV9	200-220	200/32
ZV10	220-240	220/32
ZV11	240-260	240/32
ZV12	260-280	260/32
ZV13	280-305	280/32

UNI MAT PLUS	PAINTED* white, beige, grey	VENEERED			BLACK 9005
LAMISTONE CPL		GROUP A	GROUP B	GROUP C, D	
SILKSTONE					

EXTRA CHARGES

Door frames with ranges wider than the maximum ones provided in the table above are available (upon consultation with the Sales Department).
*environment-friendly acrylic paints, RAL and NCS colours (except metallic ones) – available at an extra charge according to the colour groups (p. 10)
**NOTE! The recommended dimension of the installation hole height increased by 16 mm.
*** for leaves equipped with the ECO Schulte GBS 12 - extra charge, the installation hole width increased by 15 mm

door frame lower by 55 mm or 100 mm

door frame higher by 50 mm or 100 mm

reinforcement for surface mounted door closer**

electric action door strike BIRA HARTE XS narrow with slip (reverse) XS12R-C 12V DC (including SPEC-525 catch plate and a cut for the electric strike)***

electric action door strike BIRA HARTE XS narrow with slip (averse) XS12U-C 12V AC/DC (including SPEC-525 catch plate and a cut for the electric strike)***


electric action door strike BIRA HARTE XS narrow with slip (averse with switch) XS12UW-C 12V AC/DC (including SPEC-525 catch plate and a cut for the electric strike)***

COMPLETE SET PRICE =

VERTIGO DOOR FRAME PRICE + VERTIGO PANEL PRICE

VERTIGO PANEL 1 set (2 pcs)

VERTIGO TOP PANELS HAVE R3 RADIUS ON VERTICAL EDGES IN LAMISTONE, SILKSTONE, UNI MAT PLUS AND PAINTED VERSIONS. IT DOES NOT APPLY TO THE VENEERED VERSION.



UNI MAT PLUS	PAINTED* white, beige, grey	VENEERED			BLACK 9005
LAMISTONE CPL		GROUP A	GROUP B	GROUP C, D	
SILKSTONE					

range in mm 100-1000

WIDTH

single leaf (slab) door						
type	So	Sd	Ss	Sop	SopL	SopF
"60"	690	652	625	793	793	795
"70"	790	752	725	893	893	895
"80"	890	852	825	993	993	995
"90"	990	952	925	1093	1093	1095
"90 plus"	1015	977	950	1117	1118	1120

HEIGHT

H _o	H _d	H _{op}
2082	2070	2353

Ss - door leaf (slab) width
Sd - door frame external width
So - installation hole width
Sop - architrave external width
SopL - door frame dimension on the adjustment side for laminated and painted door frame
SopF - door frame dimension on the adjustment side for veneered door frame
Hs - door leaf (slab) height
Hd - door frame external height
Ho - installation hole height
Hop - panel external height



Approval no. AT-15-9775/2016

POL-SKONE SYSTEM METAL DUO FIXED door frame



NOTE! The DUO metal frame price includes the DUO concealed hinges.

COLOURS

Powder-coated door frame.
Standard colours: white (RAL 9016), white (RAL 9003), grey (RAL 7047), brown (RAL 8014), beige (RAL 1001), graphite (RAL 7024), black (RAL 9005). Other RAL colours are available at an extra charge - upon consultation with the Sales Department (except the metallic and pearl ones)




single leaf (slab) door			double leaf (slab) door		
F93, range in mm 101					
"60"÷"80"	"90"	"100"÷"110"	"60"+"60", "60"+"70", "60"+"80", "70"+"70", "70"+"80"	"90"+"60"	"160"÷"200"
number of concealed hinges	2 pcs.	3 pcs.	3 pcs.	4 pcs.	6 pcs.
				6 pcs.	6 pcs.

EXTRA CHARGES

door frame lower by 55 mm or 100 mm
door frame higher by 50 mm
door frame higher by 100 mm
door frame higher by 150 mm
door frame higher by 200 mm
reinforcement for the surface mounted door closer
compatible with the electric door strike
door frames in metallic colours (p. 11)
electric action door strike BIRA HARTE XS narrow with slip (reverse) XS12R-C 12V DC (including SPEC-576 catch plate and a cut for the electric strike)*
electric action door strike BIRA HARTE XS narrow with slip (averse) XS12U-C 12V AC/DC (including SPEC-576 catch plate and a cut for the electric strike)*
electric action door strike BIRA HARTE XS narrow with slip (averse with switch) XS12UW-C 12V (including SPEC-576 catch plate and a cut for the electric strike)*

* for leaves equipped with the ECO Schulte GBS 12 - extra charge

The installation hole must be enlarged for door frames equipped with an electric strike by additional 5 mm.



WIDTH							
single leaf (slab) door				double leaf (slab) door			
type	So	Sd	Sc	type	So	Sd	Sc
"60"	685	675	701	"120"	1300	1290	1316
"70"	785	775	801	"130"	1400	1390	1416
"80"	885	875	901	"140"	1500	1490	1516
"90"	985	975	1001	"150"	1600	1590	1616
"90"plus	1010	1000	1026	"160"	1700	1690	1716
"100"	1085	1075	1101	"170"	1800	1790	1816
"110"	1185	1175	1201	"180"	1900	1890	1916
				"190"	2000	1990	2016
				"200"	2100	2090	2116
HEIGHT							
				Ho	Hc	Hd	
				2080	2088	2075	

Sd - door frame external width
So - installation hole width
Sc - total door frame width

Hd - door frame external height
Ho - installation hole height
Hc - total door frame width



Approval no. AT-15-9775/2016

POL-SKONE SYSTEM METAL DUO ADJUSTABLE door frame



NOTE! The DUO metal frame price includes the DUO concealed hinges.

COLOURS
Powder-coated door frame.
Standard colours: white (RAL 9016), white (RAL 9003), grey (RAL 7047), brown (RAL 8014), beige (RAL 1001), graphite (RAL 7024), black (RAL 9005). Other RAL colours are available at an extra charge - upon consultation with the Sales Department (except the metallic and pearl ones)




single leaf (slab) door				double leaf (slab) door		
F7, range in mm 110-380						
	"60"÷"80"	"90"	"100"÷"110"	"60"+"60", "60"+"70", "60"+"80", "70"+"70", "70"+"80"	"90"+"60"	"160"÷"200"
number of concealed hinges	2 pcs.	3 pcs.	3 pcs.	4 pcs.	6 pcs.	6 pcs.

EXTRA CHARGES

additional ZOX adjustment system for the rebated adjustable frame (wall width range increase 650 mm)
door frame lower by 55 mm or 100 mm
door frame higher by 50 mm
door frame higher by 100 mm
door frame higher by 150 mm
door frame higher by 200 mm
reinforcement for the surface mounted door closer
compatible with the electric door strike
door frames in metallic colours (p. 11)
electric action door strike BIRA HARTE XS narrow with slip (reverse) XS12R-C 12V DC (including SPEC-576 catch plate and a cut for the electric strike)*
electric action door strike BIRA HARTE XS narrow with slip (averse) XS12U-C 12V AC/DC (including SPEC-576 catch plate and a cut for the electric strike)*
electric action door strike BIRA HARTE XS narrow with slip (averse with switch) XS12UW-C 12V (including SPEC-576 catch plate and a cut for the electric strike)*

* for leaves equipped with the ECO Schulte GBS 12 - extra charge



WIDTH					
single leaf (slab) door			double leaf (slab) door		
type	Sc	So	type	Sc	So
"60"	721	693	"120"	1336	1308
"70"	821	793	"130"	1436	1408
"80"	921	893	"140"	1536	1508
"90"	1021	993	"150"	1636	1608
"90"plus	1046	1018	"160"	1736	1708
"100"	1121	1093	"170"	1836	1808
"110"	1221	1193	"180"	1936	1908
			"190"	2036	2008
			"200"	2136	2108
HEIGHT					
			Ho	Hc	
			2085	2098	

So - installation hole width
Sc - total door frame width

Ho - installation hole height
Hc - total door frame height

REVES SYSTEM

ADJUSTABLE

door frame



single leaf (slab) door	ECO TOP	for the laminated type	PAINTED* white, beige, grey	VENEERED			BLACK
		UNI MAT PLUS					
		HIGH TOP					
		LAMISTONE CPL		GROUP A	GROUP B	GROUP C, D	
		SILKSTONE					

ZW, range in mm 75-295



*RAL and NCS colours - available at an extra charge according to the colour specification table.

EXTRA CHARGES

door frame higher by 100 mm
change of colour of the chrome matt hinge to black (RAL 9005) or white (RAL 9016)

type	Sd	SopA	SopB	Ss	So
"60"	676	766	816	625	705
"70"	776	866	916	725	805
"80"	876	966	1016	825	905
"90"	976	1066	1116	925	1005
"90 plus"	1001	1091	1141	950	1030
"100"	1076	1166	1216	1025	1105

type	Hd	HopA	HopB	Hs	Ho
standard	2088	2133	2158	2053	2105
+50	2138	2183	2208	2103	2155
+100	2188	2233	2258	2153	2205
+200	2288	2333	2358	2253	2305
-55	2033	2078	2103	1998	2050
-100	1988	2033	2058	1953	2005



Ss - door leaf (slab) width
Sd - door frame external width
So - installation hole width
SopA - architrave external width on the hinge side
SopB - architrave external width on the adjustment side

Hs - door leaf (slab) height
Hd - door frame external height
Ho - installation hole height
HopA - architrave external height on the hinge side
HopB - architrave external height on the adjustment side



ADJUSTMENT SYSTEM

MADE OF MDF

FOR FIXED METAL

door frame



Dedicated to:
FD93 non-rebated metal door frame
FD12 rebated metal door frame
Fixed metal door frame for RC3, RC3 INVEST door
Fixed metal door frame for CERBER PLUS, CERBER PLUS RC2 door

COLOURS

FD12, FD93, RC3 fixed metal door frame
Cerber Plus: powder painted in colours from RAL palette
Adjustment system made of MFD: ECO TOP, HIGH TOP, LAMISTONE, SILKSTONE, VENEERED GROUP A, B, C.




single leaf (slab) door	ECO TOP	for the laminated type	VENEERED		
		HIGH TOP	GROUP A	GROUP B	GROUP C, D
		LAMISTONE CPL			
		SILKSTONE			
MA, MB, range in mm 175-415					

EXTRA CHARGES

double leaf (slab) door

(*) the adjustment range includes the thickness of the FD12, CERBER PLUS, RC3 and FD93 door frames
MA: adjustments for FD12, CERBER PLUS, RC3
MB: adjustments for FD93




WIDTH (Ssp)				
single leaf (slab) door				
type	FD12	CERBER PLUS	RC3 RC3 INVEST	FD93
"60"	601	-	-	605
"70"	701	-	701	705
"80"	801	801	801	805
"90"	901	901	901	905
"90 plus"	-	911	921	-
"100"	1001	1001	1001	1005
"110"	1101	-	-	1105
"120"	1201	-	-	1205
HEIGHT (Hsp)				
	2020	2020	2020	2040
A	109	109	112	109

Ssp – panel width within the clear opening

Hsp – panel height within the clear opening

TUNNELS / WALL ENCASEMENTS

VERTIGO TUNNEL DOOR FRAME



WIDTH			
type	S _d	S _o	S _{op}
"60"	656	680	793
"70"	756	780	893
"80"	856	880	993
"90"	956	980	1093
HEIGHT			
	H _d	H _o	
	2071	2085	

PAINTED* white, beige, grey		UNI MAT PLUS	VENEERED			BLACK
		LAMISTONE				
		SILKSTONE	GROUP A	GROUP B	GROUP C, D	
Adjustment range	Range in mm	Complete set of elements				
		Vertical elements				
VT 1	76-96	Panel 76 mm, architrave with tongue 32 mm				
VT 2	96-116	Panel 76 mm, architrave with tongue 32 mm				
VT 3	116-142	Panel 76 mm, architrave with tongue 52 mm				
VT 4	142-182	Panel 142 mm, architrave with tongue 32 mm				
VT 5	182-208	Panel 142 mm, architrave with tongue 52 mm				
VT 6	208-248	Panel 208 mm, architrave with tongue 32 mm				
VT 7	248-274	Panel 208 mm, architrave with tongue 52 mm				
VT 8	274-314	Panel 274 mm, architrave with tongue 32 mm				
VT 9	314-354	Panel 274 mm, architrave with tongue 52 mm				

Net price - main part of the tunnel encasement

*applicable to 80 mm wide architraves

WALL ENCASEMENT FINISH TUNNEL:
ZN (encasement for the on-wall sliding system)
and ZT (wall encasement without door)

ECO TOP	UNI MAT PLUS	PAINTED* white, beige, grey	HIGH TOP	VENEERED		
			LAMISTONE CPL	GROUP A	GROUP B	GROUP C, D
			SILKSTONE for the laminated type			

Adjustment range			Complete set of elements	
On-wall system	Tunnel system	Range in mm	Standard dimensions	
ZN 1	ZT 1	76-116	Panel 76 mm, architrave with tongue 32 mm	
ZN 2	ZT 2	116-142	Panel 76 mm, architrave with tongue 52 mm	
ZN 3	ZT 3	142-182	Panel 142 mm, architrave with tongue 32 mm	
ZN 4	ZT 4	182-208	Panel 142 mm, architrave with tongue 52 mm	
ZN 5	ZT 5	208-248	Panel 208 mm, architrave with tongue 32 mm	
ZN 6	ZT 6	248-274	Panel 208 mm, architrave with tongue 52 mm	
ZN 7	ZT 7	274-314	Panel 274 mm, architrave with tongue 32 mm	
ZN 8	ZT 8	314-354	Panel 274 mm, architrave with tongue 52 mm	


EXTRA CHARGES

non-standard height of tunnels (up to 2300 mm)
double leaf (slab) tunnels dimension "100"+"100"
double leaf (slab) tunnels dimension "110"+"110"
DUO system tunnel door frame
"100"; "110"
architraves interconnected at the 90° angle (applicable to 80 mm wide architraves)
environment-friendly acrylic paints, RAL and NCS colours (except metallic ones) – available at an extra charge according to the colour groups (p. 10)
*applicable to 80 mm wide architraves

ZN, ZN DUO SYSTEM TUNNEL DOOR FRAME (not applicable to DIN DUO)
(wall encasement for the sliding on-wall system)
ZT SYSTEM DIN TUNNEL DOOR FRAME
(wall encasement for DIN door frames without door)

WIDTH									
single leaf (slab) door					double leaf (slab) door				
type	S _d	S _o	S _{op}	S _{op} *	type	S _d	S _o	S _{op}	S _{op} *
"60"	649	670	746	786	"60"+"60"	1282	1305	1379	1419
"70"	749	770	846	886	"70"+"70"	1482	1505	1579	1619
"80"	849	870	946	986	"80"+"80"	1682	1705	1779	1819
"90"	949	970	1046	1086	"90"+"90"	1882	1905	1979	2019
"100"	1049	1070	1146	1186	"100"+"100"	2082	2105	2179	2219
HEIGHT									
	H _d	H _o	H _{op}	H _{op} *					
	2044	2055	2093	2113					

* DUO SYSTEM (not applicable to DIN DUO)




ZT POL-SKONE SYSTEM TUNNEL DOOR FRAME (not applicable to ZT DIN)
(wall encasement without door)

WIDTH							
single leaf (slab) door				double leaf (slab) door			
type	S _d	S _o	S _{op}	type	S _d	S _o	S _{op}
"60"	700	720	797	"60"+"60"	1334	1360	1431
"70"	800	820	897	"60"+"70"	1434	1460	1531
"80"	900	920	997	"60"+"80", "70"+"70"	1534	1560	1631
"90"	1000	1020	1097	"60"+"90", "70"+"80"	1634	1660	1731
"100"	1100	1120	1197	"70"+"90", "80"+"80"	1734	1760	1831
				"80"+"90"	1834	1860	1931
				"90"+"90"	1934	1960	2031
				"100"+"100"	2134	2160	2231
HEIGHT				H _d	H _o	H _{op}	
				2069	2080	2118	

Available only with the colours of natural veneers

ZT tunnel
with the "60" architraves




60 mm wide architraves are not available in the painted version

ZT DIN DUO SYSTEM TUNNEL DOOR FRAME
(wall encasement without door)

WIDTH							
single leaf (slab) door				double leaf (slab) door			
type	S _o	S _d	S _{op}	type	S _o	S _d	S _{op}
"60"	675	655	792	"60"+"60"	1290	1270	1407
"70"	775	755	892	"60"+"70"	1390	1370	1507
"80"	875	855	992	"60"+"80", "70"+"70"	1490	1470	1607
"90"	975	955	1092	"60"+"90", "70"+"80"	1590	1570	1707
				"70"+"90", "80"+"80"	1690	1670	1807
				"80"+"90"	1790	1770	1907
				"90"+"90"	1890	1870	2007
HEIGHT				H _o	H _d	H _{op}	
				2075	2065	2133	


ZT tunnel
with the "80" architraves



ZT tunnel for the DUO SYSTEM door
(wall encasement without door)

WIDTH							
single leaf (slab) door				double leaf (slab) door			
type	S _d	S _o	S _{op}	type	S _d	S _o	S _{op}
"60"	699	720	836	"60"+"60"	1326	1350	1463
"70"	799	820	936	"60"+"70"	1426	1450	1563
"80"	899	920	1036	"70"+"70"	1526	1550	1663
"90"	999	1020	1136	"70"+"80"	1626	1650	1763
				"80"+"80"	1726	1750	1863
				"80"+"90"	1826	1850	1963
				"90"+"90"	1926	1950	2063
HEIGHT				H _d	H _o	H _{op}	
				2085	2095	2154	

ZT tunnel
with the "80" architraves



S_d – door frame external width
S_o – installation hole width
S_{op} – architrave external width


H_d – door frame external height
H_o – installation hole height
H_{op} – architrave external height



TOPLIGHTS

FOR DIN/DIN DUO DOOR FRAME

REBATED SYSTEM





TOPLIGHTS on the DIN door frame profile

(price per 1 meter of the toplight along its external perimeter)

PAINTED* white, beige, grey	ECO TOP	UNI MAT PLUS	for the laminated type	VENEERED		
			HIGH TOP	GROUP A	GROUP B	GROUP C, D
			LAMISTONE CPL			
			SILKSTONE			

NP, range in mm 75-300

toplight price = 1 m price x 2(A+B) + glass 1 sq. m. price x A x B
optional use of 80 mm architraves



Maximum dimension of toplights and sidelights is:

- toplights SxH = 2190x700 mm
- sidelights SxH = 1000x2093 mm

*In case when 80 mm - 140 mm architraves are used

**In case when 80 mm - 80 mm architraves are used

NON-REBATED SYSTEM





TOPLIGHTS on the DIN DUO door frame profile

(price per 1 meter of the toplight along its external perimeter)

PAINTED* white, beige, grey	ECO TOP	UNI MAT PLUS	for the laminated type	VENEERED		
			HIGH TOP	GROUP A	GROUP B	GROUP C, D
			LAMISTONE CPL			
			SILKSTONE			

ND, range in mm 75-300

toplight price = 1 m price x 2(A+B) + glass 1 sq. m. price x A x B



The maximum dimension of toplights and sidelights is:

- topline SxH = 2207x700 mm
- sidelight SxH = 1000x2133 mm

USE THE TOPLIGHT WITH THE FOLLOWING GLASS PANE TYPES:

- A. Security glass pane, white matt 3.3.1, thickness: 6.4 mm
- B. Security glass pane, transparent 3.3.1, thickness: 6.4 mm
- C. White matt tempered glass pane, thickness: 6 mm
- D. Tempered transparent glass pane, thickness: 6 mm

The architraves of the DIN/DIN DUO toplights cannot be provided at an angle of 90°.

Recommended way of connecting toplights along the DIN/DIN DUO door frame by means of installation blocks

*environment-friendly acrylic paints, RAL and NCS colours (except metallic ones) – available at an extra charge according to the colour groups (p. 10)




TOPLIGHTS FOR THE FIXED DOOR FRAME

TOPLIGHTS on the door frame profile:
POL-SKONE fixed (rebated system)
DUO fixed (non-rebated system)
(price per 1 meter of the toplight/sidelight along its external perimeter)


PAINTED* white	for the laminated type	VENEERED		
	UNI MAT PLUS	GROUP A	GROUP B	GROUP C, D
	HIGH TOP			
	LAMISTONE CPL			
	SILKSTONE			
fixed 92 mm				

toplight price = 1 m price x 2(A+B) + glass 1 sq. m. price x A x B

REBATED SYSTEM



NON-REBATED SYSTEM



Recommended method of connecting toplights on the fixed/DUO fixed door frame profile
*environment-friendly acrylic paints, RAL and NCS colours (except metallic ones) – available at an extra charge according to the colour groups (p. 10)




SEMPRE INTERIOR DOOR SIDE PANELS

The side panels are compatible with the models
SEMPRE, SEMPRE LUX (version W02, W03)







PRICE OF DOOR Leaf (slab) WITH INACTIVE Leaf (slab) = 2 x DOOR Leaf (slab) PRICE

WIDTH (rebated system)		
type	Ss with a rebate	Sds
"40"+ "70"	744	431
"50"+ "70"		531
"60"+ "70"		631
"40"+ "80"	844	431
"50"+ "80"		531
"60"+ "80"		631
"40"+ "90"	944	431
"50"+ "90"		531
"60"+ "90"		631

WIDTH (non-rebated system)		
type	Ss	Sds
"40"+ "70"	725	412
"50"+ "70"		512
"60"+ "70"		612
"40"+ "80"	825	412
"50"+ "80"		512
"60"+ "80"		612
"40"+ "90"	925	412
"50"+ "90"		512
"60"+ "90"		612




STRIPS

			ECO TOP	for the laminated type		PAINTED* white	VENEERED		
				UNI MAT PLUS	HIGH TOP		GROUP A	GROUP B	GROUP C, D
				LAMISTONE CPL					
				SILKSTONE					
	OVAL STRIP LC1		symbol	LC1F	LC1F	LC1F	LC1O	LC1O	LC1O
			for the single leaf (slab) door	X	X	X	X	X	X
			for the double leaf (slab) door	X	X	X	X	X	X
	MASKING STRIP LD6		symbol	LD6F	LD6F	LD6F	LD6O	LD6O	LD6O
			for the single leaf (slab) door	X	X	-	X	X	X
			for the double leaf (slab) door	X	X	-	X	X	X
	MASKING STRIP LD10		symbol	LD10F	LD10F	LD10F	LD10O	LD10O	LD10O
			for the single leaf (slab) door	X	X	X	X	X	X
			for the double leaf (slab) door	X	X	X	X	X	X

*environment-friendly acrylic paints, RAL and NCS colours (except metallic ones) – available at an extra charge according to the colour groups (p. 10)

Strips in the following colors: 244 black, 258 white, 276 Polish oak, 295 Royal merbau, 80 mm high, available from stock.


RECOMMENDED CONNECTIONS OF STRIPS



LD10
complete set for the single leaf (slab) door: 2 strips with a length of 2200 mm + 1 strip with a length of 1150 mm; complete set for double leaf (slab) door: 3 strips with a length of 2200 mm;

LC1, LD6
complete set for the single leaf (slab) door: 2 strips with a length of 2150 mm + 1 strip with a length of 1150 mm; complete set for double leaf (slab) door: 3 strips with a length of 2150 mm



BASEBOARDS



Baseboard made of moisture-proof board

PAINTED* white	UNI MAT PLUS	VENEERED		
	LAMISTONE	GROUP A	GROUP B	GROUP C, D
	SILKSTONE			

Baseboards available as 2.6 m long elements.
Minimum order volume for a single colour is 5 elements (1 package).



ABS EDGING



- high mechanical and moisture resistance
- product recommended by specialists
- dedicated to LOFTY, IMPULS, HAPTIC, DECO doors



Due to the edging production process, colour differences between the leaf (slab), frame and edging are possible.

PORTHOLES



size	S ₀	colour
porthole 1 (Ø 240 mm, gr. 18, 40 mm)	135 mm	stainless steel (mat) glass - lacomat
porthole 2 (Ø 320 mm, gr. 18, 40 mm)	215 mm	
porthole 3 (Ø 350 mm, gr. 18, 40 mm)	235 mm	
porthole 4 (Ø 400 mm, gr. 18, 40 mm)	280 mm	

size	S ₀	colour
porthole 2 (Ø 300 mm, gr. 35-45 mm)	225 mm	stainless steel (mat) glass - lacomat
porthole 3 (Ø 350 mm, gr. 35-45 mm)	265 mm	
porthole 4 (Ø 400 mm, gr. 35-45 mm)	295 mm	

size	S ₀	colour
porthole 2 (Ø 300 mm, gr. 35-45 mm)	225 mm	stainless steel (mat) glass - lacomat
porthole 3 (Ø 350 mm, gr. 35-45 mm)	265 mm	
porthole 4 (Ø 400 mm, gr. 35-45 mm)	295 mm	

DOOR MODELS	PORTHOLES ONLY IN FLUSH VERSIONS	NOTES
DECO, HAPTIC	BMD, BMJ, BMN	
DECO LUX	BMD, BMJ, BMN	
ETIUDA version B0	BMD, BMJ, BMN	
ETIUDA LUX version B0		
IMPULS	(BMD, BMJ, BMN) ¹	1) only in the 01 version
INTERSOLID II ²	BMD ¹	1) porthole only with widths of "70", "80" and "90" 2) not applicable to versions 10, 11
INTERSOLID	BMD ¹	1) porthole only with widths of "70", "80" and "90"
MODERN, MODERN DUO	BMD ¹	1) porthole only with widths of "70", "80" and "90"
CAMBIO, CAMBIO DUO	BMD, BMJ, BMN	
INTER-AMBER	BMD, BMJ, BMN	
SIMPLE, SIMPLE DUO	BMD, BMJ, BMN	

Safe mat glass – in standard (not applicable to BMD)
Transparent glass – extra charge (not applicable to BMJ)
chipboard must be ordered if a porthole is to be applied

S₀ - dimension on the internal side of the porthole

CROWNS

for the door frame: DIN SYSTEM "60", DIN SYSTEM "80",
POL-SKONE SYSTEM, DIN DUO SYSTEM, DUO SYSTEM




crown for the single leaf (slab) door for one side




Crown for the "60" - "90" single leaf (slab) door for one side (1 piece)

ECO TOP surface finish
Surface finishes: HIGH TOP, LAMISTONE CPL, SILKSTONE
Painted*
VENEERS GROUP A, GROUP B, GROUP C
EXTRA CHARGES
for the double leaf (slab) door crown "100", "110"

*environment-friendly acrylic paints, RAL and NCS colours (except metallic ones) – available at an extra charge according to the colour groups (p. 10)



CROWN DIMENSIONS		for DIN door frame - Polish standard		for in-wall door housing - Polish standard		for the following door frames: ZN, ZT DIN SYSTEM, ZN DUO SYSTEM (not applicable to DIN DUO) - Polish standard		for the following door frames ZT SYSTEM POL-SKONE - Polish standard		for the following door frames ZT SYSTEM DIN DUO - Polish standard		for the following door frames ZY - Polish standard		for adjustable wooden door frame - Polish standard		for the following door frames DIN DUO (ZD) - Polish standard		for the following door frames ZZ (60 mm pitch) - Polish standard	
		60 mm wide architraves	80 mm wide architraves	60 mm wide architraves	80 mm wide architraves	60 mm wide architraves	80 mm wide architraves	60 mm wide architraves	for the following door frames ZT SYSTEM DIN DUO - Polish standard	for the following door frames ZY - Polish standard	hinge side D1-D16 range	adjustment side D13-D116 range	adjustment side D1-D12 range	for the following door frames DIN DUO (ZD) - Polish standard	hinge side ZZ1-ZZ17 range	adjustment side ZZ4-ZZ11 range	adjustment side ZZ1-ZZ3 range		
for single leaf (slab) door	type	total width of the door frame with a crown Sk (mm)																	
	"60"	823	863	802	842	823	863	874	869	913	913	1013	1003	869	875	865			
	"70"	923	963	902	942	923	963	974	969	1013	1013	1113	1103	969	975	965			
	"80"	1023	1063	1002	1042	1023	1063	1074	1069	1113	1213	1203	1169	1075	1075	1065			
	"90"	1123	1163	1102	1142	1123	1163	1174	1169	1213	1313	1303	1269	1175	1175	1165			
	"90 PLUS"	1133	1173	-	-	-	-	-	-	-	1238	1228	1194	1185	1175				
	"100"	1223	1263	1202	1242	1223	1263	1274	1269	1313	1313	1303	1269	1275	1265				
	"110"	-	-	-	-	1323	1363	1374	1369	-	1413	1403	1369	1375	1365				
for double leaf (slab) door	"60"+"60"	1457	1497	1393	1433	1456	1496	1508	1484	1540	1528	1518	1484	1510	1500				
	"70"+"60"	1557	1597	-	-	-	-	1608	1584	1640	1628	1618	1584	1610	1600				
	"70"+"70"	1657	1697	1593	1633	1656	1696	1708	1684	1740	1728	1718	1684	1710	1700				
	"80"+"60"	1657	1697	-	-	-	-	1708	1684	1740	1728	1718	1684	1710	1700				
	"80"+"70"	1757	1797	-	-	-	-	1808	1784	1840	1828	1818	1784	1810	1800				
	"90"+"60"	1757	1797	-	-	-	-	1808	1784	1840	1828	1818	1784	1810	1800				
	"80"+"80"	1857	1897	1793	1833	1856	1896	1908	1884	1940	1928	1918	1884	1910	1900				
	"90"+"70"	1857	1897	-	-	-	-	1908	1884	1940	2028	1918	1884	1910	1900				
	"90"+"80"	1957	1997	-	-	-	-	2008	1984	2040	2028	2018	1984	2010	2000				
	"90"+"90"	2057	2097	1993	2033	2056	2096	2108	2084	2140	2128	2118	2084	2110	2100				
	"90"+"100"	2157	2197	-	-	-	-	2208	2184	2240	2228	2218	2184	2210	2200				
	"100"+"100"	2257	2197	-	-	2256	2296	2308	2284	2340	2328	2318	2284	2310	2300				
Hk (mm) - total height of the door frame with a crown		2148	2148	2131	2131	2136	2136	2161	2156	2177	2177	2172	2156	2162	2157				



Sk - crown external width
Hk - crown external height

VENTILATION OPTIONS

	plastic tubes T1-T4, T10,T13-T15	plastic tubes T240-T243, T258, T260, T263, T276	plastic tubes T120, T258, T121, T132, T141, T276, T295	plastic tubes T293-T297	ventilation trim standard	ventilation trim SEMPRE	ventilation trim ARCO	ventilation trim FORTIMO / MONA	double ventilation slot	triple ventilation slot	plastic grill	stainless steel grill	bottom rail moisture protection*	NOTES
ARCO, SEDO, VERI, MODO, EGRO			X ²⁾	X ²⁾			X ¹⁾							¹⁾ trim only with the "80" and "90" widths ²⁾ the "60" width comes with 3 tubes as a standard
INTER-AMBER	X		X		X				X		X	X	X	
IMPULS, NOSTRE, INVERNO, SONATA (W1, W2, W5, W7)	X	X		X	X				X		X	X	X	
SONATA (W4, W6)	X	X		X	X				X		X ¹⁾	X ¹⁾	X	¹⁾ ventilation grill only in the standard height version
IMPULS 13	X	X		X	X						X ¹⁾	X ¹⁾		¹⁾ ventilation grill only with the "70", "80" and "90" width models
ETIUDA A01, B1	X	X		X	X						X ¹⁾	X ¹⁾	X	¹⁾ only with the "70", "80" and "90" width models,
ETIUDA B0	X	X		X	X				X		X	X	X	
ESTATO B2, B3	X				X								X	
ETIUDA LUX A01, B1 ESTATO A01, B1 CREATO A01	X				X						X ¹⁾	X ¹⁾	X	¹⁾ only with the "70", "80" and "90" width models
ETIUDA LUX B0	X				X				X		X	X	X	
DECO	X	X		X	X				X		X	X	X	
INTERSOLID, INTERSOLID II	X				X						X ¹⁾	X ¹⁾	X	¹⁾ ventilation grill only in the standard height version
MODERN, MODENA	X				X				X		X ¹⁾	X ¹⁾	X	¹⁾ ventilation grill only in the standard height version
DECO LUX, CAMBIO, SIMPLE, TIARA (W01, W02, W05, W07), SUBLIME	X				X				X		X	X	X	
ESPINA	X				X				X ¹⁾		X	X	X	¹⁾ not applicable to the W01 version
FIORD, TIARA (W03, W04, W06), VERTIGO, VILANO	X				X				X		X ¹⁾	X ¹⁾	X	¹⁾ ventilation grill only for the standard height
LUMEN					X									
PASSO					X									
FOLDING DUO	X	X	X	X										
SONATA LUX, SEMPRE LUX						X ¹⁾				X ¹⁾				¹⁾ only with the "80", "90" widths ²⁾ the "60" width comes with 3 tubes as a standard
SEMPRE		X ²⁾				X ¹⁾				X ¹⁾				¹⁾ only with the "80", "90" widths ²⁾ the "60" width comes with 3 tubes as a standard ³⁾ not applicable to the W05, W07 version
FORTIMO		X ²⁾		X ²⁾			X ¹⁾			X ¹⁾				¹⁾ only with the "80", "90" widths ²⁾ the "60" width comes with 3 tubes as a standard
FORTIMO LUX							X ¹⁾			X ¹⁾				¹⁾ only with the "80", "90" widths ²⁾ the "60" width comes with 3 tubes as a standard
ESTATO LUX A01	X				X						X ¹⁾	X ¹⁾		¹⁾ only with the "70", "80" and "90" width models
HAPTIC					X				X		X	X	X	
TIARA W08 SONATA W8	X			X	X								X	
MONA		X						X ¹⁾		X ¹⁾				¹⁾ trim only with the "80", "90" widths
ETIUDA , ETIUDA LUX, ESTATO, ESTATO LUX, CREATO (Versions A02, A03)					X ¹⁾									¹⁾ only with the "70", "80" and "90" width models A02, A03
FIORI	X	X					X ¹⁾							¹⁾ trim only with the "80" and "90" widths
LOFTY	X	X	X	X	X				X		X	X	X	

*not applicable to door leaves with a ventilation trim
The ventilation options for the DUO collection are to be applied as for the relevant door models

Door width		Door with ventilation trim	Door with ventilation tubes		Door with two rows of ventilation tubes	
		Total cross-section of ventilation holes with the 10 mm clearance maintained [m ²]	Total cross-section of ventilation holes with the 10 mm clearance maintained [m ²]	An additional clearance between door leaf (slab) lower edge and floor is required to fulfil requirements of the regulation* [mm]	Total cross-section of ventilation holes with the 10 mm clearance maintained [m ²]	An additional clearance between door leaf (slab) lower edge and floor is required to fulfil requirements of the regulation* [mm]
REBATED	"60"	0.019	0.009	25**	0.011	20**
	"70"	0.022	0.010	20**	0.012	15**
	"80"	0.026	0.011	15**	0.013	15**
	"90"	0.029	0.012	15**	0.014	10**
	"100"	0.033	0.013	10**	0.015	10**
DUO (NON-REBATED) REVES	"110"	0.036	0.014	10**	0.016	10**
	"60"	0.016	0.009	25**	0.011	20**
	"70"	0.020	0.010	20**	0.012	15**
	"80"	0.024	0.011	15**	0.013	15**
	"90"	0.028	0.012	15**	0.014	10**
LUMEN	"100"	0.032	0.013	10**	0.015	10**
	"110"	0.036	0.014	10**	0.016	10**
	"60"	0.015	-	-	-	-
	"70"	0.019	-	-	-	-
	"80"	0.023	-	-	-	-
ARCO	"90"	0.027	-	-	-	-
	"60"	0.017	-	-	-	-
	"70"	0.021	0.010	20**	-	-
	"80"	0.026	0.011	15**	-	-
	"90"	0.030	0.012	15**	-	-
SEMPRE	"100"	0.034	0.013	10**	-	-
	"60"	0.014	0.009	25**	-	-
	"70"	0.018	0.010	20**	-	-
	"80"	0.023	0.011	15**	-	-
	"90"	0.027	0.012	15**	-	-
FORTIMO	"100"	0.032	0.014	10**	-	-
	"60"	0.016	0.009	25**	-	-
	"70"	0.020	0.010	20**	-	-
	"80"	0.024	0.011	15**	-	-
	"90"	0.028	0.012	15**	-	-

The standard clearance between the door leaf (slab) and the floor is 10 mm.




* According to the Ordinance of the Minister of Infrastructure of 12 April 2002 on the technical conditions which must be fulfilled by buildings and their location. (Journal of Laws, 75 of 2002, item 690 as amended, Journal of Laws no 33 of 2003, item 270, Journal of Laws no 109 of 2004, item 1156), Chapter 6, §. 79. "A bathroom, washroom and separate toilet door should be openable outwards and have, subject to § 75 section 2, at least 0.8 m and a height of 2 m within the clear opening of the door frame and - in the lower part - air inlet holes with a total cross-section area not smaller than 0.022 m²".

** increase the clearance by the specific value by shortening the door leaf (slab) from the bottom side in case when shortening is possible. Self-shortening the door will void the warranty.

Door leaves unavailable for shortening:
- Etiuda, (Etiuda Lux) versions A1-A3
- Sempre version W05 VERSE
Sliding door leaves fulfil requirements of the regulation without the need to add a ventilation trim or ventilation tubes due to their structural design (approximate 20 mm offset from the wall/on-wall system). The ventilation grills and the stainless steel panels with ventilation surface fulfil requirements of the regulation.


VENTILATION OPTIONS

VENTILATION*



ventilation slot in the SEMPRE, INTERSOLID collection leaves- extra charge

ESTATO, ESTADO LUX, CREATO, ETIUDA, ETIUDA LUX "80" (applicable to versions A01-A03)



The standard clearance between the door leaf (slab) and the floor is 10 mm.

* According to the Ordinance of the Minister of Infrastructure of 12 April 2002 on the technical conditions which must be fulfilled by buildings and their location. (Journal of Laws, 75 of 2002, item 690 as amended, Journal of Laws no 33 of 2003, item 270, Journal of Laws no 109 of 2004, item 1156), Chapter 6, §. 79. "A bathroom, washroom and separate toilet door should be openable outwards and have, subject to § 75 section 2, at least 0.8 m and a height of 2 m within the clear opening of the door frame and - in the lower part - air inlet holes with a total cross-section area not smaller than 0.022 m²".

** increase the clearance by the specific value by shortening the door leaf (slab) from the bottom side in case when shortening is possible.

Door leaves unavailable for shortening: ETIUDA (ETIUDA LUX) versions A1-A3; Sempre version W05 VERSE

The sliding door leaves fulfill the requirements of the regulation without the need to add a ventilation trim or ventilation tubes due to their structural design (offset from wall/tunnel by about 20 mm).

VENTILATION OPTIONS

VENTILATION TUBES made of plastic (a set of 4 pcs)



VENTILATION TUBES made of plastic (a set of 4 pcs) - designed to match the door leaf (slab) colour



T292
coffee ash



T121
oak



T132
walnut



T120/T258
white



T159
delano oak



T161
halif oak



T295
English oak



T141
Salinas oak



T276
honey oak



T258
white



T260
white oak



T263
premium walnut



T240
whitewashed
elm



T241
sand elm



T242
grey elm




T243
delano oak



T250
terra oak



T276
Polish oak



T293
Royal anthracite



T294
Royal ash



T295
Royal merbau



T296
Polish ash



T297
Royal nougat



T230
gran oak

The actual colours may vary from the colours printed in this catalogue.
The ventilation tubes do not fulfil the requirements of the Ministerial regulation concerning the cumulative cross-section of the holes for air supply.

VENTILATION OPTIONS

PANEL WITH VENTILATION SURFACE



extra charge "70"
extra charge "80"
extra charge "90", "90 PLUS"
extra charge "100"
extra charge "110"

VENTILATION TUBES*

made of plastic



white



brown



black



beige



grey



anthracite

made of stainless steel



H17 clip fastening
acid resistant, clip fastening

Stainless steel grills and panels are optionally available on request.
The area of air inflow holes is more than 0.022 m².

*** According to the Ordinance of the Minister of Infrastructure of 12 April 2002 on the technical conditions which must be fulfilled by buildings and their location. (Journal of Laws, 75 of 2002, item 690 as amended, Journal of Laws no 33 of 2003, item 270, Journal of Laws no 109 of 2004, item 1156), Chapter 6, §. 79. "A bathroom, washroom and separate toilet door should be openable outwards and have, subject to § 75 section 2, at least 0.8 m and a height of 2 m within the clear opening of the door frame and - in the lower part - air inlet holes with a total cross-section area not smaller than 0.022 m²".**

STAINLESS STEEL 0.6 MM THICK PROTECTORS of leaf (slab) and door frame edges

The vertical leaf (slab) edge protectors can be used for the 40 mm thick leaf (slab) in the LAMISTONE, SILKSTONE, CPL 0.2, CPL 0.5, CPL 0.7 and VENEERED coating. The protectors are suitable only for hinges type T.

TYPE OF PROTECTOR

(vertical protector of the lock side and a vertical protector of the hinge side)

Complete set of the 40 mm thick leaf (slab) protectors

In case of swing doors, the leaf (slab) edge protector is installed on the side opposite to the hinge side.



ACCESSORIES

HINGES FOR INTERIOR DOORS

rebated system



screwed-in B type pivot hinge, silver zinc or brushed nickel

rebated system



screwed-in D type pivot hinge, silver zinc or brushed nickel

rebated system



screwed-in C* type pivot hinge, silver zinc or brushed nickel

rebated system



screwed-in K* type pivot hinge, silver zinc or brushed nickel

rebated system



M type pivot hinge, silver zinc, for the metal door frame

rebated system



hinge with closing function (wooden door frame, fixed or adjustable on one side), silver zinc

*hinges and door frame is a set. If you order to leaf (slab) door only, should order hinges.

rebated system



Three-part T* type hinge, silver, for the DIN SYSTEM door frame

rebated system



Three-part T* type hinge, black, for the DIN SYSTEM door frame

rebated system




Three-part T* type hinge, black, for the metal door frame

non-rebated system



HARMONY* adjustable concealed hinge, satin chrome

non-rebated system



HARMONY* adjustable concealed hinge, white

non-rebated system



HARMONY* adjustable concealed hinge, black (the BLACK collection)

non-rebated system



DUO* adjustable concealed hinge, satin nickel

non-rebated system



DUO* adjustable concealed hinge white

non-rebated system



DUO* adjustable concealed hinge, black (the BLACK collection)

non-rebated system



TE* adjustable concealed hinge, silver

non-rebated system



TE* adjustable concealed hinge, white

non-rebated system



TE* adjustable concealed hinge, black

LOCKS



rebated version



non-rebated version

NEW

HINGE CAPS, Type I (a set of 2 pcs per one hinge)



colours:
golden, chrome,
chrome-matt,
patina, black
Type I caps are used for the C type and K type hinges. A single set of hinge caps consists of two identical caps.

HINGE CAPS, Type II (1 set - 2 pcs)



colours:
white, brown, golden, chrome,
chrome-matt, patina, black
Type II caps are used for the B type and D type hinges. A set of caps per one hinge consists of a short cap (the upper part) and a long cap (the lower part).

ACCESSORIES

AUTOMATIC DOOR CLOSER GEZE TS 2000



closer
colours: silver, white, brown, black

Required reinforcement for automatic door closer and reinforcement under the door frame architrave. Other models of automatic door closers are available upon consultation with the Sales Department.



drop seal

Suitable only for a leaf (slab) with a min. thickness of 40 mm (lower rail and stile set).

HOOK LOCK for sliding doors



WK lock option
chrome, chrome-matt, golden, golden-matt, patina
black




WC lock option
chrome, chrome-matt, golden, golden-matt, patina
black

PULL HANDLES for sliding doors



U1 golden
U2 golden - matt
U3 chrome
U4 chrome - matt
U5 patina
U6 black

124 mm



satin nickel stainless steel

160 mm

150 mm

ENTERO nickel satin for screws
ENTERO nickel satin for screws + WC hook lock
ENTERO II stainless steel + WC lock
ENTERO II stainless steel



satin nickel

Pull handle MAYA
(26.5 x 26.5 cylinder - extra charge)
satin nickel + key lock
satin nickel
satin nickel + hook lock for a cylinder
satin nickel + WC lock

189 mm

PULL HANDLES for folding doors (included in the door leaf (slab) price as a standard)

made of plastic



white beige brown grey

ALUMINIUM DECORS (TIARA, SONATA)



chrome matt (standard)



golden gloss (option)



black (option)



chrome gloss (option)

HANDLES


FOR INTERIOR DOORS



ARCO

split plate

colour	brushed nickel, antique brass
handle	
rosette WK, WB	
rosette WC	



ARCUS

split plate


colour	nickel satin, brushed nickel
handle	
rosette WK	
rosette WC	



LATINO

split plate


colour	stainless steel
handle + rosette WK	
handle + rosette WB	
handle + rosette WC	



MENSA

split plate


colour	chrome, satin chrome
handle	
rosette WK, WB	
rosette WC	



ENCKE

split plate


colour	nickel satin, brushed nickel
handle	
rosette WK, WB	
rosette WC	



PASSO

split plate


colour	nickel-matt, chrome matt
handle	
rosette WK, WB	
rosette WC	



VERSA

split plate

colour	satin chrome, brushed nickel, nickel satin
handle	
rosette WK, WB	
rosette WC	



UNICO

split plate

colour	structural graphite, black matt, white matt
handle	
rosette WK, WB	
rosette WC	





IMAGE-O INOX

split plate


colour	stainless steel
handle	
rosette WK, WB	
rosette WC	



LINEA

split plate


colour	brushed nickel, graphite chrome, glossy chrome
handle	
rosette WK, WB	
rosette WC	



CRUX

split plate

colour	nickel satin, satin chrome
handle	
rosette WK, WB	
rosette WC	



TOPAZ

split plate

colour	stainless steel
handle	
rosette WK, WB	
rosette WC	



BOLD

split plate


colour	stainless steel
handle	
rosette WK, WB	
rosette WC	



AGOSTO

split plate

colour	stainless steel
handle	
rosette WK	
rosette WB	
rosette WC	




AUTUNNO


split plate

colour	brushed nickel, brushed chrome, glossy chrome
handle	
rosette WK, WB	
rosette WC	

		split plate
colour	nickel	
handle		
rosette WK, WB		
rosette WC		


		split plate
colour	glossy chrome, brushed nickel, brushed chrome, black	
handle		
rosette WK, WB		
rosette WC		


		split plate
colour	brushed chrome, brushed nickel	glossy chrome
handle		
rosette WK		
rosette WC		


		split plate
colour	black	
handle		
rosette WK, WB		
rosette WC		


		split plate
colour	black	
handle		
rosette WK, WB		
rosette WC		

		split plate
colour	stainless steel	
handle		
rosette WK, WB		
rosette WC		


		split plate
colour	brushed chrome without insert, black without insert	
handle		
rosette WK		
rosette WC		
The insert in the colour of the door is available. Insert-compatible handle		

		split plate
colour	brushed nickel, brushed chrome, black	
handle		
rosette WK, WB		
rosette WC		


		split plate
colour	glossy chrome, brushed nickel, brushed chrome	
handle		
rosette WK, WB		
rosette WC		

		split plate
colour	stainless steel	
handle		
rosette WK, WB		
rosette WC		

		split plate
colour	stainless steel	
handle		
rosette WK, WB		
rosette WC		

		split plate
colour	chrome/brushed nickel, antique brass	
handle		
rosette WK, WB		
rosette WC		

		split plate
colour	stainless steel	
handle + rosette WK		
handle + rosette WB		
handle + rosette WC		
Handle + rosette HIGRO WC are designed for HIGRO doors only.		

		split plate
colour	chrome/black, chrome/white, satin chrome/black, satin chrome/white	
handle		
rosette WK, WB		
rosette WC		

BERGENIA		split plate
colour	black matt, polished chrome, satin chrom, polished gold, gold matt	
handle		
rosette WK, WB		
rosette WC		


LUPINA		split plate
colour	black matt, polished chrome, satin chrom	
handle	350/430,50	
rosette WK, WB	65/79,95	
rosette WC	100/123,00	

ARNICA		split plate
colour	black matt, polished chrome, satin chrom	
handle		
rosette WK, WB		
rosette WC		

PATINA		split plate
colour	stainless steel	
handle		
rosette WK, WB		
rosette WC		

SATEN		split plate
colour	stainless steel	
handle		
rosette WK, WB		
rosette WC		

ANMI		split plate
colour	golden-matt golden gloss	
handle		
rosette WK, WB		
rosette WC		

	GALE (left, right)	
	long plate spacing: 72 mm	
	colour	chrome, brushed nickel, antique brass
	handle + rosette WK	
	handle + rosette WB	
	handle + rosette WC	
dedicated for doors in the rebated system		

CYLINDERS FOR INTERIOR DOORS

30/35 LOB
30/30 LOB
30/40 LOB
35/30 LOB
26/26 WILKA

CYLINDERS

Lp.	Cylinder size	Manufacturer	Interior door								
			rebated single leaf (slab) type, Type A, Type B	rebated double leaf (slab) type	non-rebated single leaf (slab) type, Type A, Type B	non-rebated with an electric strike	non-rebated double leaf (slab) type	non-rebated double leaf (slab) Type A, Type B, HARMONY INVEST	Harmony, REVES	Lumen	STALIO
1	30x35	LOB	x	x			x				
2	30x30	LOB			x					x	
3	30x40	LOB						x			
4	35x30	LOB				x			x		
5	26x26	Wilka									x

NEW

GALIO
STALIO
LUMEN LOFT



POLAND

Warszawa

Lublin



BUSINESS PARTNER

POL-SKONE Sp. z o.o.

ul. Hanki Ordonówny 8; 20-328 Lublin, Poland

tel.: +48 81 728 52 85; +48 81 744 30 11-13

fax: +48 81 744 24 89; +48 81 744 39 12

e-mail: pol-skone@pol-skone.eu

www.pol-skone.eu

This Product Catalogue is valid from 16.01.2023 (on this day, all earlier POL-SKONE catalogues become invalid).
The present publication does not constitute a commercial offer as defined under applicable laws and is provided for informative purposes only.
The manufacturer reserves right to introduce modifications.