



POL-SKONE®

# FORTO



CHECK DETAILS



V01



V1S



V2S

- **colours** from LAMISTONE CPL, SILKSTONE and UNI MAT PLUS surfaces
- stiles with a thickness of 40 mm made from high-quality MDF, protected against moisture using the **HOT FOIL method**
- crossbars made from high-quality MDF, 35 mm thick
- 16 mm thick MDF panel, vertical wood grain, 4 mm panel horizontal wood grain (wood-like decors)
- single-point lock, spacing: 72 mm (rebated sys.) or magnetic (non-rebated sys.) mortise lock, for key (spacing: 90 mm), for cylinder (spacing: 85 mm) or for bathroom privacy lock (spacing: 90 mm)
- hinges: type B - for DIN system door frame, type D - for wooden door frame, type M - for metal door frame or concealed DUO nickel satin ("70"- "90" – 3 pcs)



price **net**/gross



for leaves with ventilation option



Leaf (slab) **STRUCTURE**  
high quality MDF board



protection of the bottom edge against moisture with special impregnant



"70"- "90"  
SINGLE  
LEAF (SLAB) DOORS



"140"- "180"  
DOUBLE  
LEAF (SLAB) DOORS



SLIDING SYSTEM

INTERIOR DOORS  
RAIL AND STILE TYPE LAMINATED

More information on [www.pol-skone.eu](http://www.pol-skone.eu)