



POL-SKONE®

SLIM



CHECK DETAILS



- **robust structure** made of glued laminated wood
- stiles with a thickness of 40 mm **of glued laminated wood**
- **rails** with a thickness of 35 mm **of glued laminated wood**
- **MDF boards** with a thickness of 22 mm and a highness of 260 mm covered with UNI MAT PLUS, SILKSTONE or LAMISTONE surface
- single-point mortise lock, spacing: 72 mm, for key WK, WB, WC or magnetic mortise lock, for key (spacing: 90 mm), for cylinder (spacing: 85 mm) or for bathroom privacy lock (spacing: WC)
- hinges: type K, brushed nickel - for DIN system door frame, type C, brushed nickel - for wooden door frame, type M - for metal door frame or concealed DUO nickel satin ("60"- "80" - 2 pcs, "90" - 3 pcs)



price **net**/gross



for door leaves with ventilation option



Leaf (slab) STRUCTURE
glued laminated wood



bottom edge of the door
leaf protected with
a special moisture-resistant
impregnant



"60"- "100"
SINGLE
LEAF (SLAB) DOORS



"120"- "180"
DOUBLE
LEAF (SLAB) DOORS



SLIDING SYSTEM



INTERIOR DOORS
RAIL AND STILE TYPE LAMINATED

More information on www.pol-skone.eu