

**POL-SKONE**

DRZWI I OKNA

**DECLARATION OF PERFORMANCE**Nr  
2023/EJ-07W1/141

1. Unique identification code of the product type: EJ-07W1  
2. Intended use or uses: ERIS exterior doors are intended for use in communication in domestic and commercial locations  
3. Producer: POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin  
Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj  
4. Authorised representative: –  
5. System of assessment and verification of constancy of performance: 3  
6a. Harmonised standard: PN-EN 14351-1+A2:2016-10

## Notified bodies:

Instytut Techniki Budowlanej (Notified Body No. 1488) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report.

Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report.

- 6b. European Assessment Document: N/A

## 7. Declared performance:

Essential characteristics		Performance		
Wind load		3		
Test pressure P1 (Pa)		1200 (Pa)		
Wind load		C		
Frame deflection		≤1/300		
Water tightness Unprotected (A)		4A		
Test pressure (Pa)		150 (Pa)		
Load capacity of protective devices		npd		
Acoustic properties $R_w(C;C_{tr})$		npd		
Hazardous substances		not contain		
Type of door		"80"	"90"	"100"
Width and height (opening in frame for external dimension of the door)		801 x 2005 [mm] For door 971 x 2100 [mm]	901 x 2005 [mm] For door 1071 x 2100 [mm]	1001 x 2005 [mm] For door 1171 x 2100 [mm]
Heat insulation	Model:			
	V00, V01, V02, V03, V04, V05	Frame Pine 0,80 (W/m²K) Frame Oak 0,86 (W/m²K)	Frame Pine 0,78 (W/m²K) Frame Oak 0,83 (W/m²K)	Frame Pine 0,76 (W/m²K) Frame Oak 0,81 (W/m²K)
Air permeability		4		
Max. Test pressure (Pa)		600 (Pa)		
Reference air permeability at 100 Pa (m³/h·m²) or (m³/h·m)		3 m³/h·m² 0,75 m³/h·m		
Resistance to burglary		EN 1627 RC2		
Resistance to impact		4		

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer:  
Monika Dudek-Stachal  
Lublin, 01.08.2023.  
(place and date of issue)

DYREKTOR OPERACYJNY

  
mgr Monika Dudek-Stachal

Signature