

DECLARATION OF PERFORMANCE

No. 2021/PC-10PA/80

1. Unique identification code of the product type:

PC-10PA

Intended use or uses:

PATIO ALVERSA TYP C are intended for use in communication in domestic

and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin

Production facility no. 3 in Bilgoraj ul. Zamojska 165, 23-400 Bilgoraj

4. Authorised representative:

System of assessment and verification of constancy of performance:

3

PN-EN14351-1:2006 +A1:2010

6a. Harmonised standard: Notified bodies:

> Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:

6b. European Assessment Document:

N/A

7. Declared performance:

| Essential characteristics | | | Performance |
|--|------|---|---|
| Wind load | | | 2 |
| Test pressure P1 (Pa) | | | (800 Pa) |
| Wind load | | | В |
| Frame deflection | | | (<1/200) |
| Water tightness Unprotected (A) | | | 5A |
| Test pressure (Pa) | | | (200 Pa) |
| Load capacity of protective devices | | | 350 N |
| | | | (wartość progowa) |
| Acoustic properties R _w (C;C _{tr}) (dB) | | | npd |
| Hazardous substances | | | not contain |
| Heat insulation | Pine | The highest value declared for window with undivided pane | npd |
| | | Window with aluminium pane spacer* | npd |
| | | Window with Termo TGI pane spacer* | npd |
| Heat insulation | Oak | The highest value declared for window with undivided pane | npd |
| | | Window with aluminium pane spacer* | npd |
| | | Window with Termo TGI pane spacer* | npd |
| Air permeability Max. Test pressure (Pa) Reference air permeability at 100 Pa (m³/h*m²) or (m³/h*m) | | | 4 (600 Pa) (3m³/h*m²) (0,75m³/h*m) |
| Total atmospheric light transmittance g _n ** | | | 54% |
| Light transmittance Lt** | | | 76% |

^{* -} for window dimensions 2,20 x 2,20 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Monika Dudek-Stachal Lublin, 21.06.2021. (place and date of issue)

Monika Dudek-Stachal Signature

Dyrektor Techniczny

Declaration of Performance is available on www.pol-skone.eu

^{** -} for glazing unit: 4 Float/16 Ar/4 Thermofloat 1,0, Ug=1,0 W/m²K