

## **DECLARATION OF PERFORMANCE**

No 2021/PD-08W1/65

1. Unique identification code of the product type:

PD-08W1

Intended use or uses:

Double sash windows PATIO LIFE DUAL STANDARD are intended for use

in communication in domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin

Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj

4. Authorised representative:

5. System of assessment and verification of constancy of performance:

3

6a. Harmonised standard:

PN-EN14351-1+A2:2016-10

Notified bodies:

Instytut Techniki Budowlanej (Notified Body No. 1488) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test

Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:

6b. European Assessment Document:

N/A

7. Declared performance:

		Performance	
Wind load*			3 1200 (Pa)
Test pressure P1 (Pa) Wind load*			С
Frame deflection			≤1/300 <b>4A</b>
Water tightness Unprotected (A)* Test pressure (Pa)			150 (Pa)
Load capacity of protective devices			npd
Acoustic properties R <sub>w</sub> (C;C <sub>tr</sub> ) (dB)			npd
Hazardous substances			not contain
Heat insulation	Pine	The highest value declared for window with undivided pane	1.2 W/m <sup>2</sup> K
		Window with aluminium pane spacer*	1.1 W/m <sup>2</sup> K
		Window with Termo TGI pane spacer*	1.0 W/m <sup>2</sup> K
Air permeability* Max. Test pressure (Pa) Reference air permeability at 100 Pa (m³/h*m²) or (m³/h*m²) or (m³/h*m²)			4 600 (Pa) 3 m <sup>3</sup> /h*m <sup>2</sup> 0.75 m <sup>3</sup> /h*m
Total atmospheric light transmittance g <sub>n</sub> **			51 %
Light transmittance Lt**			72 %

<sup>\* -</sup> for window dimensions 3.00 X 2.20 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Monika Dudek-Stachal Lublin, 21.06.2021. (place and date of issue)

Signature

Dyrektor Techniczny

Declaration of Performance is available on www.pol-skone.eu

<sup>\*\* -</sup> for glazing unit: Thermofloat 1.1 4mm/10 Ar/Float 4mm/10 Ar/Thermofloat 1.1 4mm, Ug=0,8 W/m²K