

## **DECLARATION OF PERFORMANCE**

No. 2024/IN-05W2/144

1. Unique identification code of the

product type: 2. Intended use or uses:

Double sash windows INTEGRAL are intended for use in communication in

domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj

4. Authorised representative:

5. System of assessment and verification

of constancy of performance:

3

IN-05W2

6a. Harmonised standard:

EN 14351-1:2006+A2:2016

Notified bodies:

Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the

respective test report. 6b. European Assessment Document:

N/A

7. Declared performance:

	Performance		
Wind load			<b>2</b> 800 (Pa)
Test pressure P1 (Pa)			000 (Fa)
Wind load			≤1/300
Frame deflection			≥1/300 9 <b>A</b>
Water tightness Unprotected (A)			
Test pressure (Pa)			(600 Pa)
Load capacity of protective devices			350 N (threshold value)
Acoustic properties** $R_w(C; C_{tr})$ (dB) Total area $\leq 2.7m^2$ $2,7m^2 < Total$ area $\leq 3,6m^2$ $3,6m^2 < Total$ area $\leq 4,6m^2$ $4,6m^2 < Total$ area			34 (-1;-5) dB 33 (-1;-5) dB 32 (-1;-5) dB 31 (-1;-5) dB
Hazardous substances			not contain
Heat insulation	Pine	The highest value declared for window*	1,2 W/m²K
		Value for window dimensions 1.48 X 2.18 m*	0,86 W/m <sup>2</sup> K
Air permeability			Class 4
Total atmosp	heric ligh	41 %	
Light transmittance Lt**			65 %

<sup>\* -</sup> for window with undivided pane

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Lublin, 16.02.2024. (place and date of issue)

Months Durch Bedia

Declaration of Performance is available on www.pol-skone.eu

<sup>\*\*</sup> - for glazing unit: 4mm Thermofloat 1.0 / 16 Ar / Float 4mm / 16 Ar / Thermofloat 1.0 4mm, Ug=0,5  $\,$  W/m $^2$ K