

DRZWIIOKNA

DECLARATION OF PERFORMANCE

No. 2024/NE-05B2/170

 Unique identification code of the product type: NE-05B2

2. Intended use or uses:

Double sash balcony windows with a low threshold ENERGY CONCEPT 92 are intended for use in communication in domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj

4. Authorised representative:

^

5. System of assessment and verification of constancy of performance:

3

6a. Harmonised standard:

EN 14351-1:2006+A2:2016

Notified bodies:

Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report.

6b. European Assessment Document:

N/A

7. Declared performance:

Essential characteristics			Performance
Wind load			npd
Test pressure P1 (Pa)			При
Wind load			npd
Frame deflection			
Water tightness Unprotected (A)			npd
Test pressure (Pa)			
Load capacity of protective devices			npd
Acoustic properties** R _w (C;C _{tr}) (dB)			npd
Hazardous substances			not contain
Heat insulation	Pine	The highest value declared for window*	0,98 W/m²K
		Value for window dimensions 1.48 X 2.18 m*	0,87 W/m ² K
Air permeability			npd
Total atmospheric light transmittance g _n **			41 %
Light transmittance Lt**			65 %

^{* -} for window with undivided pane

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Lublin, 10.05.2024. (place and date of issue) Monika Dudek-Stachal

Monitive Durich - Nechol

Signature

^{** -} for glazing unit: 4mm Thermofloat 1.0 / 18 Ar / Float 4mm / 18 Ar / Thermofloat 1.0 4mm, Ug=0,5 W/m²K