

1. Unique identification code of the product type: DE-10W2
2. Intended use or uses: ELEGANT PLUS exterior doors are intended for use in communication in domestic and commercial locations
3. Producer: POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin  
Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj
4. Authorised representative: –
5. System of assessment and verification of constancy of performance: 3
- 6a. Harmonised standard: PN-EN 14351-1+A2:2016-10
- Notified bodies:  
Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:
- 6b. European Assessment Document: N/A
7. Declared performance:

Essential characteristics		Performance					
Wind load		2					
Test pressure P <sub>1</sub> (Pa)		800 (Pa)					
Wind load		C					
Frame deflection		(≤1/300)					
Water tightness Protected (B)		3 B					
Test pressure (Pa)		100 (Pa)					
Load capacity of protective devices		npd					
Acoustic properties R <sub>w</sub> (C;C <sub>tr</sub> )		npd					
Hazardous substances		not contain					
Type of door		„90+40”	„90+50”	„90+60”	„90+70”	„90+80”	„90+90”
Width and height (opening in frame for external dimension of the door)		1358x2000 [mm] for door 1498x2090 [mm]	1458x2000 [mm] for door 1598x2090 [mm]	1558x2000 [mm] for door 1698x2090 [mm]	1658x2000 [mm] for door 1798x2090 [mm]	1758x2000 [mm] for door 1898x2090 [mm]	1858x2000 [mm] for door 1998x2090 [mm]
Heat insulation	Model D03	Pine – 1,4 (W/m <sup>2</sup> K) Oak – 1,6 (W/m <sup>2</sup> K)					
	Model D04	Pine – 1,8 (W/m <sup>2</sup> K) Oak – 2,1 (W/m <sup>2</sup> K)					
	Model D08	Pine – 1,3 (W/m <sup>2</sup> K) Oak – 1,6 (W/m <sup>2</sup> K)					
Air permeability		4					
Max. Test pressure (Pa)		600 (Pa)					
Reference air permeability at 100 Pa (m <sup>3</sup> /h*m <sup>2</sup> ) or (m <sup>3</sup> /h*m)		3 m <sup>3</sup> /h*m <sup>2</sup> 0,75 m <sup>3</sup> /h*m					
Resistance to impact		3					
Total atmospheric light transmittance g <sub>n</sub> *		49 %					
Light transmittance L <sub>t</sub> *		75 %					

\* - for glazing unit: 44.4 kl. P4A/16 Ar/Thermofloat 1.0 6mm z ciepłą ramką Termo TGI

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer:  
Monika Dudek-Stachal  
Lublin, 21.06.2021.  
(place and date of issue)

Dyrektor Techniczny

*Monika*

mgr. Monika Dudek-Stachal

Signature