

DECLARATION OF PERFORMANCE

No. 2021/PD-10W2/64

1. Unique identification code of the product type:

PD-10W2

Intended use or uses:

4-sash windows PATIO LIFE DUAL STANDARD are intended for use in

communication in domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin

Production facility no. 3 in Bilgoraj ul. Zamojska 165, 23-400 Bilgoraj

4. Authorised representative:

5. System of assessment and verification of constancy of performance:

3

6a. Harmonised standard:

PN-EN14351-1+A2:2016-10

Notified bodies:

Instytut Techniki Budowlanej (Notified Body No. 1488) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test

6b. European Assessment Document:

N/A

7. Declared performance:

Essential characteristics			Performance
Wind load Test pressure P1 (Pa)			2 (800 Pa)
Wind load Frame deflection			C ≤1/300
Water tightness Unprotected (A) Test pressure (Pa)			3A (100 Pa)
Load capacity of protective devices			npd
Acoustic properties R _w (C;C _{tr}) (dB)			npd
Hazardous substances			not contain
Heat insulation	Pine	The highest value declared for window with undivided pane	1.4 W/m ² K
		Window with aluminium pane spacer*	1.3 W/m ² K
		Window with Termo TGI pane spacer*	1.2 W/m ² K
Air permeability Max. Test pressure (Pa) Reference air permeability at 100 Pa (m³/h*m²) or (m³/h*m)			4 600 (Pa) 3 m3/h*m2 0.75 m3/h*3
Total atmospheric light transmittance g _n **			54 %
Light transmittance Lt**			76 %

^{* -} for window dimensions 4.00 X 2.20 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

Dyrektor Techniozny

On behalf of the producer: Monika Dudek-Stachal Lublin, 21.06.2021. (place and date of issue)

Signature

Declaration of Performance is available on www.pol-skone.eu

^{** -} for glazing unit: Float 4mm/16 Ar/Thermofloat 1.0 4mm, Ug=1,0 W/m²K