

1. Unique identification code of the product type: **HP-05W2**
2. Intended use or uses: Windows **HS PANORAMA DUAL schema C** are intended for use in communication in domestic and commercial locations
3. Producer: **POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin**
Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj
4. Authorised representative: –
5. System of assessment and verification of constancy of performance: **3**
- 6a. Harmonised standard: **PN-EN14351-1+A2:2016-10**
Notified bodies:
Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report.
- 6b. European Assessment Document: **N/A**
7. Declared performance:

| Essential characteristics | | | Performance | |
|---|-------------|---|--------------------|----------------|
| Wind load* | | | 2 | |
| Test pressure P1 (Pa) | | | 800 (Pa) | |
| Wind load* | | | C | |
| Frame deflection | | | ≤1/300 | |
| Water tightness Unprotected (A)* | | | 4A | |
| Test pressure (Pa) | | | 150 (Pa) | |
| Load capacity of protective devices | | | npd | |
| Acoustic properties** R _w (C;C _{tr}) (dB) | | | | |
| Total area ≤2.7m ² | | | 29 (-1;-3) dB | |
| 2,7m ² < Total area ≤ 3,6m ² | | | 28 (-1;-3) dB | |
| 3,6m ² < Total area ≤ 4,6m ² | | | 27 (-1;-3) dB | |
| 4,6m ² < Total area | | | 26 (-1;-3) dB | |
| Hazardous substances | | | not contain | |
| Heat insulation | Pine | Schema: | C | |
| | | The highest value declared for window* | 0.90 W/m²K | |
| | | Value for window dimensions 4,00 x 2,20m* | 0.79 W/m²K | |
| Air permeability* | | | Class 4 | |
| Total atmospheric light transmittance g_n | | | 38 %** | 41 %*** |
| Light transmittance L_t | | | 59 %** | 65 %*** |

* - for window with undivided pane

** - for glazing unit: PlanithermOne 4mm/16 Ar/Planiclear 4mm/16 Ar/ PlanithermOne 4mm, Ug= 0,5 W/m²*** - for glazing unit: 4mm Thermofloat 1.0 / 16 Ar / Float 4mm / 16 Ar / Thermofloat 1.0 4mm, Ug=0,5 W/m²K

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

DYREKTOR OPERACYJNY

mgr Monika Dudek-Stachal

On behalf of the producer: **Monika Dudek-Stachal**
Lublin, 16.02.2024.
(place and date of issue)


Signature