

DECLARATION OF PERFORMANCE

No. 2021/AC-08PA/83

1. Unique identification code of the product type:

AC-08PA

Intended use or uses:

PATIO ALVERSA ALU-EFFECT windows are intended for use in

communication in domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin

Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj

4. Authorised representative:

5. System of assessment and verification of constancy of performance:

3

6a. Harmonised standard:

PN-EN14351-1:2006 +A1:2010

Notified bodies:

Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:

6b. European Assessment Document:

N/A

7. Declared performance:

Essential characteristics			Performance
Wind load			2
Test pressure P1 (Pa)			(800 Pa)
Wind load			В
Frame deflection			(<1/200)
Water tightness Unprotected (A)			5A
Test pressure (Pa)			(200 Pa)
Load capacity of protective devices			350 N (thershold value)
Acoustic properties R _w (C;C _{tr}) (dB)			npd
Hazardous substances			not contain
Heat insulation	Pine	The highest value declared for window with undivided pane	npd
		Window with aluminium pane spacer*	npd
		Window with Termo TGI pane spacer*	npd
Heat insulation	Oak	The highest value declared for window with undivided pane	npd
		Window with aluminium pane spacer*	npd
		Window with Termo TGI pane spacer*	npd
Air permeability Max. Test pressure (Pa) Reference air permeability at 100 Pa (m³/h*m²) or (m³/h*m)			4 (600 Pa) (3m³/h*m²) (0,75m³/h*m)
Total atmospheric light transmittance g _n **			52%
Light transmittance L _t **			74%

^{* -} for window dimensions 2,20 x 2,20 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

Dyrektor Techniozny

On behalf of the producer: Monika Dudek-Stachal Lublin, 21.06.2021. (place and date of issue)

Signature

Declaration of Performance is available on www.pol-skone.eu

^{** -} for glazing unit: Thermofloat 1,1 4mm/10 Ar/Float 4mm/10 Ar/Thermofloat 1,1 4mm, Ug= 0,8 W/m²K