

1. Unique identification code of the product type: **PC-08W2**
2. Intended use or uses: Double sash windows **POL – SKONE TYP C** are intended for use in communication in domestic and commercial locations
3. Producer: **POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin**  
 Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj
4. Authorised representative: –
5. System of assessment and verification of constancy of performance: **3**
- 6a. Harmonised standard: **PN-EN 14351-1+A2:2016-10**
- Notified bodies:  
**Instytut Techniki Budowlanej (Notified Body No. 1488)** performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:  
**Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827)** performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:
- 6b. European Assessment Document: **N/A**
7. Declared performance:

Essential characteristics			Performance
Wind load			2
Test pressure P1 (Pa)			(800 Pa)
Wind load			C
Frame deflection			(<1/300)
Water tightness Unprotected (A)			5A
Test pressure (Pa)			(200 Pa)
Load capacity of protective devices			350 N (threshold value)
Acoustic properties** R <sub>w</sub> (C;C <sub>tr</sub> ) (dB)			
Total area ≤2.7m <sup>2</sup>			33 (-1;-5) dB
2,7m <sup>2</sup> < Total area ≤ 3,6m <sup>2</sup>			32 (-1;-5) dB
3,6m <sup>2</sup> < Total area ≤ 4,6m <sup>2</sup>			31 (-1;-5) dB
4,6m <sup>2</sup> < Total area			30 (-1;-5) dB
Hazardous substances			not contain
Heat insulation	Pine	The highest value declared for window with undivided pane	1,5 (W/m <sup>2</sup> K)
		Window with aluminium pane spacer*	1,2 (W/m <sup>2</sup> K)
		Window with Termo TGI pane spacer*	1,1 (W/m <sup>2</sup> K)
Air permeability			4
Max. Test pressure (Pa)			(600 Pa)
Reference air permeability at 100 Pa			(3m <sup>3</sup> /h*m <sup>2</sup> )
(m <sup>3</sup> /h*m <sup>2</sup> ) or (m <sup>3</sup> /h*m)			(0,75m <sup>3</sup> /h*m)
Total atmospheric light transmittance g <sub>n</sub> **			52 %
Light transmittance L <sub>t</sub> **			74 %

\* - for window dimensions 1,48 x 2,18 m

\*\* - for glazing unit: Thermofloat 1.1 4mm/10 Ar/Float 4mm/10 Ar/Thermofloat 1.1 4mm, Ug=0,8 W/m<sup>2</sup>K

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: **Monika Dudek-Stachal**  
 Lublin, 21.06.2021.  
 (place and date of issue)

Dyrektor Techniczny

*mgr Monika Dudek-Stachal*

Signature