

## **DECLARATION OF PERFORMANCE**

No. 2021/EC-05WN2/100

1. Unique identification code of the

product type:

EC-05WN2

2. Intended use or uses:

Double sash windows Energy Concept 90 with vent are intended for use in

communication in domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin

Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj

4. Authorised representative:

5. System of assessment and verification

of constancy of performance:

3

6a. Harmonised standard:

PN-EN 14351-1+A2:2016-10

Notified bodies:

Laboratorium Techniki Budowlanej Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report.

6b. European Assessment Document:

N/A

## 7. Declared performance:

Essential characteristics		Performance
Wind load		3
Test pressure P1 (Pa)		1200 (Pa)
Wind load		С
Frame deflection		≤1/300
Water tightness Unprotected (A)		4A
Test pressure (Pa)		150 (Pa)
Load capacity of protective devices		350 N
		(threshold value)
Acoustic properties R <sub>w</sub> (C;C <sub>tr</sub> ) (dB)		npd
Hazardous substances		not contain
Heat insulation	Window with SGG Swisspacer pane spacer*	npd
Air permeability		4
Max. Test pressure (Pa)		(600 Pa)
Reference air permeability at 100 Pa		(3 m³/h*m²)
(m³/h*m²) or (m³/h*m)		(0,75m <sup>3</sup> /h*m)
Total atmospheric light transmittance g <sub>n</sub> **		38%
Light transmittance Lt**		59%

<sup>\* -</sup> for window dimensions 1,23 x 1,48 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

Dyrektor Techniozny

Lublin, 21.06.2021. (place and date of issue)

On behalf of the producer: Monika Dudek-Stachal

Signature

Declaration of Performance is available on www.pol-skone.eu

<sup>\*\* -</sup> for glazing unit: PlanithermOne 4mm/16 Ar/Planiclear 4mm/16 Ar/ PlanithermOne 4mm, Ug=0,5 W/m²K