

## **DECLARATION OF PERFORMANCE**

No. 2021/EP-05W2/28

1. Unique identification code of the

EP-05W2

product type: 2. Intended use or uses:

Double sash windows EC 90 PLUS are intended for use in communication in

domestic and commercial locations

3. Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj

4. Authorised representative:

System of assessment and verification

of constancy of performance:

3

6a. Harmonised standard:

PN-EN 14351-1+A2:2016-10

Notified bodies:

Instytut Techniki Budowlanej (Notified Body No. 1488) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test

Laboratorium Techniki Budowlanei Sp. Z o.o. (Notified Body No. 1827) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test report:

6b. European Assessment Document:

N/A

7. Declared performance:

|   | Performance |   |   |
|---|-------------|---|---|
| Wind load   |             |   | 2   |
| Test pressure P1 (Pa)   |             |   | 800 (Pa)  |
| Wind load   |             |   | С   |
| Frame deflection  |             |   | ≤1/300  |
| Water tightness Unprotected (A)   |             |   | 1A  |
| Test pressure (Pa)  |             |   | 0 (Pa)  |
| Load capacity of protective devices   |             |   | 350 N<br>(threshold value)  |
| Acoustic properties** R <sub>w</sub> (C;C <sub>tr</sub> ) (dB)                                      |             |   | npd   |
| Hazardous substances  |             |   | not contain   |
| Heat<br>insulation  | Pine        | The highest value declared for window with undivided pane | 0.95 W/m <sup>2</sup> K   |
|   |             | Window with SGG Swisspacer pane spacer*                   | 0.88 W/m <sup>2</sup> K   |
| Air permeability Max. Test pressure (Pa) Reference air permeability at 100 Pa (m³/h*m²) or (m³/h*m) |             |   | 4<br>600 (Pa)<br>3 m <sup>3</sup> /h*m <sup>2</sup><br>0.75 m <sup>3</sup> /h*m |
| Total atmospheric light transmittance g <sub>n</sub> **   |             |   | 60 %  |
| Light transmittance Lt**  |             |   | 77 %  |

<sup>\* -</sup> for window dimensions 1.48 X 2.18 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Monika Dudek-Stachal Lublin, 21.06.2021 (place and date of issue)

mgr Monika Dudek-Stachal Signature

Dyrektor Techniozny

Declaration of Performance is available on www.pol-skone.eu

<sup>\*\* -</sup> for glazing unit: ECLAZ 4mm/16 Ar/Planiclear 4mm/16 Ar/ ECLAZ 4mm, Ug= 0,6 W/m²K