

DECLARATION OF PERFORMANCE

No. 2021/PO-10F/101

Unique identification code of the

product type:

PO-10F

Intended use or uses:

Fixed windows (not openable) EC 90 EX are intended for use in

communication in domestic and commercial locations

Producer:

POL-SKONE Sp. z o.o. ul. Hanki Ordonówny 8, 20-328 Lublin

Production facility no. 3 in Biłgoraj ul. Zamojska 165, 23-400 Biłgoraj

4. Authorised representative:

5. System of assessment and verification of constancy of performance:

3

6a. Harmonised standard:

PN-EN 14351-1+A2:2016-10

Notified bodies:

Instytut Techniki Budowlanej (Notified Body No. 1488) performed determination of the product type by conducting the type examination (based on samples obtained for the tests from the producer) in system 3 and issued the respective test

6b. European Assessment Document:

N/A

7. Declared performance:

Essential characteristics			Performance
Wind load			npd
Test pressure P1 (Pa)			·
Wind load			npd
Frame deflection			54050
Water tightness Unprotected (A)			E1050
Test pressure (Pa)			1050 (Pa)
Load capacity of protective devices			npd
Acoustic properties** R _w (C;C _{tr}) (dB) Total area ≤3.8m ²			46 (-1;-5) dB
Hazardous substances			npd
Heat insulation	Pine	The highest value declared for window with undivided pane	1.4 W/m²K
		Window with Termo TGI pane spacer*	1.2 W/m ² K
Air permeability Max. Test pressure (Pa) Reference air permeability at 100 Pa (m³/h*m²) or (m³/h*m)			4 600 (Pa) 3 m ³ /h*m ² 0.75 m ³ /h*m
Total atmospheric light transmittance g _n **			npd
Light transmittance L _t **			npd

^{* -} for window dimensions 1.23 x 1.48 m

The performance of the aforementioned product is consistent with the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) no. 305/2011 at the sole responsibility of the producer specified hereinabove.

On behalf of the producer: Monika Dudek-Stachal Lublin, 21.06.2021. (place and date of issue)

mgr Manika Dudek-Stachal. . Signature

Dyrektor Techniozny

Declaration of Performance is available on www.pol-skone.eu

^{** -} for glazing unit: 44.2 Thermofloat 1,0 kl.P2A/16 Ar/Pyrobel 16, Ug=1,0 W/m2K